

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 24 SEP 2010		2. REPORT TYPE Final		3. DATES COVERED 10-04-2009 to 10-05-2010	
4. TITLE AND SUBTITLE Study on Active Terahertz Metamaterials			5a. CONTRACT NUMBER FA23860914031		
			5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Taiichi Otsuji			5d. PROJECT NUMBER		
			5e. TASK NUMBER		
			5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Tohoku University,2-1-1 Katahira, Aoba-ku,Sendai, Miyagi 980-8577,Japan,NA,NA			8. PERFORMING ORGANIZATION REPORT NUMBER N/A		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AOARD, UNIT 45002, APO, AP, 96337-5002			10. SPONSOR/MONITOR'S ACRONYM(S) AOARD		
			11. SPONSOR/MONITOR'S REPORT NUMBER(S) AOARD-094031		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT In this program the grantee investigated terahertz radiation sources and modulators formed by active metamaterials made with the grantee's original interdigitated grating gate (DGG) structures on HEMT device layers. The principle of operation is the 2DPs which are confined into artificial dimensions of metamaterial structure in a HEMT and are electrically or optoelectronically excited to seed the electromagnetic radiation.					
15. SUBJECT TERMS Terahertz Radiation, Heterostrucuture Semiconductor					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Final Report

Project: AOARD-09-4031 “Study on Active Terahertz Metamaterials”

May 31, 2010

Name of Principal Investigator: Taiichi Otsuji

- e-mail address : otsuji@riec.tohoku.ac.jp
- Institution : RIEC: Research Institute of Electrical Communication, Tohoku University
- Mailing Address : 2-1-1 Katahira, Aoba-ku, Sendai, Miyagi, 980-8577, Japan
- Phone : +81-22-217-6104
- Fax : +81-22-217-6104

Award No.: FA2386-09-1-4031

Period of Performance: 13 months from April 10, 2009

Title: Study on Active Terahertz Metamaterials

Background: “Metamaterial” is defined as an artificially structured electromagnetic material exhibiting extraordinary response to the electromagnetic radiation that is hardly performed in natural fashions. Study on “metamaterial” is now one of the emerging science and engineering fields [1-3]. “Terahertz” staying in between radio and optical frequencies is still an unexplored, but now becoming one of the hottest frequency bands [4] to creating new “active” metamaterial systems [5]. In [5], Chen et al., first demonstrated an “active” transmittance control by 50% of terahertz radiation by implementing an arrayed semiconductor metamaterial structure including Schottky diodes. This is an excellent first-step ignition, but fundamental improvements/breakthroughs are necessary to explore deeper science and technology hidden behind the presence. On such a background, two dimensional plasmons (2DPs) in submicron transistors have attracted much attention due to their nature of promoting emission/detection/manipulation of electromagnetic radiation in the terahertz range [6-10].

Results obtained: In this program the grantee investigated terahertz radiation sources and modulators formed by active metamaterials made with the grantee’s original interdigitated grating gate (DGG) structures on HEMT device layers. The principle of operation is the 2DPs which are confined into artificial dimensions of metamaterial structure in a HEMT and are electrically or optoelectronically excited to seed the electromagnetic radiation. The basic structure of the grantee’s original is focused on (see Fig. 1) and to be improved so as to enhance the radiation power and to realize coherent, monochromatic radiation. To realize coherent monochromatic terahertz radiation and wavelength selectivity, currently installed vertical cavity structure was improved (see Fig. 2); the cavity Q factor should be drastically enhanced. The device process has been carried out at our own, the Laboratory for Nanoelectronics and Spintronics in RIEC. Together with the high Q cavity installation, injection-locking by photomixed dual-laser irradiation was pursued to realize THz emission of coherent monochromatic radiation. Up to now high reflectivity >90% up to 4.5 THz was confirmed from the fabricated samples (see Fig. 3). Verification and characterization of real operation is now undertaken. In terms of the intensity modulators, the controllability of the transmittance of the 2D plasmonic plane in the DGG-HEMT was numerically analyzed. The finite difference time domain analysis demonstrates that the coupling of THz electromagnetic waves and 2DPs changes with the electron drift velocity and with the sheet electron density in 2DPs (see Fig. 4). The analysis also reveals that the intensity of transmitted waves can be modulated over a wide THz range with an extinction ratio beyond 60% by optimizing the sheet electron density and the drift velocity under nominal area-factor condition (ratio of the 2DP area over the total active channel area) up to 0.6 [11].




Fig. 1. GaAs-based plasmonic Emitter: structure, SEM image, FTIR setup, and measured spectra.




Fig. 2. Schematic view of the high-Q vertical cavity installed in a DGG-HEMT.




Fig. 3 Transmittance of the fabricated device measured by FTIR. PW-1500 is the case of the real device where ITO is coated on PW-1500 dielectric material coated on a GaAs substrate, showing high reflectivity (low transmittance).




Fig. 5. Transmittance spectra of a DGG-HEMT for various electron drift velocities: v_d and sheet electron density: n_s .




Fig. 6. DGG-HEMT intensity modulator.

References:

- [1] V.G. Veselago, "The electrodynamics of substances with simultaneously negative values of ϵ and μ ," Sov. Phys. Uspekhi **10**, 09-514 (1968).
- [2] J. Pendry and D. Smith, "The quest for the super lens," Sci. American **295**, 60-67 (2006).
- [3] N. Engheta and R.W. Ziolkowski eds., "Metamaterials, Physics and Engineering Explorations," John Wiley & Sons, Inc., NJ, USA, (2006).
- [4] M. Tonouchi, "Cutting-edge terahertz technology," Nature Photon. **1**, 97-105(2007).
- [5] H.-T. Chen, W.J. Padilla¹, J. M.O. Zide, A.C. Gossard, A.J. Taylor and R.D. Averitt, "Active terahertz metamaterial devices," Nature **444**, 597-600(2006).
- [6] M. Dyakonov, and M. Shur, "Shallow water analogy for a ballistic field effect transistor: new mechanism of plasma wave generation by dc current," Phys. Rev. Lett. **71**, 2465-2468 (1993).
- [7] T. Otsuji, M. Hanabe, T. Nishimura and E. Sano, "A grating-bicoupled plasma-wave photomixer with resonant-cavity enhanced structure," Opt. Express **14**, 4815-4825 (2006).
- [8] T. Otsuji, Y. M. Meziani, T. Nishimura, T. Suemitsu, W. Knap, E. Sano, T. Asano, V.V. Popov, "Emission of terahertz radiation from dual-grating-gates plasmon-resonant emitters fabricated with InGaP/InGaAs/GaAs material systems," J. Phys.: Condens. Matter **20**, 384206 (2008).
- [9] T. Nishimura and T. Otsuji, "Terahertz polarization controller based on electronic dispersion control of 2D plasmons," International Journal of High Speed Electronics and Systems **13**, 547-555 (2007).
- [10] T. Nishimura, M. Hanabe, M. Miyamoto, T. Otsuji and E. Sano, "Terahertz frequency multiplier operation of 2-D plasmon-resonant photomixer," IEICE Trans. Electron. **E89-C**, 1005-1011 (2006).
- [11] T. Nishimura, N. Magome, and T. Otsuji, "An intensity modulator for terahertz electromagnetic waves utilizing two-dimensional plasmon resonance in a dual-grating-gate high-electron-mobility transistor," Jpn. J. Appl. Phys. **49**, 054301 (2010).