

Performance of Self-Adaptive Techniques for Multi-Static, Concurrent Detection, Classification and Localization of Targets in Shallow Water Using Distributed Autonomous Sensor Networks

Karim G. Sabra,
School of Mechanical Engineering, Georgia Institute of Technology
Atlanta, GA 30332
Phone: (404) 385-6193 Fax(404) 894-1658 E-mail: karim.sabra@me.gatech.edu

Award number: N00014-08-1-0087

LONG TERM GOALS

To develop coherent space-time-frequency processing algorithms to enhance the multi-static concurrent detection, classification and localization of proud and buried targets in shallow ocean waveguides using distributed autonomous sensor networks.

OBJECTIVE

The proposed Georgia Institute of Technology (GIT) research effort will develop coherent space-time-frequency processing techniques to enhance the resonant acoustic signatures of man-made targets (e.g. elastic shells) recorded on various nodes of an autonomous distributed sensor network. Both the issues of 1) time-frequency shift of the acoustic signatures across the sensing aperture and 2) convolution of the target echoes with the multipath response of the shallow water sound channel, will be addressed.

APPROACH

These space-time-frequency signal processing techniques will be applied to the analysis of the 3D multistatic acoustics collected during the SWAMSI experiment conducted in March-April 2009 in Panama City collected either on a vertical-receive array (VRA), or on a synthetic-aperture horizontal receive array (S-HRA) created from an AUV track. The 3D multistatic acoustics of seabed targets in shallow water will also be investigated numerically using the simulation frameworks developed in collaboration with MIT and NATO Undersea Research Centre, including 3D target scattering in ocean waveguides, seafloor reverberation and time-reversal acoustics for various sensor array configuration

The proposed GTech research effort will develop robust coherent space-time-frequency processing algorithms for analyzing the 3D multistatic acoustic signatures of seabed targets in shallow water in collaboration with MIT and MPL/SIO,

Report Documentation Page			Form Approved OMB No. 0704-0188		
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2009		2. REPORT TYPE Annual		3. DATES COVERED 00-00-2009 to 00-00-2009	
4. TITLE AND SUBTITLE Performance Of Self-Adaptive Techniques For Multi-Static, Concurrent Detection, Classification And Localization Of Targets In Shallow Water Using Distributed Autonomous Sensor Networks				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Georgia Institute of Technology,School of Mechanical Engineering,Atlanta,GA,30332				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES Code 1 only					
14. ABSTRACT To develop coherent space-time-frequency processing algorithms to enhance the multi-static concurrent detection, classification and localization of proud and buried targets in shallow ocean waveguides using distributed autonomous sensor networks.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

WORK COMPLETED and PRELIMINARY RESULTS




Figure 1: a) Bistatic response of an elastic shell (shell is 1m diameter, 1.5 cm thick steel) in the frequency-angle domain (“Acoustic color”). The angular variable measures the angular spacing between the source and receiver location. Note the strong coincidence pattern at $\theta=180^\circ$ (monostatic direction). b) Time-angle representation of the same bistatic response (“Sinogram”). The first wavefront correspond to the specular echoe and is followed by successive wavefronts corresponding the shell elastic resonances (S_0, A_0) circling around the shell. c) Time-frequency analysis of the backscatter response of an elastic shell (monostatic response, i.e. $\theta=180^\circ$). Note the various strong resonances (narrowband) appearing beyond the firstg broadband specular echo. The locations of these resonances vary in the time-frequency plan

For underwater sonar, time-frequency analysis and, in particular Wigner-Ville analysis, has been shown to be a relevant tool for discriminating a man made target (shell) from a natural one of the same shape (solid) and even to estimate some target characteristics (shell thickness, shear velocity..). This processing tool takes advantage of the evolutionary, time dependent aspect of the echo spectrum (see Fig. 1.c). The estimated time-frequency patterns can be used for detection and wideband classification of sonar echoes in order to reduce false alarms. In particular, the so-called "coincidence pattern" appearing for specific frequency range is a robust time-frequency signature of man-made shells (see Fig. 1.c). Indeed, the source-receiver configuration, target geometry (e.g. shell thickness) and medium parameters (e.g. sound speed, density) influence the evolution of the time-frequency signatures of these scattered echoes. Hence, in practice, the time-frequency content of each structural echoes of the surveyed target (e.g. Fig. 1) will vary for each of the selected multistatic source-receiver pairs or configurations.

A space-time-frequency analysis allows understanding the echo formation mechanisms and their bistatic evolution, as illustrated for instance in Fig .2. Most importantly the energetic coincidence

pattern (resulting from the interactions of A0+ and A0- waves) appears to vary in the time-frequency plan when bi-static receiver angles changes. This occur since the A0+ and A0- waves shift and separate as path lengths to the receiver vary for bi-static receiver angles (see Fig. 2). Hence a coherent processing of the various echoes of the spherical shell will not be possible using conventional approach limited to the frequency domain (e.g. conventional time-delay beamforming) since the frequency content of the echoes is not constant. Instead the full space-time-frequency coherence of the echoes need to be combined to enhance detection with respect to surrounding ambient noise and reverberation due to clutter. One implemented approach is to correct for both estimated time-delay and frequency shift of the coincidence pattern (time-frequency beamforming using companded signals)

Consequently, this space-time-frequency variations of the 3D multistatic acoustics signature of elastic shells is especially challenging for concurrent DCL using conventional broadband coherent processing techniques (e.g. time-delay beamforming) since the scattered echoes are not simply a time-delayed version of each others. Hence generalized coherent space-time-frequency signal processing algorithms need to be developed to enhance the extraction of the structural echoes vs. ambient noise or clutter.




Figure 2: Splitting of the bistatic time-frequency signature of the elastic shell in two patterns (#1 and #2) corresponding to the two coherent interference of A0+ and A0- waves when their path lengths around the sphere vary (bistatic configuration). Measurements of time-delay and frequency shift of the coincidence pattern vs. bistatic angle.

IMPACT

This work is focused on developing potential MCM procedures to improve multistatic concurrent Detection, Classification and Localization of elastic target by investigating the full space-time-frequency coherence of their echoes.

PUBLICATIONS

“Time-frequency analysis of the bistatic response of elastic spherical shells” S. Anderson, K. G. Sabra.
Paper in preparation.