

# AIRBLAST EQUIVALENT WEIGHTS OF VARIOUS EXPLOSIVE CHARGE SHAPES FOR TESTING STRUCTURES

*Michael M. Swisdak, APT Research, Inc, 4950 Research Drive, Huntsville, AL 35805. Phone: +1-301-908-8272; FAX: +1-256-837-7786, E-mail: [MSwisdak@APT-Research.com](mailto:MSwisdak@APT-Research.com)*

*Lippe D. Sadwin, Sadwin Engineering Consultancy, Kefar Pines 37920 Israel. E-mail: [ldsadwin@netvision.net.il](mailto:ldsadwin@netvision.net.il) WEB: [www.sadwin-explosives.com](http://www.sadwin-explosives.com)*

## ABSTRACT

The testing of various security-related and civilian protective structures is often done with explosive charges having cylindrical and other shapes. At long ranges, the characteristics of the blast wave are hardly affected by a complex charge configuration. However, at scaled distances between the charge and test structures, which are less than about  $7 \text{ m/Kg}^{1/3}$ , there exists the phenomenon of blast wave enhancement relative to the more conventional hemispherical or spherical charge shapes. This effect can be put to advantage using the airblast analysis tool of an Equivalent Weight concept. Relatively large Equivalent Weight factors based on actual test data are presented thus providing a useful engineering tool to the Explosion Testing designer.

## CV

Mr. Swisdak is a Senior Scientist in the Explosives Event Modeling and Testing Group at APT Research, Inc, headquartered in Huntsville, AL. He recently retired from the Department of Defense after 45 years of service. His specialties include airblast, explosion-produced debris, and its effect on explosive-safety quantity-distance. He is the author or co-author of over 145 technical publications in these fields. He holds a Master of Science degree in Physics from the University of Florida.

Mr. Sadwin, in the field of Explosives and Explosions since 1959, has been an independent Engineering Consultant in this specialty since 1991. He and his team have conducted numerous instrumented full scale explosion tests on structures designed to resist blast. In addition, he has developed a unique graduate level course at the Ben Gurion University entitled "Energetic Explosive Materials". His R&D work has appeared in the form of over 200 Engineering Reports and professional papers.

# Report Documentation Page

Form Approved  
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE <b>JUL 2010</b>		2. REPORT TYPE <b>N/A</b>		3. DATES COVERED <b>-</b>	
4. TITLE AND SUBTITLE <b>Airblast Equivalent Weights Of Various Explosive Charge Shapes For Testing Structures</b>				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) <b>APT Research, Inc, 4950 Research Drive, Huntsville, AL 35805</b>				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT <b>Approved for public release, distribution unlimited</b>					
13. SUPPLEMENTARY NOTES <b>See also ADM002313. Department of Defense Explosives Safety Board Seminar (34th) held in Portland, Oregon on 13-15 July 2010, The original document contains color images.</b>					
14. ABSTRACT <b>The testing of various security-related and civilian protective structures is often done with explosive charges having cylindrical and other shapes. At long ranges, the characteristics of the blast wave are hardly affected by a complex charge configuration. However, at scaled distances between the charge and test structures, which are less than about <math>7 \text{ m/Kg}^{1/3}</math>, there exists the phenomenon of blast wave enhancement relative to the more conventional hemispherical or spherical charge shapes. This effect can be put to advantage using the airblast analysis tool of an Equivalent Weight concept. Relatively large Equivalent Weight factors based on actual test data are presented thus providing a useful engineering tool to the Explosion Testing designer.</b>					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT <b>unclassified</b>	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE <b>unclassified</b>			

## OBJECTIVE

During the full scale testing of targets or structures designed to resist airblast, cylindrical charges, often of cast TNT, are frequently used since they are more easily fabricated than spherical or hemispherical charges. The cylindrical shape, although azimuthally symmetrical, can strongly influence the airblast performance of both peak pressure and positive impulse, at close ranges. In fact, due to the unique behavior of the airblast produced by cylindrical detonations, both enhanced and degraded performance relative to that of spheres or hemispheres is possible.

Cylindrical charge airblast performance information is presented in Reference 1 in graphical form. In this reference, data are presented for various length to diameter (L/D) ratios from vertical, bottom end-initiated cylinders detonated in free-air and from surface burst, top-initiated cylinders. The ordinate parameter of the referenced graphs is the ratio of the Peak Pressure generated from cylinders to that from spherical charges. The abscissa parameter is the scaled range.

The test designer who plans to utilize cylindrical charges for generating explosive loading on targets or test structures needs a convenient and easily applied tool in order to dictate the distance of the structure from the explosive charge where the desired airblast exposure is expected.

## METHODOLOGY


We present the use of the Equivalent Weight (EW) method of analysis in order to represent the behavior of cylindrical explosive charges of various values of L/D. The Equivalent Weight Concept itself is described in more detail in Reference 2. An earlier example of the use of this technique was presented in Reference 3 for a cylinder with an L/D of 6/1 detonated in free air. In Reference 4, both Pressure and Impulse Equivalent Weights were examined as well.

When determining the explosive loading on a target or test structure, the first step is to define the Peak Pressure and Positive Impulse values that are desired. Once these are known, the charge shape, weight, and location can be computed. Three charge shapes will be considered: hemispherical, spherical and cylindrical. Three aspect (L/D) ratios will be examined for the cylindrical charges: 1/1, 3/1, and 4/1. Since large scale testing usually involves structures that are placed on the ground surface, we discuss only the data from surface burst events.


For hemispherical charges, either Reference 5 or the DDESB Blast Effects Computer<sup>6</sup> can be used to generate pressure versus scaled distance curves. Reference 1 can be used to generate similar pressure information for spheres and cylinders detonated on the surface. Impulse information for 3/1 cylinders can be found in Reference 7.

Figure 1 compares the peak pressure for spheres and hemispheres detonated on the surface, while Figure 2 compares the peak pressure produced by three aspect ratio cylinders (1/1, 3/1 and 4/1) under similar conditions. Figure 3 compares the scaled positive impulse produced by spheres, hemispheres, and 3/1 cylinders detonated on the surface.


The major emphasis of the paper will be on peak pressure-related topics, with a limited discussion of impulse effects. This is because there is significantly more pressure-related information than cylindrical impulse data in the literature.



**FIGURE 1. Pressure vs. Scaled Distance for Hemispheres and Spheres**



**FIGURE 2. Pressure vs. Scaled Distance for Hemispheres and Cylinders**



**FIGURE 3. Scaled Impulse vs. Scaled Distance for Hemispheres, Spheres and Cylinders**


### **PRESSURE RESULTS**

Examining Figure 1, we see that relative to the hemispherical airblast, the sphere produces higher airblast at pressures above about 50 kPa. Below this value, the spherical airblast falls below the hemispherical airblast, until a pressure level of about 10 kPa is reached.


Using the EW concept, the variation of the spherical charge output relative to a hemispherical charge can be calculated. This is shown in Figure 4. At about the 280 kPa level, the EW of spheres is about 1.5 compared to hemispheres. The EW falls below 1.0 at about 50 kPa. Although not shown in the Figure, the EW again rises above 1 below about 10 kPa.

Examining the cylindrical airblast shown in Figure 2, we see that relative to the hemispherical airblast, the 1/1 cylinder produces higher pressures above about 75 kPa, while the 3/1 and 4/1 cylinders produces higher pressures above about 40 kPa. Below these values, the cylindrical pressure falls and remains below that of the hemisphere.


Again, using the EW concept, the variation of the cylindrical charge output relative to a hemispherical charge can be calculated. These are shown in Figure 5. The airblast from the 1/1 cylinder is above that of a hemisphere at pressures above 75 kPa; the 3/1 and 4/1 cylinders are above a hemisphere at pressures above about 40 kPa. Below these pressure levels, the pressure equivalence falls below 1 and is less than that of a hemisphere.



**FIGURE 4. Pressure Equivalent Weight vs. Peak Pressure of Surface Burst Spheres**



**FIGURE 5. Pressure Equivalent Weight vs. Peak Pressure of Surface Burst Cylinders**



**FIGURE 6. Impulse Equivalent Weight vs. Peak Pressure of Surface Burst Spheres and Cylinders**

Examining the impulse data shown in Figure 3, we see that relative to the hemisphere the sphere produces nearly identical impulses, while the 3/1 cylinder produces higher impulses above about 150 kPa. Again, using the EW concept, the variation of the output relative to a hemispherical charge can be calculated. These are shown in Figure 6.

### APPLICATION

Suppose that a test is being planned that requires a full-scale structure to be loaded with a pressure level of 350 kPa. If we were to use a hemispherical charge, it would have to be placed at a scaled distance of  $1.82 \text{ m/kg}^{1/3}$ . A spherical charge would need to be placed at  $2.10 \text{ m/kg}^{1/3}$ . Depending on the L/D ratio of the cylinder, these would need to be placed at the following distances:  $2.22 \text{ m/kg}^{1/3}$  (1/1),  $2.40 \text{ m/kg}^{1/3}$  (3/1), or  $2.27 \text{ m/kg}^{1/3}$  (4/1).

Let us assume that the charge shape is hemispherical and the weight of this charge shape is W. Examining Figures 3 and 4, we see that this same pressure level can be achieved with a much smaller charge weight if other charge shapes are considered. These are shown in Table 1.

**Table 1. Effect of Charge Shape on Required Charge Weight**

Charge Shape	350 kPa		80 kPa	
	Charge Weight		Charge Weight	
Hemisphere	W	W	W	W
Sphere	W/1.54	0.65*W	W/1.14	0.88*W
1/1 Cylinder	W/1.87	0.53*W	W/1.04	0.96*W
3/1 Cylinder	W/2.30	0.43*W	W/1.33	0.75*W
4/1 Cylinder	W/1.94	0.52*W	W/1.25	0.80*W

As can be seen in Table 1, once a pressure level is selected for an explosive loading test, the choice of the charge shape has the potential of saving test costs by reducing the amount of energetic materials required. For a 350 kPa blast, charge weight reductions of over 50%, compared to a hemispherical charge, are possible. The savings are not as dramatic, however, at other pressure levels. As the required blast loading approaches or falls below 10 kPa, little or no charge weight savings are obtained. Moreover, at these lower pressure levels, a weight penalty may accrue, as the TNT equivalence of these alternate charge shapes falls below a value of 1.

When impulse must also be considered, the reductions are not as dramatic. Because the impulse from spheres is nearly identical to hemispheres, changing to a spherical charge shape would not cause a weight reduction. However, if a 3/1 cylinder is used, the weight could be reduced by W/1.3 and still achieve the same impulse as a hemisphere with a weight of W.

### CONCLUSIONS

The EW of cylindrical TNT relative to hemispherical TNT is greater than 1.0 for scaled ranges less than about  $4 \text{ m/kg}^{1/3}$  for 1/1 cylinders and about  $5 \text{ m/kg}^{1/3}$  for 3/1 and 4/1 cylinders. Spherical TNT has increasing EW values and is greater than 1.0 for Peak Pressure levels above 35 KPa. We have shown that introducing the charge shape as a variable can lead to significant cost savings.

Many test structures are sensitive to not only the Pressure but also the Positive Phase Impulse imparted to them by the test explosion. Comprehensive Impulse data from cylinders detonated on the surface are, at best, limited in nature, and in many cases not available. The authors know of only limited data on the impulse characteristics of surface burst cylinders.

It is recommended that a comprehensive program of airblast measurements from surface burst cylinders be undertaken to fill-in this void of information.

## REFERENCES

- [1] Swisdak, M. M. Jr., "Explosion Effects and Properties, Part I - Explosion Effects in Air," Naval Surface Weapons Center TR 75-116, 6 October 1975.
- [2] Swisdak, M. M., "Characterization of Event Yields With A Discussion of Possible Causes For the Observed Output (or *Where Has All The Output Gone?*)," Minutes of the 33<sup>rd</sup> DDESB Seminar, August 2008.
- [3] Sadwin, L. D., "Airblast Equivalent Weight Watching," Proceedings of the Specialty Symposium on Structures Response to Impact and Blast, Tel Aviv, Israel, October 1996.
- [4] Sadwin, L. D. and Brochier, M., "Comparative Evaluation of Detonators by Airblast Measurements," Proceedings of the 28<sup>th</sup> International Pyrotechnics Seminar, Adelaide, South Australia, November 2001.
- [5] Kingery, C.N. and G. Bulmash, "Airblast Parameters from TNT Spherical Air Burst and Hemispherical Surface Burst," ARBRL TR02555, April 1984.
- [6] Swisdak, Michael M., "DDESB Blast Effects Computer Version 6: Users Manual and Documentation," DDESB Technical Paper No. 17 Revision 1, 10 March 2005.
- [7] Reisler, Ralph, Giglio-tos, Louis, and Teel, George, "Air Blast Parameters from Pentolite Cylinders Detonated on the Ground," BRL MR 2471, April 1975.

# **Airblast Equivalent Weights of Cylindrical Explosive Charges for Testing Structures**

**Lippe D. Sadwin**

**Sadwin Engineering Consultancy**

**Michael M. Swisdak, Jr.**


**A-P-T Research, Inc.**

# WHAT IS EQUIVALENT WEIGHT (YIELD)?

- Weight of a standard explosive required to produce a selected blast parameter of equal magnitude to that produced by a unit weight of the event or material in question

# EQUIVALENT WEIGHT BASED ON PEAK PRESSURE

$$Yield = \left( \frac{R_{test}}{R_{standard}} \right)_{\text{pressure} = \text{constant}}^3 \left( \frac{W_{standard}}{W_{test}} \right)$$




$$Yield \quad 1 = \left[ \frac{R_{t1}}{R_{s1}} \right]^3 \left[ \frac{W_s}{W_t} \right]$$

$$Yield \quad 2 = \left[ \frac{R_{t2}}{R_{s2}} \right]^3 \left[ \frac{W_s}{W_t} \right]$$

$$Yield = \left( \frac{I_{test}}{I_{standard}} \right)^3$$

- Note: Ratio is taken along slope lines of the log-log cycles in log-log space


## IMPULSE YIELD




# IMPULSE YIELD (continued)

- Scaled Reference Impulse =  $a_s = I_s/W_s^{1/3}$
- Scaled Test Impulse =  $a_t = I_t/W_t^{1/3}$
- Scaled Reference Distance =  $Z_s = R_s/W_s^{1/3}$
- Scaled Test Distance =  $Z_t = R_t/W_t^{1/3}$
- **Yield =  $(a_t / a_s)^3$  at points of intersection of construction line with both impulse curves**


# Pressure vs. Scaled Distance Spheres and Hemispheres




# Pressure vs. Scaled Distance Hemispheres and Cylinders




# Scaled Impulse vs. Scaled Distance Hemispheres, Spheres, and Cylinders




# Pressure Equivalent Weight vs. Peak Pressure Surface Burst Spheres



# Pressure Equivalent Weight vs. Peak Pressure Surface Burst Cylinders



# Impulse Equivalent Weight vs. Peak Pressure Surface Burst Spheres and Cylinders



# Effect of Charge Shape On Required Charge Weight

Charge Shape	350 kPa		80 kPa	
	Charge Weight		Charge Weight	
Hemisphere	W	W	W	W
Sphere	W/1.54	0.65*W	W/1.14	0.88*W
1/1 Cylinder	W/1.87	0.53*W	W/1.04	0.96*W
3/1 Cylinder	W/2.30	0.43*W	W/1.33	0.75*W
4/1 Cylinder	W/1.94	0.52*W	W/1.25	0.80*W