

AD

AD-E403 345

Technical Report ARMET-TR-11001

ALUMINUM-ZINC (Al-Zn) DUST ANALYSES FOR RECYCLING PURPOSES

Dr. Tapan Chatterjee
Stacey Kerwien
Eugene LaBuz
Elias Jelis

August 2011

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND
ENGINEERING CENTER

Munitions Engineering Technology Center

Picatinny Arsenal, New Jersey



Approved for public release; distribution is unlimited.

20110829020

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement by or approval of the U.S. Government.

Destroy this report when no longer needed by any method that will prevent disclosure of its contents or reconstruction of the document. Do not return to the originator.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-01-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) August 2011		2. REPORT TYPE		3. DATES COVERED (From - To) January to December 2010	
4. TITLE AND SUBTITLE ALUMINUM-ZINC (Al-Zn) DUST ANALYSES FOR RECYCLING PURPOSES				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHORS Dr. Tapan Chatterjee, Stacey Kerwien, Eugene LaBuz, and Elias Jelis				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC, METC Energetics, Warheads & Manufacturing Technology Directorate (RDAR-MEE-M) Picatinny Arsenal, NJ 07806-5000				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC, ESIC Knowledge & Process Management (RDAR-EIK) Picatinny Arsenal, NJ 07806-5000				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) Technical Report ARMET-TR-11001	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The physical vapor deposition (PVD) process facility at the McAlester Army Ammunition Plant, McAlester, Oklahoma coat 500-lb bombs with aluminum-zinc (Al-Zn). Transmission electron microscopy and electron diffraction technique revealed Zn and Al particles in the dust waste generated by this PVD process. The x-ray fluorescence analyses and selected electron diffraction pattern confirmed the presence of Al-Zn particles and their crystal structure. Powder data files and a standard evaporated gold thin film electron diffraction pattern were used to determine the d-spacing of Al and Zn dust particles.					
15. SUBJECT TERMS Physical vapor deposition (PVD) Transmission electron microscopy (TEM) Electron diffraction					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 11	19a. NAME OF RESPONSIBLE PERSON Dr. Tapan Chatterjee
a. REPORT U	b. ABSTRACT U	c. THIS PAGE U			19b. TELEPHONE NUMBER (Include area code) (973) 724-9457

Standard Form 298 (Rev. 8/98)
Prescribed by ANSI Std. Z39.18

CONTENTS

	Page
Introduction	1
Specimen Preparation	1
Discussion/Conclusions	2
Distribution List	7

FIGURES

1	500-lb bombs with Zn-Al coat	1
2	50-gal drums stored at MCAAP	1
3	TEM of Al-Zn dust on 400-mesh grids	3
4	Magnification of this TEM picture is higher than that of figure 3	3
5	400-mesh grid at very high magnification at nano range	4
6	Electron diffraction pattern from Al-Zn dust with very low beam density	4
7	Electron diffraction pattern of Al-Zn dust with normal beam density using a beam stop	5
8	Electron diffraction pattern from standard gold sample used for calibration	5

INTRODUCTION

The U.S. Army Armament Research, Development and Engineering Center (ARDEC), Picatinny Arsenal, New Jersey engineers visited the McAlester Army Ammunition Plant (MCAAP), McAlester, Oklahoma on 10 July 2008 to view and obtain information on their zinc (Zn) and aluminum (Al) disposal process. For the past 2 yrs, the price to dispose of this waste has increased significantly. The original cost to remove the Al/Zn dust was set at \$0.39/lb (FY08). In 1 yr, the price increased to \$2.00/lb (FY09). In the past year, this price escalated to approximately \$6.00/lb (FY10). This translates to an estimated cost of \$400,000 a year to dispose of this waste. The main reason for this spike in price is due to the reactivity of the collection drums. The Al in the dust particles reacts with rain water. This reaction results in hydrogen gas, which builds up pressure. The barrels are occasionally mishandled and sealed with water inside. The buildup of pressure results in the barrel's top firing off. This increased hazard increased the shipping cost dramatically. Unless an alternate form of disposal is found for this Al-Zn waste, the physical vapor deposition (PVD) process facility will be closed. The primary purpose of the PVD thermal arc process metal coating is to provide fire protection for the round and increase the bomb's high temperature threshold. In addition, it provides a more effective adhesion of paint to the shell body.

The ARDEC engineers contacted the Sarakem Corporation, a trusted hazardous waste management industry in Hanover, New Hampshire. The composition of Al-Zn dust and total weight of shipment was determined and provided to the Sarakem Corporation that planned to recycle this dust to zinc oxide as a chemical product. The Al-Zn waste stream that was previously disposed of as hazardous waste was reclassified as a recyclable waste, since MCAAP/ARDEC secured a contractor (Sarakem) that will accept and recycle the Al-Zn waste stream. This resulted in a total cost savings of approximately \$838,860.

SPECIMEN PREPARATION

The 500-lb bombs are coated with Al-Zn (fig. 1) and the Al-Zn dust is collected in 50-gal drums (fig. 2). The ARDEC received this Al-Zn dust from MCAAP for x-ray fluorescence (XRF) analysis to determine the composition of the dust sample.



Figure 1
500-lb bombs with Zn-Al coat



Figure 2
50-gal drums stored at MCAAP

A small amount of this Al-Zn dust was dissolved in water and dropped on a 200-mesh carbon coated copper grid and dried at room temperature. This specimen was then placed in a single tilt specimen holder and inserted in a Philips 420 transmission electron microscope (TEM).

DISCUSSION/CONCLUSIONS

The XRF analysis revealed approximately 88.8% Zn, 10.9% Al, and minute traces of other metal elements as shown in the table.

SQX Calculation Result							
Sample :		Date analyzed :		2009-2-27 15:49			
Application : EZS003MSV		Model : Bulk		Balance :			
				Matching library:			
				File :		Tapan AlZn	
No.	Component	Result	Unit	Det.limit	El.line	Intensity	w/o normal
1	Al	10.9	mass%	0.0243	Al-KA	15.3782	10.3946
2	Si	0.143	mass%	0.0060	Si-KA	0.1998	0.1358
3	P	0.0053	mass%	0.0027	P-KA	0.0218	0.0050
4	S	0.0167	mass%	0.0030	S-KA	0.0567	0.0159
5	Ca	0.0237	mass%	0.0104	Ca-KA	0.0949	0.0225
6	Fe	0.0877	mass%	0.0078	Fe-KA	0.7050	0.0833
7	Ni	0.0129	mass%	0.0052	Ni-KA	0.1920	0.0122
8	Zn	88.8	mass%	0.0236	Zn-KA	889.4754	84.3667

Transmission Electron Micrographs Analyses

The TEM of Al-Zn dust samples were taken from different specimens at low and high magnifications. Figure 3 shows a Zn particle denoted by A; the arrow indicates the border of a single mesh. The same area was blown up to a higher magnification and figure 4 shows an area with a large a concentration of Zn particles and a much smaller concentration of Al dust particles are clustered together. Figure 5 shows an electron micrograph of very high magnification from another area of the specimen. Clusters of Al-Zn dust are revealed. A selected electron diffraction (SAED) pattern corresponding to this electron micrograph is shown at figure 6. The spotty rings reveal the Al-Zn dust particle distribution is not polycrystalline in nature; rather they are preferentially oriented. Low electron beam density and a small condenser aperture were used to obtain this SAED. Figure 7 is another SAED pattern taken from a different area of the specimen. A larger condenser aperture with normal electron beam density was used to obtain this ring pattern that is different from that in figure 6.

It is concluded the Al-Zn dust particles generated by the PVD deposition process are not homo-geneous in nature. The d-spacing's of these ring patterns were measured using the equation $L\lambda = rd$; where L = camera length, λ is the wavelength of the electron beam at 120kV, r = radius of the diffraction ring, and D is the interplanar spacings of the Zn and/or Al particles. The powder data file and a standard electron diffraction pattern (fig. 8), from standard Au specimen, confirmed the presence of Al-Zn particles.




Figure 3
TEM of Al-Zn dust on 400-mesh grids




Figure 4
Magnification of this TEM picture is higher than that of the figure 3




Figure 5
400-mesh grid at very high magnification at nano range
(different area)




Figure 6
Electron diffraction pattern from Al-Zn dust with very low beam density



Figure 7
Electron diffraction pattern of Al-Zn dust with normal beam density using a beam stop




Figure 8
Electron diffraction pattern from standard gold sample used for calibration

DISTRIBUTION LIST

U.S. Army ARDEC
ATTN: RDAR-EIK
RDAR-GC
RDAR-MEE-M (25)
Picatinny Arsenal, NJ 07806-5000

Defense Technical Information Center (DTIC)
ATTN: Accessions Division
8725 John J. Kingman Road, Ste 0944
Fort Belvoir, VA 22060-6218

Commander
Soldier and Biological/Chemical Command
ATTN: AMSSB-CII, Library
Aberdeen Proving Ground, MD 21010-5423

Director
U.S. Army Research Laboratory
ATTN: AMSRL-CI-LP, Technical Library
Bldg. 4600
Aberdeen Proving Ground, MD 21005-5066

Chief
Benet Weapons Laboratory, WSEC
U.S. Army Research, Development and Engineering Command
Armament Research, Development and Engineering Center
ATTN: RDAR-WSB
Watervliet, NY 12189-5000

Director
U.S. Army TRADOC Analysis Center-WSMR
ATTN: ATRC-WSS-R
White Sands Missile Range, NM 88002

Chemical Propulsion Information Agency
ATTN: Accessions
10630 Little Patuxent Parkway, Suite 202
Columbia, MD 21044-3204

GIDEP Operations Center
P.O. Box 8000
Corona, CA 91718-8000