



Calculations of Temperature, Conductive Heat Flux, and Heat Wave Velocities Due to Radiant Heating of Opaque Materials

by Arthur Cohen

ARL-TR-5804

November 2011

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5069

ARL-TR-5804

November 2011

Calculations of Temperature, Conductive Heat Flux, and Heat Wave Velocities Due to Radiant Heating of Opaque Materials

Arthur Cohen

Weapons and Materials Research Directorate, ARL

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) November 2011		2. REPORT TYPE Final		3. DATES COVERED (From - To) September 2009–September 2011	
4. TITLE AND SUBTITLE Calculations of Temperature, Conductive Heat Flux, and Heat Wave Velocities Due to Radiant Heating of Opaque Materials				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Arthur Cohen				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: RDRL-WML-B Aberdeen Proving Ground, MD 21005-5069				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TR-5804	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The analytic solutions of the one-dimensional Fourier conductive heat flux law and corresponding transient heat transfer equation have been used to calculate temperature, conductive heat flux, and their trajectories due to radiant heating of opaque materials. Heat wave trajectories (and velocities) are defined by the value of a constant temperature or constant conductive heat flux that propagates through the materials. For constant values of zero, the analytic solutions lead to infinite heat wave velocities. For nonzero constant values, the numerical solutions at ultra-short transient times result in other nonphysical velocities (i.e., $>3E(10)$ cm/s). These calculations demonstrate that there are limitations to the validity of the Fourier heat flux law and corresponding heat transfer equation, although they have been used successfully to solve engineering and scientific heat conduction problems for over 180 years.					
15. SUBJECT TERMS radiant heating, opaque materials, Fourier heat transfer, temperature/conductive heat flux, infinite heat wave velocity calculations					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 18	19a. NAME OF RESPONSIBLE PERSON Arthur Cohen
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 410-306-0677

Contents

List of Figures	iv
List of Tables	iv
Acknowledgments	v
1. Introduction	1
2. Nomenclature	1
3. Mathematical Formulation	2
4. Conclusion	7
5. References	8
Distribution List	9

List of Figures

Figure 1. Conductive flux vs. distance.....	3
Figure 2. Temperature vs. distance.....	3
Figure 3. Temperature trajectory distance vs. time.	5
Figure 4. Temperature wave velocity vs. time.	6
Figure 5. Flux wave trajectory distance vs. time.	6
Figure 6. Flux wave velocity vs. time.....	6

List of Tables

Table 1. Nomenclature.....	1
----------------------------	---

Acknowledgments

The suggestions of Dr. Gene Cooper for clarifying the mathematical presentation and the help of Dr. Anthony Kotlar with the Mathcad calculations are greatly appreciated.

INTENTIONALLY LEFT BLANK.

1. Introduction

The objective of this report is to document recent one-dimensional (1-D) calculations of temperature, conductive heat flux, and heat wave velocities for an opaque, semi-infinite cylinder due to radiant heating. The Fourier conductive heat flux law is assumed to be valid. An idealized model is used for the calculations. Radiant flux enters the planar surface. It is uniform and steady with beam and cylinder diameters equal. The initial temperature is uniform, and thermal properties are constant. Heat wave trajectories (and velocities) are defined by the value of a constant temperature or constant conductive heat flux that propagates through the opaque material. For the constant values of zero, the analytic solutions (1) of the 1-D Fourier conductive heat flux law and transient heat transfer equation (derived by applying energy conservation to the Fourier heat flux law) lead to infinite heat wave velocities. For the constant values >0 , the numerical solutions at ultra-short transient times result in other nonphysical velocities (i.e., $>3E(10)$ cm/s).

These calculations suggest that there are limitations to the validity of the Fourier heat flux law and heat transfer equation, although they have been used successfully to solve engineering and scientific heat conduction problems for over 180 years.

2. Nomenclature

Table 1 shows the units and values of the thermophysical properties and F that were used in all calculations. The thermophysical values chosen were those for RDX at $T \sim 288$ K (2).

Table 1. Nomenclature.

Symbols	Quantity	Units	Values
t	radiant flux time	s	—
d	distance from the planar surface	cm	—
V	temperature increment, i.e., $V(d,0) = 0$	K	—
f	conductive heat flux	cal/cm ² -s	—
λ	thermal conductivity	cal/cm-s-K	2.5×10^{-4}
ρ	density	g/cm ³	1.76
c	heat capacity	cal/g-K	0.3
α	thermal diffusivity = $\lambda/\rho \cdot c$	cm ² /s	4.7×10^{-4}
F	radiant flux	cal/cm ² -s	100

3. Mathematical Formulation

For the simplified model with opaque (surface absorption) materials, the Fourier heat flux law is

$$f(d,t) = -(1/\lambda) \cdot \frac{\partial}{\partial d} V(d,t) \quad (1)$$

with boundary condition

$$f(d,t) = F; \quad d = 0, t > 0. \quad (2)$$

The Fourier heat transfer equation is

$$\frac{\partial}{\partial t} V(d,t) = \alpha \frac{\partial^2}{\partial d^2} V(d,t) \quad (3)$$

with boundary condition

$$\frac{\partial}{\partial d} V(d,t) = -F/\lambda; \quad d = 0, t > 0. \quad (4)$$

Using equations 1 and 3, Carslaw and Jaeger (1) show that the Fourier flux transfer equation is

$$\frac{\partial}{\partial t} f(d,t) = \alpha \frac{\partial^2}{\partial d^2} f(d,t); \quad d > 0, t > 0 \quad (5)$$

with the boundary condition

$$f(d,t) = F; \quad d = 0. \quad (6)$$

The solution for $f(d,t)$ (1) is

$$f(d,t) = F \cdot \operatorname{erfc}\left(\frac{d}{2 \cdot \sqrt{\alpha \cdot t}}\right). \quad (7)$$

The solution for $V(d,t)$, obtained by integration of equation 1, is (1)

$$V(d,t) = 2 \cdot \frac{F}{\lambda} \left(\sqrt{\frac{\alpha \cdot t}{\pi}} \exp\left(\frac{-d^2}{4\alpha t}\right) - \frac{d}{2} \cdot \operatorname{erfc}\left(\frac{d}{2 \cdot \sqrt{\alpha \cdot t}}\right) \right). \quad (8)$$

Figures 1 and 2 are calculated values of f (cal/cm²-s) and V (K) vs. d (cm) at t (s) = 0.001, 0.01, 0.05, and 0.1.




Figure 1. Conductive flux vs. distance.




Figure 2. Temperature vs. distance.

Average heat wave velocities for conductive flux at $f = 10$ and 60 and for temperature at $V = 50$ and 150 can be obtained from the distances between intersections of their corresponding lines with those calculated for different values of t . Distances vary inversely with the values of both $f(d)$ and $V(d)$, which suggests that the largest heat wave velocities are for $f = 0$ and $V = 0$. To obtain heat wave velocities at points on trajectories, let x = trajectory distance (cm) from the planar surface.

Values of x at given values of t can be obtained from numerical solutions of equations 7 and 8. For $f = 0$ and $V = 0$, the numerical solutions (3) are unstable. To calculate these trajectories,

let $z = \frac{x}{2 \cdot \sqrt{\alpha \cdot t}}$ and substitute into equations 7 and 8.

$$f(z) = F \cdot \text{erfc}(z). \quad (7a)$$

$$V(z, t) = 2 \cdot \frac{F}{\lambda} \cdot \sqrt{\frac{\alpha \cdot t}{\pi}} \cdot e^{z^2} \cdot \left(1 - \sqrt{\pi} \cdot z \cdot e^{z^2} \cdot \text{erfc}(z)\right). \quad (8a)$$

The trajectories ($x = 2 \cdot z \cdot \sqrt{\alpha \cdot t}$) can be calculated for given values of t from solutions of equations 7a and 8a for z .

When $f(z) = 0$, then $\text{erfc}(z) = 0$. The solution to equation 7a is $z = \infty$.

When $V(z, t) = 0$, then

$$\sqrt{\pi} z \cdot e^{z^2} \cdot \text{erfc}(z) = 1. \quad (9)$$

Using L'Hopital's rule, when $z = \infty$, then

$$\sqrt{\pi} z \cdot e^{z^2} \cdot \text{erfc}(z) = 1. \quad (10)$$

The solution to equation 8a is $z = \infty$.

For $V > 0$ and $f > 0$, the trajectories ($x = 2 \cdot z \cdot \sqrt{\alpha \cdot t}$) can be calculated from the values of x corresponding to given values of t from numerical solutions of equations 7 and 8 or the corresponding z from equations 7a and 8a.

Corresponding velocities $\frac{d}{dt}x$ (f_v for flux and V_v for temperature) can be calculated by numerical differentiation. Calculating trajectories with $z = \infty$ is a problem. The heat wave velocities can also be obtained analytically from the calculated trajectories using $g(x, t) =$

$$\text{constant}; \quad \frac{d}{dt}x = - \left(\frac{\partial}{\partial t} g(x, t) \cdot \frac{1}{\frac{\partial}{\partial x} g(x, t)} \right).$$

When $f(x, t) = g(x, t)$, then

$$f_v = \frac{x}{2 \cdot t} = z \cdot \sqrt{\frac{\alpha}{t}}. \quad (11)$$

When $f(x, t) = 0$, then $z = \infty$.

When $x = 0$, then $z < \infty$, i.e., $0 < x \leq \infty$.

When $x = \infty$ and $t = \infty$, then $z = 1 < \infty$, i.e., $0 \leq t < \infty$.

Using equation 11 with $0 < x \leq \infty$ and $0 \leq t < \infty$,

$$fv = \infty. \quad (11a)$$

When $V(x,t) = g(x,t)$, then

$$Vv = \frac{e^{-\frac{x^2}{4 \cdot t \cdot \alpha}} \sqrt{\frac{\alpha}{t}}}{\sqrt{\pi} \cdot \operatorname{erfc}\left(\frac{x}{2 \cdot \sqrt{t \cdot \alpha}}\right)} = \frac{z \sqrt{\frac{\alpha}{t}}}{\sqrt{\pi} \cdot z \cdot e^{z^2} \cdot \operatorname{erfc}(z)}. \quad (12)$$

When $V(x,t) = 0$, then $z = \infty$. Using equation 10, $\sqrt{\pi} z \cdot e^{z^2} \cdot \operatorname{erfc}(z) = 1$.

$$Vv = z \cdot \sqrt{\frac{\alpha}{t}}. \quad (13)$$

When $0 < x \leq \infty$ and $0 \leq t < \infty$, then

$$Vv = \infty, \quad (13a)$$

Equations 11a and 13a show that when $0 < x \leq \infty$ and $0 \leq t < \infty$, and $f(z) = V(z,t) = 0$, then $Vv = fv = \infty$. This is consistent with the results shown in figures 1 and 2.

Figures 3 and 4 show the calculated values of $x(\text{cm})$ and $vV(\text{cm/s})$ vs. $t(\text{s})$ for constant values of V . The x ratios (RxV) and v ratios (RvV) are shown on the right y-axis. In figure 4, the vertical line indicates that for $V = 1E(-19)$; $vV > 3E10$ at $t < 1.37 \cdot 10^{-23}$.




Figure 3. Temperature trajectory distance vs. time.




Figure 4. Temperature wave velocity vs. time.

Figures 5 and 6 correspond to figures 3 and 4 for the calculated values of x and v_f vs. time for constant values of f/F . The x ratios (R_{xf}) and v_f ratios (R_{vf}) are shown on the right y-axis. In figure 6, the vertical lines indicate that for $f/F = 1E(-10)$ and $1E(-16)$, $v_f > 3E(10)$ at $t < 1.1 \cdot 10^{-23}$ and $1.8 \cdot 10^{-23}$, respectively.




Figure 5. Flux wave trajectory distance vs. time.




Figure 6. Flux wave velocity vs. time.

4. Conclusion

The calculations of nonphysical heat wave velocities for temperature and heat flux using analytic solutions of the Fourier heat flux law and the corresponding transient heat transfer equation indicate that there are limitations to their validity. This problem has been well noted in the heat transfer literature (4). The inability of the Fourier heat transfer (parabolic) equation to predict measurements of heat propagation velocities in solids near zero absolute temperatures and for pulsed laser processing of solid surfaces involving ultra-short transient heating times is probably due to the Fourier flux law being constitutive and not valid under these extreme conditions. The Fourier equations are based on the linear dependence of heat flux and temperature gradient. The details of the mechanism for thermal energy transfer (molecular collisions in the absence of net mass motion) are still under investigation. Consideration of phonon interactions as a molecular gas (5) has recently been used to describe the thermal energy transfer mechanism for conductive heat flux.

Non-Fourier-type conductive heat flux laws in solids have been proposed and include both time and temperature gradient dependence (4). These laws combined with energy conservation can lead to hyperbolic type transient heat transfer equations, which avoid the Fourier problem of nonphysical heat propagation velocity predictions and give better agreement with measurements under extreme conditions. Under normal conditions, these time-dependent conductive heat flux laws transit into the Fourier temperature gradient flux law.

Temperature measurements (using different techniques) of the rate at which equilibrium is established when solids (meat) at different (near room) temperatures are placed in contact have been used to compare heat transfer velocities with predictions of the Fourier and non-Fourier type conductive heat transfer equations in solids (6). The conclusions as to which type equation is in better agreement with the data are in disagreement. It is of interest to determine the lower time limits at which Fourier's heat transfer equation remains valid. It may be possible to obtain estimates from the published results of recent pulsed radiant heating experiments on opaque and semi-transparent solids.

5. References

1. Carslaw, H.; Jaeger, J. *Conduction of Heat in Solids*, 2nd ed. Oxford Science Publications: London, 1959.
2. Miller, M. S. Thermophysical Properties of Cyclotrimethylenetrinitramine. *Journal of Thermophysics and Heat Transfer* **1994**, *8*, 803–805.
3. Parametric Technology Corporation. *Mathcad 2001*; Needham, MA, 2001.
4. Joseph, D. D.; Preziosi, L. Heat Waves. *Rev. Modern Physics* **1989**, *61* (1), 41–73.
5. Cao, B-Y; Guo, Z-Y. *Journal of Applied Physics* **2007**, *102*, 053503.
6. Herwig, H.; Beckert, K. *Journal of Heat Transfer* **May 2000**, *122*, 363–365.

NO. OF
COPIES ORGANIZATION

1 (PDF only)	DEFENSE TECHNICAL INFORMATION CTR DTIC OCA 8725 JOHN J KINGMAN RD STE 0944 FORT BELVOIR VA 22060-6218
1	DIRECTOR US ARMY RESEARCH LAB IMNE ALC HRR 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DIRECTOR US ARMY RESEARCH LAB RDRL CIO LL 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DIRECTOR US ARMY RESEARCH LAB RDRL CIO MT 2800 POWDER MILL RD ADELPHI MD 20783-1197
1	DIRECTOR US ARMY RESEARCH LAB RDRL D 2800 POWDER MILL RD ADELPHI MD 20783-1197

NO. OF
COPIES ORGANIZATION

2 PENNSYLVANIA STATE UNIV
DEPT OF MECHL & NUCLEAR ENGRG
K KUO
S THYNELL
UNIVERSITY PARK PA 16802

1 UNIV WASHINGTON
AERONAUTICS AND ASTRONAUTICS
A BRUCKNER
BOX 352400
SEATTLE WA 98195-2400

1 SANDIA NATIONAL LAB
COMBUSTION RSCH FACLTY
R BEHRENS
LIVERMORE CA 94551-0969

1 UNIV CALIFORNIA AT SAN DIEGO
F WILLIAMS
LA JOLLA CA 92093

1 E COHEN
421 4TH ST
BROOKLYN NY 11215

1 A COHEN
721 115TH AVE SE
LAKE STEVENS WA 98258

ABERDEEN PROVING GROUND

25 DIR USARL
RDRL SLB G
L COHEN
RDRL WM
B FORCH
RDRL WML B
J BRENNAN
S BUNTE
A COHEN
P KASTE
J MORRIS
S PIRAINO
B RICE
R RODRIGUEZ (3 CPS)
R SAUSA
M SCHROEDER
RDRL WML C
K MCNESBY
RDRL WML D
W ANDERSON
R BEYER

NO. OF
COPIES ORGANIZATION

L M CHANG
P CONROY
A HORST
A KOTLAR
M MCQUAID
M NUSCA
RDRL WML E
G COOPER
RDRL WMP G
B HOMAN