

On Orbit Performance of the Defense Meteorological Satellite Program (DMSP) 5D3 Spacecraft Power System

December 30, 2011

Edward J. Simburger
Electronics and Photonics Laboratory
Physical Sciences Laboratories

David Rust
Lockheed Martin Space Systems Company

Prepared for:
Space and Missile Systems Center
Air Force Space Command
483 N. Aviation Blvd.
El Segundo, CA 90245-2808

Authorized by: Space Systems Group

Approved for public release;
distribution is unlimited.

This report was submitted by The Aerospace Corporation, El Segundo, CA 90245-4691, under Contract No. FA8802-09-C-0001 with the Space and Missile Systems Center, 483 N. Aviation Blvd., El Segundo, CA 90245. It was reviewed and approved for The Aerospace Corporation by Bernardo Jaduszliwer, Principal Director, Electronics and Photonics Laboratory; and Patrick H. Mak, Principal Director, Defense Meteorological Satellite Program. Capt. Victor Thompson was the project officer.

This report has been reviewed by the Public Affairs Office (PAS) and is releasable to the National Technical Information Service (NTIS). At NTIS, it will be available to the general public, including foreign nationals.

This technical report has been reviewed and is approved for publication. Publication of this report does not constitute Air Force approval of the report's findings or conclusions. It is published only for the exchange and stimulation of ideas.

Refer to OTR20110201111620
SMC Case no. 11-106

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.				
1. REPORT DATE (DD-MM-YYYY) 30-12-2011		2. REPORT TYPE		3. DATES COVERED (From - To)
4. TITLE AND SUBTITLE On Orbit Performance of the Defense Meteorological Satellite Program (DMSP) 5D3 Spacecraft Power System		5a. CONTRACT NUMBER FA8802-09-C-0001		
		5b. GRANT NUMBER		
		5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Edward J. Simburger and David Rust		5d. PROJECT NUMBER		
		5e. TASK NUMBER		
		5f. WORK UNIT NUMBER		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The Aerospace Corporation Physical Sciences Laboratories El Segundo, CA 90245-4691		8. PERFORMING ORGANIZATION REPORT NUMBER TR-2011(1550)-2		
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Space and Missile Systems Center Air Force Space Command 483 N. Aviation Blvd. El Segundo, CA 90245		10. SPONSOR/MONITOR'S ACRONYM(S) SMC		
		11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.				
13. SUPPLEMENTARY NOTES 20120123004				
14. ABSTRACT This report provides an analysis of the orbital performance of the three DMSP 5D3 spacecraft presently on orbit. The mission of the DMSP spacecraft is to collect and disseminate global high-resolution visible and thermal cloud cover imagery for DoD forces and the intelligence community. The present two-satellite constellation (early morning and mid morning) has an inclination of 98.7° with a 458 nmi sun synchronous polar orbit. The orbit period is 101 min with eclipses lasting up to 35 min. The satellites complete 14.2 revolutions around the Earth each day. The report presents data from the satellite telemetry that will allow determination of the spacecraft power demand for the range of sun angles and spacecraft configurations for the three operational 5D3 spacecraft. This is used in determining spacecraft energy balance margins under various operating conditions.				
15. SUBJECT TERMS Defense Meteorological Satellite Program, Satellite power system				
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES
a. REPORT UNCLASSIFIED	b. ABSTRACT UNCLASSIFIED	c. THIS PAGE UNCLASSIFIED	Leave blank	41
			19a. NAME OF RESPONSIBLE PERSON Edward Simburger	
			19b. TELEPHONE NUMBER (include area code) (310)336-7126	

On Orbit Performance of the Defense Meteorological Satellite Program (DMSP) 5D3 Spacecraft Power System

Edward J. Simburger
The Aerospace Corporation

David Rust
Lockheed Martin Space Systems Company

Energy Technology Department
April 18 – 21, 2011



History of DMSP 5D3 Spacecraft

- The build of five 5D-3 spacecraft was completed in 1997
- The first 5D-3 satellite designated F-16 was launched on October 18, 2003 after six years of storage
- The second 5D-3 DMSP designated F-17 was launched on November 4, 2006
- The third 5D-3 DMSP designated F-18 was launched on October 18, 2009
- The final DMSP satellite will not be launched until 2014 or later!

DMSG Mission Description

- Collect and disseminate global high-resolution visible and thermal cloud cover imagery to DoD forces and the intelligence community
- Two satellite constellation (early morning and mid morning)
- 98.7 deg inclination
- 458 nm sun sync polar orbit
- 101 min period with up to 35 minutes eclipse per orbit
- 14.2 revs/day



DMSP 5D-3 Spacecraft Power System


- Direct energy transfer configuration
 - *Solar array partial shunt regulation*
 - *Battery boost regulation*
- Solar array
 - 10 co-planar panels each with 21 series strings with 89 or 90 silicon solar cells
 - Single axis tracking by rotating solar array around Z-axis once per orbit
 - *Capability to command solar array to point off of sun (SADLAG)*
- Battery
 - Three 17 – cell SAFT 40 AH NiCd batteries

Solar Array Design Features

- The solar array boom can be canted with respect to the +Z axis of the spacecraft from 12° to 42° in 5° increments
- The cant is set prior to launch and cannot be changed on orbit
- The DMSP Solar Array is a single axis tracking system
- The single axis of tracking is accomplished by rotating the solar array around the boom once per orbit



Impact of Single Axis Tracking and Preset Cant Angle




Solar array output as function of sun angle and preset cant angle after five years on orbit in the month of June

Spacecraft Load Varies with Sun Angle, Solar Array SADLAG, and Spacecraft


- F-16 and F-18 Sun angle predicted to vary between 0° and 45° over lifetime
- F-17 sun angle predicted to vary between 0° and 30° over lifetime
- F-16 and 17 implemented SADLAG of 55° for sun angles greater than 15° to cool battery 3
- F-17 and 18 have addition of miniature inertial measurement unit (MIMU)
- F-18 had the radiator on battery 3 enlarged eliminating the need to SADLAG the solar array to shade battery 3

Solar Array Capacity




- Solar array capacity as function of SADLAG and sun angle with optimal cant angle after 5 years on orbit

DMSP F-16 Spacecraft Sun Angle Prediction




F-16 Load Data for Sun Angle 30° with SADLAG of 0°



Orbit Average Load for F-16 at Sun Angle 30° and
SADLAG 0°

Date	Orbit Number	Sun Angle	Orbit Average Load Watts
1-14-2004	1246	29.1	514
1-14-2004	1247	29.1	516.5

F-16 Load Data for Sun Angle 30° with SADLAG of 55°




Orbit Average Load for F-16 at Sun Angle 30° and SADLAG 55°

Date	Orbit Number	Sun Angle	Orbit Average Load Watts
1-15-2005	6448	29.5	570.7
2-15-2006	12015	29.5	566.4
3-15-2007	17566	30.2	568.8
9-15-2008	25334	29.7	570.6
8-17-2009	30078	29.5	568.2
5-15-2010	33909	31.8	555.0

F-16 Load Change due to Change from SADLAG = 0° to SADLAG = 55° at Sun Angle of 30°

- Average load for SADLAG of 0° = 515 watts
- Average load for SADLAG of 55° = 566 watts
- Average additional heater load for SADLAG of 55° = 51 watts


F-16 Load Data for Sun Angle 45° with SADLAG of 55°




Orbit Average Load for F-16 at Sun Angle 45° and SADLAG 55°

Date	Orbit Number	Sun Angle Degrees	Orbit Average Load Watts
6-15-2004	3389	44.1	537.2
6-15-2005	8566	45.4	532.4
7-15-2006	14160	43.2	529.6
6-15-2007	18866	44.2	521.6
6-25-2008	24180	41.3	528.1

DMSP F17 Sun Angle Prediction




F-17 Load Data for Sun Angle 0-5° with SADLAG of 0°



Orbit Average Load for F-17 at Sun Angle 0°–5° and SADLAG 0°

Date	Orbit Number	Sun Angle Degrees	Orbit Average Load Watts
10-15-2007	4867	3.8	726.1
10-14-2008	10023	4.4	714.8
10-15-2009	15191	4.2	720.5
10-18-2010	20390	3.4	722.7


F-17 Load Data for Sun Angle 15° with SADLAG of 0°



Orbit Average Load for F-17 at Sun Angle 15° and SADLAG 0°

Date	Orbit Number	Sun Angle Degrees	Orbit Average Load Watts
1-15-2007	1012	15.1	620.2
1-18-2008	6208	15.4	616.1
1-15-2009	11336	15.8	602.3
1-15-2010	16484	15.7	599.9


F-17 Load Data for Sun Angle 30° with SADLAG of 55°




Orbit Average Load for F-17 at Sun Angle 30° and SADLAG 55°

Date	Orbit Number	Sun Angle Degrees	Orbit Average Load Watts
7-15-2007	3596	31.2	622.8
5-21-2008	7962	39.8	621.8
7-15-2009	13892	31.7	612.1
7-14-2010	19037	31.6	613.9

DMSP F18 Sun Angle Prediction




F-18 Load Data for Sun Angle 30° with SADLAG of 0°



Orbit Average Load for F-18 at Sun Angle 30° and
SADLAG 0°

Date	Orbit Number	Sun Angle Degrees	Orbit Average Load Watts
1-14-2010	1239	28.9	579.5
1-17-2011	6432	31.0	558.0

F-18 Load Data for Sun Angle 45° with SADLAG of 0°



Orbit Average Load for F-18 at Sun Angle 45° and SADLAG 0°

Date	Orbit Number	Sun Angle Degrees	Orbit Average Load Watts
6-17-2010	3384	42.9	538

Comparison of F-16, F-17 and F-18 with Sun Angle of 30° to Determine Added Load for MIMU

- SADLAG 0°
 - Average F-16 load is 515 watts
 - Average F-18 load is 568 watts
 - Added load due to MIMU and larger battery 3 radiator is 53 watts
- SADLAG 55°
 - Average F-16 load is 566 watts
 - Average F-17 load is 617 watts
 - Added load due to MIMU is 51 watts

The Aerospace Corporation Energy Balance Model Validation




Filtering of Raw Telemetry Data for Energy Balance Model Validation

- Aerospace DMSP energy balance model uses 0.5 minute time steps
- To validate Aerospace energy balance model a load input data file was generated from actual spacecraft telemetry
 - *Telemetry data has six data points per minute*
 - *Filtered raw telemetry by averaging the three telemetry data points for each 0.5 minute model load data point*

Validation Of Aerospace Energy Balance Model

- Aerospace energy balance model includes a solar array model which includes:
 - *Sun angle*
 - *Time of year*
 - *Cant angle*
 - *Number of years on orbit*
- Aerospace energy balance model includes:
 - *Model of the battery charger V/T curves*
 - *NiCd battery charge/discharge characteristic*
- Comparison of solar array output and battery charge/discharge currents from actual spacecraft with model using actual loads as forcing function will validate model
- Actual spacecraft data was filtered for comparison

Comparison of Actual Spacecraft Data to Aerospace Energy Balance Model Rev's 8566/8567 after 2 Years on Orbit




Comparison of Actual Spacecraft Data to Aerospace Energy Balance Model


- Solar array and battery discharge currents calculated by model match actual measured values
- Battery charge currents calculated by model differ slightly from actual measured values
 - *Peak charge currents match*
 - *Model predicts beginning of taper charge later than actual data*
 - *Model predicts beginning of trickle charge with a high degree of accuracy*
- Model is considered to be validated with the caveat that predicted battery charge currents for actual satellite may differ slightly

Power System Margin at Sun Angle of 45°


DMSP F-16 Energy Balance Predicts 5 Years EOL, Sun Angle 45°, SADLAG 55°, Month of June, with 180 Watts Added Load and 10 Amp Battery Charge Rate




DMSP F-16 Energy Balance Predicts 5 Years EOL, Sun Angle 45°, SADLAG 0°, Month of June, with 360 Watts Added Load and 10 Amp Battery Charge Rate



DMSP F-16 Energy Balance Predicts 5 Years EOL, Sun Angle 45°, SADLAG 55°, Month of June, with 160 Watts Added Load and 7.5 Amp Battery Charge Rate



DMSP F-16 Energy Balance Predicts 5 Years EOL, Sun Angle 45°, SADLAG 0°, Month of June, with 290 Watts Added Load and 7.5 Amp Battery Charge Rate



Power Margin for DMSP F-16 as function of Battery Charge Rate and Solar Array SADLAG at Sun Angle of 45°

SADLAG Degrees	7.5 Amp Battery Charge Rate	10 Amp Battery Charge Rate
0	290 Watts	360 Watts
55	160 Watts	180 Watts

Conclusions

- Orbit load data shows little change over many years at same sun angle
- SADLAG of the solar array has an impact on the heater loads of the spacecraft
- Spacecraft power margin is a function of spacecraft age, sun angle, SADLAG, battery charge rate and spacecraft configuration
- Orbit load data essential as input to energy balance models to determine spacecraft margins

PHYSICAL SCIENCES LABORATORIES

The Aerospace Corporation functions as an "architect-engineer" for national security programs, specializing in advanced military space systems. The Corporation's Physical Sciences Laboratories support the effective and timely development and operation of national security systems through scientific research and the application of advanced technology. Vital to the success of the Corporation is the technical staff's wide-ranging expertise and its ability to stay abreast of new technological developments and program support issues associated with rapidly evolving space systems. Contributing capabilities are provided by these individual organizations:

Electronics and Photonics Laboratory: Microelectronics, VLSI reliability, failure analysis, solid-state device physics, compound semiconductors, radiation effects, infrared and CCD detector devices, data storage and display technologies; lasers and electro-optics, solid-state laser design, micro-optics, optical communications, and fiber-optic sensors; atomic frequency standards, applied laser spectroscopy, laser chemistry, atmospheric propagation and beam control, LIDAR/LADAR remote sensing; solar cell and array testing and evaluation, battery electrochemistry, battery testing and evaluation.

Space Materials Laboratory: Evaluation and characterizations of new materials and processing techniques: metals, alloys, ceramics, polymers, thin films, and composites; development of advanced deposition processes; nondestructive evaluation, component failure analysis and reliability; structural mechanics, fracture mechanics, and stress corrosion; analysis and evaluation of materials at cryogenic and elevated temperatures; launch vehicle fluid mechanics, heat transfer and flight dynamics; aerothermodynamics; chemical and electric propulsion; environmental chemistry; combustion processes; space environment effects on materials, hardening and vulnerability assessment; contamination, thermal and structural control; lubrication and surface phenomena. Microelectromechanical systems (MEMS) for space applications; laser micromachining; laser-surface physical and chemical interactions; micropropulsion; micro- and nanosatellite mission analysis; intelligent microinstruments for monitoring space and launch system environments.

Space Science Applications Laboratory: Magnetospheric, auroral and cosmic-ray physics, wave-particle interactions, magnetospheric plasma waves; atmospheric and ionospheric physics, density and composition of the upper atmosphere, remote sensing using atmospheric radiation; solar physics, infrared astronomy, infrared signature analysis; infrared surveillance, imaging and remote sensing; multispectral and hyperspectral sensor development; data analysis and algorithm development; applications of multispectral and hyperspectral imagery to defense, civil space, commercial, and environmental missions; effects of solar activity, magnetic storms and nuclear explosions on the Earth's atmosphere, ionosphere and magnetosphere; effects of electromagnetic and particulate radiations on space systems; space instrumentation, design, fabrication and test; environmental chemistry, trace detection; atmospheric chemical reactions, atmospheric optics, light scattering, state-specific chemical reactions, and radiative signatures of missile plumes.