

Temperature gradients in diode-pumped alkali lasers

Charles Fox and Glen Perram

Localized heating in diode-pumped alkali lasers induces spatial variations in metal vapor density, leading to a reduction in laser power.

The quest for a high-power, electrically driven laser with excellent thermal management, lightweight packaging, and high brightness for tactical military applications may be realized with the advent of the diode-pumped alkali laser (DPAL). Pumping a gas-phase medium with large diode arrays combines the best features of electrically driven lasers with the inherent thermal management advantages of a gas laser. Indeed, DPALs offer significant promise for high-average-power-performance.¹ The radiation from bars or stacks of diode lasers is absorbed by atomic potassium, rubidium, or cesium. Collision-induced energy transfer populates the upper laser level, and lasing is achieved in the near-IR on the D₁ (pump) line. A rubidium laser pumped by a 1.28kW diode stack with a 0.35nm spectral bandwidth recently achieved 145W average power.² More than 70% of the diode pump power can be converted to the DPAL power when the pump and resonator volumes are mode-matched, and a high fraction of the incident pump radiation is absorbed.³ Hybrid DPAL systems combine efficient diode pumping with the good beam quality and thermal characteristics of gas lasers.

DPAL quantum efficiency is very high (95–98%) and collisional quenching is typically negligible, offering the potential for low waste heat loads. However, cycling of atoms by the pump beam can be $>10^9$ photons/atom-s. The energy of the spin-orbit splitting is lost to waste heat in each cycle. Several recent DPAL demonstrations by us and others have observed negative impacts associated with gain medium heating, and the community is beginning to develop slow-flowing gas handling systems. We have found no significant kinetic problems associated with gas heating.⁴ It is more likely that localized heating induces a spatial variation in alkali atom concentration. A corresponding reduction in pump absorbance would directly impact output power. Here, we describe work showing that pump-beam heating




Figure 1. Diode-pumped alkali metal vapor laser (DPAL) heat pipe for a cesium laser.

induces a radial distribution of absorbance and establishes a significant temperature rise within the pumped volume.

Most DPAL systems have used static glass cells for the gain medium. We use a heat pipe with Brewster-angle windows, as shown in Figure 1. We use a $0.8\text{W}/\text{cm}^2$ pump laser at the D₁ frequency to heat the medium in a $T = 50 - 100^\circ\text{C}$ cesium heat pipe with nitrogen (5Torr) to artificially increase the heat load. The ends of the heat pipe are held at 15°C to avoid deposits of cesium from forming on the windows. These colder regions are often referred to as a condenser and the center an evaporator as the gas medium changes phase in these two distinct regions. The heat pipe contains a stainless steel wire mesh of 150×150 strands per inch rolled four times on the inner wall of the heat pipe, often called the wick. The wick is responsible for the capillary pumping of cesium from the condenser to the evaporator.

We use a $31\mu\text{W}/\text{cm}^2$ diode laser to probe the spectral absorbance of the cesium cell on the D₂ (laser) transition with radial spatial resolution of 2mm. The frequency of the probe

Continued on next page

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 18 JAN 2012		2. REPORT TYPE		3. DATES COVERED 00-00-2012 to 00-00-2012	
4. TITLE AND SUBTITLE Temperature Gradients In Diode-pumped Alkali Lasers				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Institute of Technology, Department of Engineering Physics, Wright-Patterson AFB, OH, 45433				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES SPIE Newsroom, January 18, 2012					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			
unclassified	unclassified	unclassified	Same as Report (SAR)	4	




Figure 2. Probe laser absorption spectra at various radial positions (x).

laser is scanned by 20GHz across the optically thick hyperfine structure, revealing absorbances of 1–5 (see Figure 2). The larger hyperfine splitting in the ground state of 9192.6MHz is easily resolved. The pump beam is located off-axis at $x=10$ mm. The spectral features are modified by several effects: depopulation of the ground state ($F'' = 4$ component) by the pump laser; changes in the Doppler broadening due to local temperatures; and changes in the Lorentzian lineshape due to local variations in total number density. Spectral simulations of the lineshapes reveal spatially dependent alkali concentrations, temperature, and nitrogen concentrations.

The absorbance outside of the pumped volume is modulated by up to a factor of two when the pump beam is blocked, suggesting significant temperature gradients. Figure 3 shows the radial distribution of absorbance when the probe beam is detuned by 2GHz to the red side of the $F''=2$ hyperfine component. When the pump beam is blocked, the absorbance is independent of position. When the pump beam is active and displaced from the center of the pipe at $x=10$ mm, the absorbance is reduced within the pump beam and enhanced by a factor of two outside of the pumped volume. Heating occurs within the pumped volume, reducing the local alkali concentration. Pump absorption is reduced, leading to lower DPAL output power. We have characterized the dependence of the temperature profiles on pump power, nitrogen pressure, and heat pipe temperature.

In summary, we have investigated heat loads in DPALs using a diode laser to probe the radial dependence of the absorbance. The absorbance outside of the pumped volume is modulated by




Figure 3. Spatially resolved absorbance, $A = -\ln(I_t/I_0)$, at -2 GHz detuning.

up to a factor of two when the pump beam is blocked, suggesting significant temperature gradients that are detrimental. Ideal DPAL system performance can be restored by properly designing the alkali concentration in the presence of the heat load. We are now prepared to study temperature gradients in high-power DPAL devices.

Author Information

Charles Fox and Glen Perram
Department of Engineering Physics
Air Force Institute of Technology
Wright-Patterson AFB, OH

Charles Fox completed his MS in aeronautical engineering at the Air Force Institute of Technology in March 2011 and is now pursuing a PhD in optical science and engineering.

Glen Perram has served as a member of the faculty since 1989. He is a fellow of the Directed Energy Professional Society and recently published a book on laser weapons systems.

References

1. W. F. Krupke, R. J. Beach, V. K. Kanz, and S. A. Payne, *Resonance transition 795-nm rubidium laser*, *Opt. Lett.* **28**, pp. 2336–2338, 2003. doi:10.1364/OL.28.002336
2. J. Zweiback, A. Komashko, and W. F. Krupke, *Alkali-vapor lasers*, *Proc. SPIE* **7581**, p. 75810G, 2010. doi:10.1117/12.843594

Continued on next page

3. B. V. Zhdanov, J. Sell, and R. J. Knize, *Multiple laser diode array pumped Cs laser with 48 W output power*, **Electron. Lett.** **44**, pp. 582–583, 2008. doi:10.1049/el:20080728
4. G. D. Hager and G. P. Perram, *A three-level analytic model for alkali vapor lasers: part I. Narrowband optical pumping*, **Appl. Phys. B** **101**, pp. 45–56, 2010. doi:10.1007/s00340-010-4050-6