

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 11-28-2011		2. REPORT TYPE Final Report		3. DATES COVERED (From - To) 07/01/2008-06/30/2011	
4. TITLE AND SUBTITLE High Transition Temperature Quantum Interference Filters				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER FA9550-08-1-0305	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Shane Cybart and R. C. Dynes				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of California Department of Physics 366 LeConte Hall Berkeley, CA. 94720				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR 875 N. Randolph St. Suite 325 Arlington, VA 22203				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-OSR-VA-TR-2012-0262	
12. DISTRIBUTION / AVAILABILITY STATEMENT Public distribution/availability					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT We have fabricated and tested large scale arrays of Josephson junctions. Some devices have as many as 150,000 junctions in a single device. To aid in device design we have also developed a numerical simulation program in matlab to simulate voltage field characteristics for these arrays. Our numerical simulation code supports the modeling of 2 dimensional array structures and takes into account mutual interactions between all of the squids in the array. The results are in excellent agreement with our experimental measurements. We have also performed measurements of the critical current noise in our Josephson junctions and have been testing arrays in flux locked loops.					
15. SUBJECT TERMS Superconductivity, SQUID arrays					
16. SECURITY CLASSIFICATION OF: Unclassified			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code)

High Transition Temperature Superconducting Quantum Interference Filters
FA 9550-08-1-0305 Final Report: July 1, 2008 - June 30, 2011

R.C. Dynes and S.A. Cybart

Abstract:

We have fabricated and tested large scale arrays of Josephson junctions. Some devices have as many as 150,000 junctions in a single device. To aid in device design we have also developed a numerical simulation program in Matlab to simulate voltage magnetic field characteristics for these arrays. Our numerical simulation code supports the modeling of 2 dimensional array structures and takes into account mutual interactions between all of the squids in the array. The results are in excellent agreement with our experimental measurements. We have also performed measurements of the critical current noise in our Josephson junctions and have been testing arrays in flux locked loops.

Narrative:

Arrays of Josephson junctions or SQUIDs are of great interest for communication electronics because sensors built from them can have high-linearity, wide bandwidth and a large dynamic range. These sensors detect the magnetic field component of an incoming signal opposed to the electric field component. Quality devices have been demonstrated in low temperature superconductors but the cooling requirements to achieve 4K, exceed the size weight and power for most practical applications. Therefore our group has been investigating arrays fabricated from YBCO that can operate at 77K.

We built two different configurations of array for this grant. The first contained a series array of 500 SQUIDs embedded into a coplanar wave guide,[1] and the second was a 2D array with tens of thousands of junctions built into a superconducting microstrip.[2] Measurements of these devices revealed that when the SQUIDs are placed in close proximity with one another mutual interactions between them significantly reduce the modulation voltage and alter linearity.[3] We were able to confirm this by developing computer simulation software that solves the differential equations for all of the junctions in the array simultaneously to generate voltage- magnetic field characteristics.[4] The results obtained from our simulations are in excellent agreement with experimental measurements for many different 2D array configurations. Using our simulation program we have developed new array geometries optimized for maximum voltage modulation and transfer function linearity. [5]

We have also improved our fabrication process by eliminating an initial photolithography patterning step and moving to an all electron beam lithography process. The new process reduces the turn-around time by a factor of 2. We have also improved our reactive ion etch nanopatterning of implantation masks [6] to accommodate higher implant energies. In addition we performed an aging and stability study on older Josephson junctions fabricated using our

technique. We found that these junctions are very robust and that their properties namely I_c and R_n have changed very little over the course of 7 years.

The results obtained under this grant will greatly help this technology move forward in to the future. This grant has supported 1 postdoc, 2 graduate students, and 6 undergraduate student researchers.

Publications:

- [1] S. A. Cybart, S. M. Wu, S. M. Anton, I. Siddiqi, J. Clarke and R. C. Dynes, “*Incommensurate arrays of high-transition temperature SQUIDS from ion damage Josephson junctions*”, Appl. Phys. Lett., vol 93, 182502 2008.
- [2] S. A. Cybart, S. M. Anton, S. M. Wu, J. Clarke, and R. C. Dynes, “*Very large scale integration of nanopatterned $YBa_2Cu_3O_{7-\delta}$ Josephson junctions in a two-dimensional array*”, Nano Lett., nl901785j, 2009.
- [3] S. A. Cybart, S. M. Anton, J. A. Drisko, T. Dalilouch, J. M. Parker, S. M. Wu, E. Cho, J. Clarke, and R. C. Dynes, “*Measurements and simulations of two dimensional arrays of SQUIDS from ion damage Josephson junctions*”, in preparation.
- [4] T. Dalilouch, S. A. Cybart, S. M. Anton, J. Clarke, and R. C. Dynes, “*Comparison of numerically simulated transfer functions for two-dimensional Josephson arrays with different geometries*”, in preparation.
- [5] S. M. Anton, S. A. Cybart, R. C. Dynes, “*Algorithm for designing SQUID arrays with high linearity*” in preparation.
- [6] S. A. Cybart, E. Ulin-Avila, and R. C. Dynes, “*Angled reactive ion etching of high-aspect-ratio nanostructures*”, in preparation.
- [7] E. Y. Cho, T. J. Wong, S. A. Cybart, Ke Chen, R. C. Dynes, “*Long-term stability of high-transition temperature Josephson junctions prepared from ion irradiation*”, in preparation
- [8] S. M. Wu, S. A. Cybart, P. Yu, M. D. Rossel, J. X. Zhang, R. Ramesh and R. C. Dynes, “*Reversible control of exchange bias in a multiferroic field effect device*”, Nature Materials., nmat2803, 2010.