

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 06-03-2011		2. REPORT TYPE Final Performance Report		3. DATES COVERED (From - To) 01 JUN 2009 - 31 MAY 2010	
4. TITLE AND SUBTITLE Acquisition of a scanning laser vibrometer system for experimental studies on nonparametric nonlinear system identification and aeroelastic instability suppression				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER FA9550-09-1-0455	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Lawrence A. Bergman, Alexander F. Vakakis, D. Michael McFarland				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Illinois Dept. of Aerospace Eng. Office of Bus and Finan Svcs 104 South Wright St. 1901 South First St., Suite A Urbana, IL 61801 Champaign, IL 61820-7406				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR 875 N. Randolph St. Room 3112 Arlington, VA 22203				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL - OSR - VA - TR - 2012 - 0550	
12. DISTRIBUTION / AVAILABILITY STATEMENT Unlimited-A					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT The PIs' current research and development, funded by AFOSR, aims to develop novel means of vibration control for aerospace systems, system identification procedures for strongly nonlinear dynamical systems, and a fully passive limit cycle oscillation (LCO) suppression system for a model generic transport wing (GTW) previously designed, built and tested in the TDT at NASA Langley. Initial efforts by the PIs led to the development of the Nonlinear Energy Sink (NES), a completely passive nonlinear mechanical device that, when physically attached to a vibrating primary system, draws energy from that system into itself in a one-way, irreversible fashion and effectively dissipates it. Later efforts by the PIs resulted in the formulation of the NSI method for system ID, combining local and global components to account for the sensitivity of strongly nonlinear systems to initial conditions and forcing. The PIs' final work, still ongoing, in conjunction with NextGen Aeronautics, Inc. and colleagues at Texas A&M University, will result in the design of an NES-based LCO suppression system housed in a winglet, specifically designed for the GTW. Upon completion of rehabilitation and modifications to the wing to accommodate the winglet/NES, the full system will be ready for additional testing in the TDT.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF: None			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON Lawrence A. Bergman
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code) 217-333-4970

Final Performance Report to AFOSR

Principal Investigators

Prof. Lawrence A. Bergman
Department of Aerospace Engineering
306 Talbot Laboratory, MC-236
104 South Wright Street
Phone: 217-333-4970; Fax: 217-244-0720
Email: lbergman@illinois.edu

Prof. Alexander F. Vakakis
Department of Mechanical Science and Engineering
Mechanical Engineering Building, MC-244
1206 West Green Street
Phone: 217-333-3048
Email: avakakis@illinois.edu

Res. Assoc. Prof. D. Michael McFarland
Department of Aerospace Engineering
306 Talbot Laboratory, MC-236
104 South Wright Street
Phone: 217-244-9573
Email: dmcf@illinois.edu

University of Illinois at Urbana-Champaign
Urbana, IL 61801

(DURIP 09): ACQUISITION OF A SCANNING LASER VIBROMETER SYSTEM FOR EXPERIMENTAL STUDIES ON NONPARAMETRIC NONLINEAR SYSTEM IDENTIFICATION AND AEROELASTIC INSTABILITY SUPPRESSION

Grant No.: AF FA9550-09-1-0455 (EQUIPMENT ONLY)
Grant Period: 01 June 09 – 31 May 10
Grant Monitor: Dr. David Stargel

Acquired Equipment: Scanning Laser Vibrometer (see below for details)

1. **Polytec Model PSV-400-H4 Turnkey 4-Channel High Performance, 80 kHz Bandwidth Vibscan System and Model UHF-120 High Frequency Laser Doppler Vibrometer, with University Maintenance, Software Updates and Training (\$354,566)**
2. **Dell T710 Server, 48 GB RAM, 2 X5560 Xeon Processors (\$8,536)**

Executive Summary:

The PIs' current research and development, funded by AFOSR, aims to develop novel means of vibration control for aerospace systems, system identification procedures for strongly nonlinear dynamical systems, and a fully passive limit cycle oscillation (LCO) suppression system for a model generic transport wing (GTW) previously designed, built and tested in the TDT at NASA Langley. Initial efforts by the PIs led to the development of the Nonlinear Energy Sink (NES), a completely passive nonlinear mechanical device that, when physically attached to a vibrating primary system, draws energy from that system into itself in a one-way, irreversible fashion and effectively dissipates it. Later efforts by the PIs resulted in the formulation of the NSI method for system ID, combining local and global components to account for the sensitivity of strongly nonlinear systems to initial conditions and forcing. The PIs' final work, still ongoing, in conjunction with NextGen Aeronautics, Inc. and colleagues at Texas A&M University, will result in the design of an NES-based LCO suppression system housed in a winglet, specifically designed for the GTW. Upon completion of rehabilitation and modifications to the wing to accommodate the winglet/NES, the full system will be ready for additional testing in the TDT

Significant Work Accomplished:

The high-end computer provides an effective platform for simulations required to estimate the stability characteristics of the GTW, both with and without the NES-based LCO suppression system in order to evaluate performance. CFD code CAPTSDv has been extensively employed to obtain data needed for NES design, while UNS3D, a more sophisticated Reynolds-averaged Navier-Stokes code, has been used to verify and validate CAPTSDv results.

The laser vibrometer has, to date, been utilized during ground vibration testing (GVT) of the GTW at UIUC. Accurate, non-contacting velocity measurements were obtained at 40 locations over the surface of the GTW in its bare configuration, with an NES installed at the wing tip in lock-down, and with a fully functional NES in place, in order to verify that the strongly nonlinear behavior of the NES couples strongly to the second bending mode and first torsional mode of the wing. These modes were observed in prior analysis and testing and again in current simulations to cause the LCO. Selected results from the GVT are included in Figures 1 through 4, below.



Figure 1: The GTW as obtained from NASA Langley on an optical table at UIUC, with NES installed on the wing tip in lock-down position, ready for ground vibration testing.



Figure 2: Photo showing shaker/stinger attachment to the GTW and wiring from internal sensors.




Figure 3: Mode shapes of GTW with NES in lock-down acquired with Polytec PSV-400 LDV. Left: 2nd bending (11.25 Hz); right: 1st torsion (30.31 Hz).




Figure 4: Accelerance frequency response functions obtained during GVT, comparing performance of GTW with NES under lock-down (linear), with NES in operating mode under moderate loading (NL 480N), and with NES in operating mode under peak loading (NL 800 N). Data acquired with Polytec PSV-400 LDV. Note the strong coupling of the NES with the second bending mode under peak loading (circled in red), resulting in nearly an order of magnitude of attenuation.