



Environment, Energy Security & Sustainability

SYMPOSIUM & EXHIBITION

Waste to Energy Potential – A High Concentration Anaerobic Bioreactor

Presenter: Scott Murphy & Rebecca
Robbennolt

ARCADIS/Malcolm Pirnie

Date 23 May 2010

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 23 MAY 2012		2. REPORT TYPE		3. DATES COVERED 00-00-2012 to 00-00-2012	
4. TITLE AND SUBTITLE Waste to Energy Potential - A High Concentration Anaerobic Bioreactor				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) ARCADIS/Malcolm Pirnie,630 Plaza Drive, Suite 200 ,Highlands Ranch,CO,80129				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES Presented at the NDIA Environment, Energy Security & Sustainability (E2S2) Symposium & Exhibition held 21-24 May 2012 in New Orleans, LA. U.S. Government or Federal Rights License					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 32	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Introduction

- Renewable energy and landfill diversion key for Department of Defense.
- *The National Defense Authorization Act of 2010:*
 - 25% of energy needs from renewable energy sources by 2025.
- *Strategic Sustainability Performance Plan 2011:*
 - Divert 50% of non-hazardous solid waste from the waste stream by 2015.
 - 254 million tons of solid waste each year
- Some states have similar goals and objectives.
 - Organic waste collection programs exist in FL, CA, WA, AZ VA, MN, OH, PA, MD, and NC.
- Solid waste management an increasing challenge
 - high cost of landfill management,
 - transportation costs,
 - tipping fees, etc.
- ARCADIS' High Concentration Anaerobic Bioreactor (HCAB) process addresses these issues.



Anaerobic Digestion

- What does it do?
 - Offers sustainability by addressing renewable energy, waste diversion, and beneficial reuse
- How does it work?
 - Uses anaerobic digestion in an energy-efficient, minimum-capacity tank, resulting in high energy output
 - Uses the organic portion of solid waste (such as food waste, paper products, and agricultural waste) to fuel an anaerobic digestion process
 - bacteria consume approximately 50-70% of the solids placed in the bioreactor and, generate a biogas
- What do you get?
 - Biogas that can be used to generate electricity
 - Residual solids that can be used as a soil amendment



Anaerobic Digestion Steps

Solubilization & breakdown of complex organics by microbes in O_2 depleted environment

Complex microbes and fermentative bacteria break down organic carbon to VFAs



Acetogens break down VFAs to $CH_3CO_2^-$ and H_2^+

Acetoclastic methanogens break down $CH_3CO_2^-$ to CO_2 and H_2O

Hydrogenotrophic methanogens convert the H_2 and CO_2 to CH_4



HCAB Timeline



HCAB Operating Process

- What is the HCAB?
 - A unique combination of existing technologies. Advancements allow the reactor to be operated at high solids concentrations
- What is special about it?
 - Patented internal rake arm for solids control
 - High solids concentration feedstock
 - High volatile solids loading
- Practical features:
 - The process uses naturally occurring bacteria, also found in landfills, wastewater digesters
 - The equipment design is based on standard equipment
 - There is no need for the purchase of specialized spare parts



Eglin AFB Project Overview

- ARCADIS studied available waste streams at Eglin Air Force Base and determined the quantity and quality of the waste
- ARCADIS installed a pilot system capable of processing up to 700 pounds per day of organic waste
- A full scale system is planned, capable of processing municipal solid waste
- Currently the Pilot Study has been completed and design of the full-scale system is underway





HCAB Pilot Operation, Eglin AFB


August 2011 through March 2012

Objectives of the Demo

- Establish the inoculation/startup procedures
- Optimize presorting requirements
- Evaluate biogas quality
- Establish biogas pre-conditioning requirements
- Understand the cause of upset conditions
- Determine
 - optimal mixture of feedstock
 - biological kinetics at pseudo-steady state
 - optimal solids concentration
 - torque requirements for mixing
 - optimal operating temperature
 - solids and volatile solids destruction
 - biogas volume
 - nutrient value of waste sludge
 - composition of wastewater side streams



Process Flow Diagram



Pilot Plant



Field Measurement Summary

Mix Tank	Reactor	Waste Tank
pH	Methane	Load Cell Data
Temperature	Gas flow	
Load Cell Data	Torque	
Feedstock Density	Motor speed	
	Solids Density	
	pH	
	Temperature	
	Pump status	



Snapshot - Data Collection

O&M Data Collection - Eglin Air Force Base HCAB

Sampling and Parameters |

Collection Point: Reactor

Collection Points Back

Current Trip: **Arrival**

View Data Collection Times Unit Conversions View Arrival and Departure

Parameter Description	Arrival	Unit	Arrival Remark	Equipment Min	Equipment Max	Design Min	Design Max	Permit Min	Permit Max
HCAB Temperature	28.4	C		-999999	999999	35	40.5	-999999	999999
HCAB pH Pre-Mix Tank Feed	7.481	SU		-999999	999999	0	14	-999999	999999
HCAB pH Post-Mix Tank Feed		SU		-999999	999999	0	14	-999999	999999
Torque		ft-lbs		-999999	999999	0	1833	-999999	999999
Motor Speed		Hz		-999999	999999	0	999999	-999999	999999
Gas Flow		LPM		-999999	999999	0	999999	-999999	999999
Methane (CH4)	60.9	%		-999999	999999	60	75	-999999	999999
Carbon Dioxide (CO2)	38	%		-999999	999999	0	30	-999999	999999
Oxygen (O2)	1.2	%		-999999	999999	0	999999	-999999	999999
Hydrogen Sulfide (%)		%		-999999	999999	0	4	-999999	999999
Balance	-0.1	%	Calculated on 10/6/2011	-999999	999999	0	100	-999999	999999
Ammonia Pre-Urea Addition	1030	mg/L		-999999	999999	0	999999	-999999	999999
Ammonia Post-Urea Addition		mg/L		-999999	999999	0	999999	-999999	999999

General Comments about this location:

Add/Edit Sampling Information 1 Sample(s) Collected

Feedstock Addition



Operational Summary

Feedstock	Mix Tank	Bioreactor	Waste Tank
Collection	Biosolids Addition	Waste/ Recycle	Waste Solids Storage
Preparation	Mixing	Biogas Production	Sampling
Grinding		Sampling	
Sampling		Field Analysis Sampling	



Composition Summary

- Composition testing determined the effects of different waste streams on the overall chemistry.

Composition 1

- Food Waste
- Paper Towel Waste

Composition 2

- Food Waste
- Paper Towel Waste
- Food Grade Grease
- Stable Waste
- Wood Waste





Results

Data Compilation



- Measure actual results against the target goals & objectives
- Extrapolate the results to a full scale system
- Determine actual energy output potential for a full scale system




Volatile and Total Solids


- Volatile Solids = food for microbes
 - high VS loading and corresponding high VS destruction = higher efficiency
- Volatile Solids in Feedstock
 - Goal 80 %
 - Actual for Composition 1: Average 92 %
 - Actual for Composition 2: Average 70%
- Volatile Solids Destruction in bioreactor
 - Goal 60 %
 - Actual for Composition 1: Average 79.4%
 - Actual for Composition 2: Average 76.8%




Volatile Solids Composition



Volatile Solids Destruction



Total Solids Destruction




Biogas Production

- Biogas contains methane = fuel source
- Biogas measured by flow meter
- Biogas generated was correlated to mass of volatile solids destroyed
- Biogas produced per unit of VS destroyed
 - Goal 1,222 ml/g VS destroyed
 - Composition 1 – 1,289 ml/g VS destroyed
 - Composition 2 – 1,076 ml/g VS destroyed
- Methane Content
 - Goal 70 %
 - Actual for Composition 1 – 55%
 - Actual for Composition 2 – 53%



mL of Biogas Produced




Operational Challenges



- Mass of Feedstock
- Mix Tank pH Stability
- Bioreactor Temperature
- Bioreactor Foaming
- Materials Processing
 - Mechanical/Pumping
 - Inert Material
- Biogas Measurement





Conclusions

Research and Development Demonstration

R&D *successfully demonstrated*:

- Technology's ability to use organic waste to generate a renewable energy source
- Alternative to landfill
- Total and Volatile solids destruction
- Energy production met or exceeded target ranges
- Best feedstock - food waste and paper towels
- Design adaptations required for full scale
- Economic Evaluation ongoing - economics of full scale system dependent on available feedstock




Full Scale Design Sustainability Objectives

Ongoing activities for the marketable full-scale product

- ✓ Further development of the Technology (continued R&D)
- ✓ Confirm O&M cost for a full scale system
- ✓ Scalable design criteria to enhance operation and biogas production
- ✓ Applicability to larger scale
- ✓ Verification of power generation using a microturbine
- ✓ Refinement of the financial model and ROI for full scale





E²
S²

Scalable Design

Full Scale Design Objectives

- Maximize VSL / minimize reactor footprint
- Minimize equipment power consumption
- Minimize building footprint
- Maximize efficiency for MSW sorting
- Maximize biogas production/energy production
- Maximize waste application
- Maximize TS input to the HCAB
- Consider other applications, such as forward operating installations



Acknowledgments

ARCADIS would like to thank the following:

- Mr. Kevin Porteck and Margaret Douchand
AFCEE
- Mr. Jim Reese
Eglin Air Force Base
- Mr. Dennis Lundquist, Chris Coonfare, and Dr. Mike Von
Fahnestock
Battelle National Lab
- Mr. Robert Breckenridge
Idaho National Lab
- Ms. Hilda R. Quinones
TEAM Integrated Engineering, Inc.



Imagine the result

Presenter: Scott Murphy, ARCADIS
Title: Waste to Energy Potential
Email: scott.murphy@arcadis-us.com

