

Time-Domain Simulations of Problems in Ocean Acoustics

John B. Schneider
School of Electrical Engineering and Computer Science
Washington State University
P.O. Box 642752 Pullman, WA 99164-2752
phone: (509) 335-4655 fax: (509) 335-3818 email: schneidj@eecs.wsu.edu

Award Number: N00014-05-1-0101
<http://www.eecs.wsu.edu/~schneidj/>

LONG-TERM GOALS

To develop time-domain numerical methods for the study of propagation and scattering of acoustic and elastic waves in the shallow water environment.

OBJECTIVES

To develop new, and enhance existing, numerical methods; to establish the accuracy, robustness, flexibility, and tractability of these methods; and to apply these methods to meaningful practical problems. To create a robust software suite for the application of the methods and to develop techniques for visualizing the propagation of scalar and vector fields in complex environments.

APPROACH

We have focused our attention on the development and use of finite-difference time-domain (FDTD) methods. Various forms of these time-domain techniques, which are flexible, robust, and generally simple to implement, have been used in a variety of disciplines to solve a wide range of problems. We have worked, and continue to work, to establish the accuracy of our proposed acoustic FDTD techniques by comparing numeric results to exact solutions for canonical problems or to results obtained using other numerical methods.

WORK COMPLETED

Equations were derived which rigorously codify the propagation of fields in FDTD grids. These equations were then used to construct a nearly perfect total-field/scattered field boundary (which is used to inject energy into the grid). Initially this work was restricted to a homogeneous medium which surrounds an arbitrary inhomogeneous medium. This work has subsequently been extended to layered media. This required the derivation of the numeric reflection and transmission coefficients which pertain to the FDTD grid. Further extensions to the theory now permit incident grazing angles less than the critical angle, lossy media, and the insonification of semi-infinite structures (such as wedges).

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2005		2. REPORT TYPE		3. DATES COVERED 00-00-2005 to 00-00-2005	
4. TITLE AND SUBTITLE Time-Domain Simulations of Problems in Ocean Acoustics				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Washington State University,School of Electrical Engineering and Computer Science,P.O. Box 642752 ,Pullman,WA,99164				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES code 1 only					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 7	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

RESULTS

The FDTD method is obtained by discretizing the differential equations that govern the underlying system. Using a Cartesian grid, the method provides an exceedingly simple way in which to express future fields (i.e., unknown fields) in terms of past fields (known fields). For propagation in a homogeneous region, the traditional FDTD method is accurate to second-order—that is, doubling the number of grid points per wavelength reduces inherent numerical errors by a factor of four.

The behavior of fields and accuracy of the FDTD method at material interfaces are much more complicated than in a homogeneous region. We previously derived exact expressions describing the behavior of plane waves at planar boundaries [1,2]. Our previous work considered normal incidence and has recently been extended to oblique incidence [3]. The derivations in [3] show rigorously what has long been assumed in practice: that the optimum density for nodes along the interface is the average of the densities to either side.

Additionally we have examined and developed ways to minimize the errors associated with the “stairstep approximation” which is inherent when modeling continuously varying surfaces in the FDTD method [4-9]. The work recently published in *The Journal of the Acoustical Society of America* showed how employing a simple modification of the equations used to update the fields adjacent to a rigid boundary could significantly improve the accuracy of the simulation [9].

Our investigations of the discretized worlds of FDTD methods have led us to a better understanding of numeric artifacts associated with resonances and to ways of alleviating these artifacts. Part of this work was presented as an invited talk in a special session organized by Prof. Allen Taflov (one of the co-founders of the FDTD method) [10]. This work is further described in a paper which has recently appeared in *IEEE Transactions on Antennas and Propagation* [11]. In that work we show how the anisotropic dispersion inherent in the traditional “Yee” FDTD algorithm can cause rather bizarre behavior in the resonant modes of a canonical resonator. Modes which are degenerate in the continuous (or “real”) world can split into multiple modes. On the other hand, modes which are distinct in the continuous world may be degenerate in the discrete FDTD world. Additionally, even modes that are not split or recombined in some spurious manner in the FDTD world can nevertheless be shifted from the true resonant frequency that pertains in the continuous world. Our work provides a way to quantify this behavior exactly without ever needing to perform an FDTD simulation.

Given this understanding of the traditional FDTD technique, we were motivated to explore a technique which was more isotropic than the traditional FDTD technique. Thus, we developed a variation of the promising FDTD scheme proposed by Eric Forgry (*IEEE Transactions on Antennas and Propagation*, **50**(7):983–996, 2002). This algorithm suffers much less grid dispersion and anisotropy than more traditional FDTD formulations but still retains the local nature of the standard update equations. The acoustic implementation of this algorithm was described in a paper which recently appeared in the *Journal of Computational Acoustics* [12].

The Yee FDTD algorithm can provide exact solutions to one-dimensional problems when operated at the so-called magic time step (i.e., when the spatial step size is equal to the speed of light times the

temporal step size). Here “exact” is taken to mean the field propagates without dispersion error or other numeric artifacts beyond those which are dictated by the finite precision of the computer. Unfortunately there is no magic time step in higher dimensions. However we have recently developed a theoretical framework for multi-dimensional algorithms that have the same exact properties as the one-dimensional Yee algorithm when operated at a particular time step. The proposed technique uses vector operators which, instead of being defined at a point such as with the usual gradient, divergence, and curl operators, are defined over spheres. Due to their inherent symmetry, these spatial operators have the same properties in all directions. With a judicious choice of the temporal step size the temporal errors can cancel the spatial errors and the algorithm is exact. However, although the framework for the algorithm has been developed, no practical (i.e., computationally efficient) algorithm has yet been developed. It should also be noted that the method is only theoretically exact on an infinite grid—a finite grid will introduce some inherent error but that error will be smaller than traditional FDTD techniques. Nevertheless proof-of-concept implementations of the algorithm (which are quite computationally expensive) have been used to demonstrate the validity of the technique and the improvements the algorithm can provide over other FDTD implementations. The algorithm also has interesting properties such as unconditional stability for an arbitrary temporal step size. Some of our work on this algorithm was presented as an invited talk at the 2003 URSI/Antennas and Propagation Symposium [13]. This work is further described in a recent publication in the *Journal of Computational Physics* [14] and a Ph.D. dissertation [15] (the author of which was partially supported under this grant).

The understanding we have obtained of the FDTD method has provided a complete quantification of the way in which plane waves propagate in the discrete FDTD world. Using this knowledge we were able to construct an enhancement to the total-field/scattered-field (TFSF) boundary, which is a boundary used to introduce field into the FDTD grid. This enhancement, which is nominally exact, can provide an enormous improvement over the traditional implementation (better than a 100 dB reduction in errors in many situations). This work is described in a paper recently published in *IEEE Transactions on Antennas and Propagation* [16]. Additionally Prof. Taflové invited the PI to contribute a section [17] to the 2005 edition of his FDTD book [18] which has come to be regarded as the authoritative source for FDTD-related information.

Our work on the implementation of TFSF boundaries has been extended to layered media—either rigid, pressure-release, or penetrable boundaries. This work is described in [3]. The capabilities this technique provides opens many new avenues of investigation. For example, the scattering from rough surfaces can be explored without having to resort to using Gaussian-tapered plane wave excitation (which is only an approximate solution to the wave equation) which was used in [19,20]. Furthermore, the scattering from semi-infinite objects (such as wedges or screens) is easily accommodated as described in [3].

We continue to expand the capabilities of our TFSF implementation. We have developed an efficient implementation for 3D problems in which the incident direction is orthogonal to one of the grid axes. The technique can also handle lossy materials and the incident angle may be sub-critical.

We continue to maintain a Web site, www.fdttd.org, that seeks to list all archival publications related to the FDTD method. This site solicits input, in the form of comments posted about work appearing in the archival literature, from the entire community interested in the FDTD method (whether applied to acoustics, electromagnetics, or solid mechanics). We have also made code available there which can be used to solve various propagation problems.

IMPACT/APPLICATIONS

Accurate and flexible numerical methods allow researchers to conduct any number of experiments without having to resort to actual field experiments, i.e., the experiment is conducted on the computer. Our work enables more accurate and more efficient numerical solutions to a wide range of problems in acoustics, electromagnetics, and continuum mechanics.

TRANSITIONS

Much of the knowledge we have gained has been disseminated via publications and conference presentations. Additional material is available via the Web. Please refer to the Web site given in the header for copies of the PI's publications or www.fdttd.org for other material pertinent to the FDTD method.

RELATED PROJECTS

This work is related to research in both high-frequency acoustics and long-range propagation. Numerical models, such as the FDTD method, can be used to predict the fields scattered from small objects under short-wavelength insonification or the propagation of long-wavelength signals over limited regions of the ocean. This work is related to that being done by several other ONR-sponsored researchers.

REFERENCES

- [1] J. B. Schneider and R. J. Kruhlak, "Plane Waves and Planar Boundaries in FDTD Simulations," IEEE AP-S International Symposium and URSI Radio Science Meeting, Salt Lake City, UT, Jul. 2000.
- [2] J. B. Schneider and R. J. Kruhlak, "Dispersion of Homogeneous and Inhomogeneous Waves in the Yee Finite-Difference Time-Domain Grid," *IEEE Trans. Microwave Theory and Techniques*, vol. 49, no. 2, pp. 280–287, 2001.
- [3] J. B. Schneider and K. Abdijalilov, "Analytic Field Propagation TFSF Boundary for FDTD Problems Involving Planar Interfaces: Part I—PECs, TE, and TM," to be submitted to *IEEE Trans. Microwave Theory and Techniques*.
- [4] F. D. Hastings, J. B. Schneider, and S. L. Broschat, "A Monte Carlo FDTD Technique for Rough Surface Scattering," *IEEE Trans. Antennas Propagat.*, vol. 43, no. 11, pp. 1183–1191, 1995.

- [5] F. D. Hastings, J. B. Schneider, and S. L. Broschat, "A Finite-Difference Time-Domain Solution to Scattering from a Rough Pressure-Release Surface," *J. Acoust. Soc. Am.*, vol. 102, no. 6, pp. 3394–3400, 1997.
- [6] J. B. Schneider, C. L. Wagner, and R. J. Kruhlak, "Simple Conformal Methods for FDTD Modeling of Pressure-Release Surfaces," *J. Acoust. Soc. Am.*, vol. 104, no. 6, pp. 3219–3226, 1998.
- [7] F. D. Hastings, J. B. Schneider, S. L. Broschat, and E. I. Thorsos, "An FDTD Method for Analysis of Scattering from Rough Fluid-Fluid Interfaces," *IEEE Journal of Oceanic Engineering*, vol. 26, no. 1, pp. 94–101, 2001.
- [8] J. B. Schneider and J. G. Tolan, "A Locally Conformal Method for Modeling Rigid Boundaries in the FDTD Method," *J. Acoust. Soc. Am.*, vol. 108, no. 5, pt. 2, pp. 2563, Newport Beach, CA, Dec. 2000.
- [9] J. G. Tolan and J. B. Schneider, "Locally Conformal Method for Acoustic Finite-Difference Time-Domain Modeling of Rigid Surfaces," *J. Acoust. Soc. Am.*, vol. 114, no. 5, pp. 2575–2581, 2003.
- [10] C. L. Wagner and J. B. Schneider, "Using the Dispersion Relation to Understand Finite-Difference Time-Domain Worlds," International Conference on Electromagnetics in Advanced Applications (ICEAA 01), Torino, Italy, pp. 375–378, Sep. 2001.
- [11] C. L. Wagner and J. B. Schneider, "On the Analysis of Resonators Using Finite-Difference Time-Domain Techniques," *IEEE Trans. Antennas Propagat.*, vol. 51, no. 10, pp. 2885–2890, 2003.
- [12] C. L. Wagner and J. B. Schneider, "An Acoustic Finite-Difference Time-Domain Algorithm with Isotropic Dispersion," *J. Computational Acoust.*, vol. 13, no. 2, pp. 365–384, 2005.
- [13] C. L. Wagner and J. B. Schneider, "Toward the Creation of a Magic Time Step in Three-Dimensional FDTD Algorithms," IEEE AP-S International Symposium and URSI Radio Science Meeting, Columbus, OH, Jun. 2003.
- [14] C. L. Wagner, "Theoretical Basis for Numerically Exact Three-Dimensional Time-Domain Algorithms," *J. Comp. Phys.*, vol. 205, no. 1, pp. 343–356, 2005.
- [15] C. L. Wagner, "Theoretical Basis for Numerically-Exact Three-Dimensional Time-Domain Algorithms," Pullman, WA, Washington State University, 2004.
- [16] J. B. Schneider, "Plane Waves in FDTD Simulations and a Nearly Perfect Total-Field/Scattered-Field Boundary," *IEEE Trans. Antennas Propagat.*, vol. 52, no. 12, pp. 3280–3287, 2004.
- [17] J. B. Schneider, "Advanced Dispersion Compensation in the TF/SF Technique," section 5.9 of [18].
- [18] A. Taflov and S. Hagness, *Computational Electrodynamics: The Finite-Difference Time-Domain Method*, 3 ed., Boston, MA, Artech House, 2005.

- [19] F. D. Hastings, J. B. Schneider, and S. L. Broschat, "A Monte Carlo FDTD Technique for Rough Surface Scattering," *IEEE Trans. Antennas Propagat.*, vol. 43, no. 11, pp. 1183–1191, 1995.
- [20] F. D. Hastings, J. B. Schneider, S. L. Broschat, and E. I. Thorsos, "An FDTD Method for Analysis of Scattering from Rough Fluid-Fluid Interfaces," *IEEE J. Oceanic Eng.*, vol. 26, no. 1, pp. 94–101, 2001.

PUBLICATIONS

- [1] C. L. Wagner and J. B. Schneider, "An Acoustic Finite-Difference Time-Domain Algorithm with Isotropic Dispersion," *J. Computational Acoust.*, vol. 13, no. 2, pp. 365–384, 2005. [published, refereed]
- [2] C. L. Wagner, "Theoretical Basis for Numerically Exact Three-Dimensional Time-Domain Algorithms," *J. Comp. Phys.*, vol. 205, no. 1, pp. 343–356, 2005. [published, refereed]
- [3] C. L. Wagner, "Theoretical Basis for Numerically-Exact Three-Dimensional Time-Domain Algorithms," Pullman, WA, Washington State University, 2004. [published]
- [4] J. B. Schneider, "Plane Waves in FDTD Simulations and a Nearly Perfect Total-Field/Scattered-Field Boundary," *IEEE Trans. Antennas Propagat.*, vol. 52, no. 12, pp. 3280–3287, 2004. [published, refereed]
- [5] J. B. Schneider, "Advanced Dispersion Compensation in the TF/SF Technique," Sec. 5.9 of *Computational Electrodynamics: The Finite-Difference Time-Domain Method*, 3 ed., A. Taflov and S. Hagness, Boston, MA, Artech House, 2005. [published]