

DESIGN MODELS AND MODEL BASED DESIGN IN FLUID FLOW
WITH APPLICATION TO MICRO AIR VEHICLES
AFOSR FA9550-06-1-0373

Gilead Tadmor
Communications & Digital Signal Processing Center
Northeastern University, Boston, MA 02115

Abstract: Our focus has been on structural enablers for very low order design models and for model-based flow control, including the flow physics underpinnings of low order flow models. Basic theory investigations concentrated primarily on Galerkin models: We derived from the NSE the essential role and form of mean field models and developed a novel none-equilibrium statistical closure and implied sub-grid turbulence models. Mean-field models now predict lift dynamics and high frequency actuation. With harmonically-pure mode-sets, mode interpolation maintains minimum model order across changing operating conditions, and is assisted by a new, efficient POD computation. Experimental studies were done in conjunction with a related MURI project, and complemented independently supported, long-term international team collaborations. We explored new feedback paradigms, including implementing duty ratio feedback modulation of pulsating jets, validated by MAV lift enhancement, and Lagrangian models in feedback for drag reduction behind a 3D bluff body. The research is presented in 7 published / accepted journal papers, 2 under review and 1 in preparation, 2 Book chapters, 17 refereed conference papers and 14 conference abstracts, the material in a forthcoming book, as well as several colloquia presentations and a dedicated short course on flow modeling and control.

1. Enablers for Low Order Galerkin Models (LOGMs) for Control Design

1.1 A basic theory of Galerkin mean field models. Mean field models incorporate low dimensional representations of the bilateral interactions of fast flow-field fluctuations with a slowly varying base flow [2],[J:4,6,9],[BC1],[C:6,16],[P:1,5,7,10,14]. These interactions are fundamental to the transition of flow configuration from linear instability of the steady flow to the marginal stability of attractors' energy levels. In [2] we introduced the *shift mode* as a compact encapsulation of mean flow variations, governed by a Galerkin counterpart of the Reynolds equation. Analyzing the reduced order system, [2] demonstrated that the resulting Landau-type Galerkin system is dynamically essential for the dynamic representation of transients. Initial validation, in [2], used the laminar cylinder wake as a simple benchmark. Subsequent studies revealed counterpart structures in the separated flow over airfoils [J:1,4-6],[BC1],[C:2,5,6,16],[P:1-4,7-10,14]. One research thrust aimed to solidify mean-field theory through a detailed analytic and quantitative investigation of its NSE-foundations [J:6,9][C6][P-4,5,7,14]. This investigation had 3 components: Direct analysis of the band-pass filtered NSE reveals both necessity of a mean-field model, including the nonlinear coupling of stability properties of the fluctuation with mean field variations, and the ideal structure of the shift mode. Second, we introduced a novel concept of quantitative transient energy flow rate

20120918069

analysis, and used that analysis to demonstrate the dominant role mean field variations play in determining fluctuation growth and decay rates. Thirdly, we have demonstrated that ideal, analytic and practical, computationally efficient definitions of the shift mode are essentially equivalent, thus validating the use of the empirical shift mode introduced in [2]. Related studies include modeling-enablers for high frequency boundary actuation, dynamic lift, and transient flow conditions. Viable subgrid models, compensating for truncated energy are discussed, are discussed in §2.




FIGURE 5. Invariant manifold for transition between two operating conditions: $\alpha = 30^\circ$ and $\alpha = 45^\circ$

Figure 1. The manifold formed by the dominant POD mode pair of the separated flow over an airfoil at a varying AOA. The vertical direction represents changes in both the mean field and the AOA

1.3 Mean field theory: high-frequency actuation models. The attenuating effect of open loop high frequency actuation on instabilities at unrelated frequencies is a fundamental flow control mechanism. Despite its significance, this mechanism has so eluded an analytical representation in reduced order Galerkin models, and has been resolved only by ad-hoc terms. In [J6],[P7,9] we proposed a *physically based* least order mean-field model capable to do just that. The model comprises 2 mode pairs for the dominant natural and actuated frequencies, and 2 mean field, shift modes represented mean field corrections driven by the respective Reynolds stress contributions of the fluctuating mode-pairs. The model explains the attenuating affect as mediated by actuated changes in the mean field: The Reynolds stress formed by the actuation leads to changes in the mean field. Stability properties of fluctuations are varied with changes in the mean field. In particular, the linear instability at the natural oscillation frequency disappears, in what amounts to an actuated subcritical Hopf bifurcation.

1.4 Mean field theory: dynamic lift models. With few extensions [1] standard lift models are confined to quasi-steady state representations or to conceptually equivalent harmonic balancing representations (e.g., for Helicopter blades). A by-product of [J6] is a first systematic framework for dynamic lift modeling. As an illustration, our objective is to resolve the response of the lift to fast MAV maneuvers, wind gusts, and actuation. A simple link of aerodynamic forces to the LOGM is obtained by substituting the Galerkin approximations of *both* the velocity and the pressure into the first principles expression

$$c_l = \frac{1}{0.5\rho U_\infty^2 c} \left(- \int_{\Gamma} p \mathbf{n} dS + \nu \int_{\Gamma} \nabla \mathbf{u} : \mathbf{n} dS \right) \cdot \mathbf{e}_y.$$

In this framework the lift is dynamically tied to changes in the dominant coherent flow structures. This work continues to date through our MURI collaborations and experimental refinement and validation of the proposed framework [C:1,3,11,13,15,17].

1.5 Mode deformation, mode interpolation and minimal mode sets for long transients.

Traditionally, LOGMs use modes obtained from a single operating condition, such as the POD mode of an attractor. The very purpose of flow control is to significantly alter and deform the coherent structures that dominate the flow e.g. due to flow reattachment of over an airfoil. As has been broadly recognized, these changes necessitate resolving controlled changes in dominant coherent structures. The use of richer mode-sets and realtime adaptation are common features of solutions proposed by the flow control community. Both these features increase realtime complexity. Additionally, the fact that, at any given time the number of dominant coherent structures remains small, and that richer mode-sets account for moderate deformations in these structures, may also entail a raise in the numerical sensitivity of dynamic observers, that now need to discern between relatively similar modes. Instead we suggest *state dependent mode deformations* over low dimensional manifolds: The time coefficients of the Galerkin expansion remain the LOGM states, but now they multiply modes that vary with the operating condition. For example, in a minimal order model of the separated flow over an airfoil, the first two modes are identified (up to state-space rotation) with the dominant unstable Eigenmodes, near the steady solution, and with the dominant POD mode-pair, near the natural attractor. Means to explicitly parameterize modes are based on simple interpolation algorithms, and the explicit derivation of the modes is required in only few operating conditions. We applied this approach to a pitching and actuated airfoil and to the cylinder wake in [J:5,10], [BC1], [C:2,8].

1.7 Harmonically specific modes. The paradigm of parameterized / interpolated mode-sets is feasible when important modal properties remain invariant under mode deformation. Key among these properties, in very low order models, is the link of modes to harmonics of the dominant temporal frequencies, even as these frequencies gradually change along transients between operating points. Standard POD modes often blend multiple spatial and temporal frequencies. To derive *harmonically-linked modes*, we use a dynamic estimation of the instantaneous frequency and an FIR filter bank to partition data trajectories into single frequency components [C:5,10],[P:3,4]. POD analysis is applied separately to each frequency component to obtain the desired modes. A preliminary high resolution POD compression of the original data is suggested, to dramatically reduce computations entailed by temporal filtering. Parameterization of mode deformation is a direct by-product. The procedure was first tested for an actuated NACA0012 airfoil [C5] and later applied to transient simulations of 2D and 3D pitching flat plates [C10]. Under independent support it was also applied, with remarkable success, to derive local mean field models for the dynamics near bifurcation branches in an analysis of the vortex breakdown phenomenon. The latter example is particularly




Figure 2: A coefficient of a standard POD mode is harmonically rich (top), compared with a harmonically-specific mode (bottom), both for a pitching flat plate.

challenging both because of the co-existence of multiple fixed points and local basins of attractions and to the strong effect of a short pipe on oscillatory dynamics.

1.8 Balanced POD system identification for periodic orbits. One key deficiency of POD modes is directly tied to their main advantage, i.e., their easy computation from empirical data. Neither the optimality criterion nor the actual computational procedure weigh the dynamic significance of selected modes. Indeed, strikingly, POD

analysis is invariant under temporal re-sequencing of the snapshots used. In contrast, *balanced truncation* is a method driven precisely by the underlying (linear) dynamics. Our MURI colleague C. W. Rowley adapted this method to fluid flow systems. A persistent shortcoming of this method is its focus on linear dynamics, and originally, a single fixed point. We joined the Princeton team in an extension to periodic orbits, as an enabler to effective modeling of periodically dominant transients and attractors [J8].

1.9 An accelerated POD computation. Even the computations necessary to extract POD modes can become taxing for high dimensional data consisting of long / rich transients. We propose an accelerated algorithm based on data partitioning in space and/or time: Following POD analysis of each partition, it is replaced by far smaller set whose first and second statistical moments approximate those of the original set. POD analysis of the reassembled global set is then guaranteed to approximate the exact POD of the original dataset. Computational savings are nearly linear (over a predicted range) in the number of partitions, and like the standard POD, a sought resolution is guaranteed. The method give rise to multiple space-time partitions and provides a formal justification for efficient iterative shortcuts. Results, validating the advantages of the procedure were presented in [C:5,9],[P:3,4] Links with concepts of sparse samplings are the subject of current investigation.

2. Turbulence Statistical Closure and Sub-grid models

Subgrid turbulence models are required to compensate for neglected length and time scales, and for the effects of truncated energy cascades. Prevalent practice is to calibrate eddy viscosities as added dissipation in the linear term of an LOGM. While successful in many cases, failures abound, suggesting a need for a new approach. The thermodynamic statistical closure problem is a daunting challenge in turbulence physics. In addition to the basic science value of a solution, related to the LOGM framework, a successful turbulence model is essential to overcome the aforementioned roadblock.

2.1 A new theory of finite-time thermodynamics (FTT) for Galerkin systems. Cutting through a persistent Gordian knot, this novel framework treats single or aggregate modal




Figure 3. POD and approximate POD eigenvalues for a long transient of a pitching airfoil are nearly identical.

energies as thermodynamic degrees of freedom. A balance of external interactions (i.e., production and dissipation) with rates of triadic, lossless energy transfer between modes, governs state dynamics. Simple closure formulae are derived from a postulated set of first principles, based on observed properties and dimensional analysis. Central axioms include the statistical independence of unrelated modes and the existence of an energy cascade from energy-rich to energy-poor modes. The dynamical system correctly predicts the energy cascade and redistribution in a number of benchmark tests, ranging from Burger's equation to the homogeneous shear turbulence. The FTT framework was reported in [J:2],[C:7,14],[P:6,11].




Figure 4. Energy flow rates determine modal energy balancing in the FTT model.

2.2 A unified framework of generalized Landau models. The structure of the FTT model reveals the intrinsic nonlinearity of energy exchanges between resolved Galerkin modes, mean-field modes and unresolved turbulence. A new class of hybrid models, based on this observation, aims to resolve the entire range of length and time scales: Mean field models resolve the largest scales and slowest time variations, an FTT based turbulence model resolves small scales statistics with pseudo-modes that captures the time variations of the aggregate energy at these scales, and standard LOGM terms resolve the usually targeted dynamics of dominant coherent structures. In particular, the implied turbulence model structure reveals both plausible reasons for eddy viscosities entailed difficulties, and alternative formalisms for simple sub-grid models. Outlines of the new framework are delineated in [J7],[P14] and work on further development and refinement continues to date.

3. Experimental Benchmarking & Verification

The design of robust feedback mechanisms utilizing few noisy sensors, is key to a realistic close control methodology. We used two benchmarks to validate our developments. One is the experimental drag reduction of the flow over a 3D bluff body (Fig. 5) at the Berlin Institute of Technology. The other is the semicircular, low aspect-ratio wing plan, developed as part of the MURI project. The primary support for the latter is under the main MURI grant and results are reported accordingly, although, for completeness, we list here publications related to both.

3.1 Feedback design utilizing a reduced order vortex models (ROVMs). This work relates to our joint work with for both rapid prototyping and implementation. Wake attenuation is achieved by symmetrizing the two shear layers, using a single pressure gauge: Pulsed blowing at the upper leap is synchronized at a preferred phase difference with the sensed pressure at the lower leap. A 40% pressure deficit reduction is achieved. This robust mechanism easily adapts to changing flow conditions where open-loop actuation at the two leaps becomes ineffective, while requiring only 60% of the actuation energy. Results




Figure 5. The wake of a 3D bluff body (top), is symmetrized (center) by pulsed actuation at the upper shear layer. Vorticity released at the upper leap is synchronized with preferred lag with sensed pressure at the lower leap (center) using an EKF.

been identified, using forward pulsed blowing at the leading edge, at an optimized frequency. A simulation study indicates that an effective feedback can be achieved by synchronizing pulsed actuation with a sensor signal, much alike the bluff body control described above. At IIT we investigating viable means to implement feedback, including a detailed modeling effort to enable accurate prediction of actuation variables, including pressure level and the temporal patterns of blowing. In particular, we developed a concept of control base on duty ratio of pulse blowing, as a practical easily implementable framework for feedback flow control [C3,4,8,11-14,17],[P12]. Compared with other applications of duty ratio control, the challenge in feedback design that we currently work on, is due to the nonlinearity of the response to individual pulses.

References unrelated to the grant

1. M. Goman and A. Khrabrov, State space representation of aerodynamic characteristics of aircraft at high angles of attack, *J. Aircraft* 31: 1109-1115, 1994
2. B.R. Noack, K. Afanasiev, M. Morzynski, G. Tadmor & F. Thiele, A hierarchy of low-dimensional models for the transient and post-transient cylinder wake, *J. Fluid*

are reported in [J3],[BC2],[P:9,13]. Currently pursued continuation of this project involve the far



Figure 6. A vortex model (left) of a tandem bluff body configuration is used to design a dynamic observer

more challenging tandem configuration, where a multiple vortex model is used a basis for a scented Kalman filter observer (Fig. 6).

3.2 Feedback control of the lift over a semi-circular wing plan. The regulation of an LEV and, consequently, the lift, is part of the related MURI project, jointly with Caltech, Princeton U., and IIT, where wind tunnel experiments are held. Collaborating with the Caltech-led team build on cross-feed between simulation studies at Caltech, wind tunnel experiments and reduced order modeling. An effective control mechanism has

Phase from disturbance input to L, $Re_{C,m} = 70,600$, SCW in gusting flow
 $Re_C = 68,000$, DTC variation case




Figure 7. Experimental phase lag in lift response of a semi-circular wingplan to incoming flow velocity variation, and to harmonically modulated duty actuation duty ratio, in open loop.

Mech 497:335-363, 2003.

Publications Related to This Grant

Book (cited as [B...])

0. B. R. Noack, G. Tadmor and M. Morzynski, **Reduced-Order Modeling for Flow Control**, Springer Verlag, in preparation (due 2009).

Journal Papers (cited as [J...])

1. M. Morzynski, B.R. Noack & G. Tadmor, *Global stability analysis and reduced order modeling for bluff-body flow control*, J. of Theo. and Applied Mechanics 45:621-642, 2007
2. B.R. Noack, M. Schlegel, B. Ahlborn, G. Mutschke, M. Morzynski, P. Comte & G. Tadmor, *A finite-time thermodynamics formalism for unsteady flows - from the onset of vortex shedding to developed homogeneous turbulence*, J. Non-equilibrium Thermodynamics 33:103-148, 2008
3. M. Pastoor, L. Henning, B.R. Noack, R. King & G. Tadmor, *Feedback shear layer control for bluff body drag reduction*, J. Fluid Mechanics, 608:161-196, 2008
4. W. Stankiewicz, M. Morzynski, B.R. Noack & G. Tadmor, *Reduced order Galerkin model of flow around a NACA-0012 airfoil*, Math. Model. Anal., 13:113-122, 2008
5. W. Stankiewicz, M. Morzynski, B.R. Noack & G. Tadmor, *Reduced order modeling of the flow around a NACA-0012 airfoil with a changing angle of attack*, Archives of Mechanics 60 (2008), 1 – 18
6. M. Luchtenburg, B. Gunther, B. R. Noack, R. King and G. Tadmor, *A generalized mean field model for high frequency control of flow separation*, J. Fluid Mechanics 623 (2009), 283-316.
7. B. .R. Noack, M. Schlegel M. Morzynski & G. Tadmor, *System reduction strategy for Galerkin models of fluid flow*. Intl. J. Numer. Meth. Fluids (2009), in press
8. Z. Ma, C. W. Rowley and G. Tadmor, *Snapshot-based Balanced Truncation for Linear Time-periodic Systems*, IEEE Trans. Automatic Control, under review
9. G. Tadmor, O. Lehmann, B. R. Noack and M. Morzynski, *Mean Field Representation of the Natural and Actuated Cylinder Wake*, Physics of Fluids, under review
10. O. Lehman, G. Tadmor, B. R. Noack and M. Morzynski, *Parameterized POD models for wake stabilization*, in preparation

Book Chapters (cited as [BC...])

1. M. Morzynski, W. Stankiewicz, B.R. Noack, R. King, F. Thiele & G. Tadmor, *Continuous mode interpolation for control-oriented models of fluid flow*, in **Active Flow Control**, R. King (Editor) Springer- Verlag, pp. 260-278.
2. L. Henning, M. Pastoor, B.R. Noack, R. King, & G. Tadmor, *Feedback control applied to the bluff-body wake*, in **Active Flow Control**, R. King (Editor) Springer- Verlag, pp. 369-390.

Conference Papers (cited as [C...])

1. C. W. Rowley, G. Tadmor and D. Williams, *Sensing and estimation for feedback control of unstable flows*, 3rd AIAA Flow Control Conference, 5-8, June 2006 San Francisco
2. M. Morzynski, W. Stankiewicz, B. R. Noack, F. Thiele and G. Tadmor, *Generalized Mean field Model with Continuous Mode Interpolation for Flow Control*, 3rd AIAA Flow Control Conference, 5-8 June 2006 San Francisco, CA
3. T. Colonius, C. W. Rowley, G. Tadmor, D. R Williams, and K. Taira, *Closed-loop control of leading-edge and tip vortices for small UAV*, International Conference on Active Flow Control, Berlin, Germany, 2006
4. S. Ahuja, C. Rowley, I. Kevrekidis, and M. Wei, T. Colonius, and G. Tadmor, *Low-Dimensional Models for Control of Leading-Edge Vortices: Equilibria and Linearized models*, 45th AIAA Aerospace Sciences Meeting and Exhibit, Reno, Nevada, Jan. 8-11, AIAA Paper 2007-709

5. G. Tadmor, M.D. Centuori, B.R. Noack, O. Lehmann, M. Luchtenbur & M. Morzynski, *A low order Galerkin models for the actuated flow around a 2-D airfoil*. 45th AIAA Aerospace Sciences Meeting and Exhibit, 8 - 11 Jan 2007, Reno, Nevada, AIAA Paper 2007-1313
 6. G. Tadmor, J. Gonzalez, O. Lehmann, B.R. Noack, M. Morzynski & W. Stankiewicz, *Shift modes and transient dynamics in low order design oriented Galerkin models*. 45th AIAA Aerospace Sciences Meeting and Exhibit, 8 - 11 Jan 2007, Reno, Nevada, AIAA Paper 2007-111, 2007
 7. B.R. Noack, M. Schlegel, B. Ahlborn, G. Mutschke, M. Morzynski, P. Comte & G. Tadmor, *A finite-time thermodynamics of unsteady flows from the onset of vortex shedding to developed homogeneous turbulence*. Proc. 9th Joint European Thermodynamics Conference (JETC IX), pp. 129—132.
 8. W-T. Joe, K. Taira, T. Colonius, D. G. MacMynowski and G. Tadmor, *Closed-Loop Control of Vortex Shedding on a Two-Dimensional Flat-Plate Airfoil at a Low Reynolds Number*, 46th AIAA Aerospace sciences Meeting & Exhibit, Reno, NV, January 7-10, 2008, AIAA Paper 2008-597
 9. G. Tadmor, D. Bissex, B. R. Noack, M. Morzynski, T. Colonius and K. Taira, *A Fast Approximate POD Algorithm for Long Time Data Trajectories*, 38th AIAA Fluid Dynamics / 4th Flow Control Conference and Exhibit, June 23-26, 2008
 10. G. Tadmor, D. Bissex, B. R. Noack, M. Morzynski, T. Colonius and K. Taira, *Temporal-Harmonic Specific POD Mode Extraction*, 38th AIAA Fluid Dynamics / 4th Flow Control Conference and Exhibit, June 23-26, 2008
 11. D. R. Williams, J. Collins, C. Jankhot, T. Colonius and G. Tadmor, *Control of Flow Structure on a Semi-Circular Planform Wing*, 46th AIAA Aerospace sciences Meeting & Exhibit, Reno, NV, January 7-10, 2008, AIAA Paper 2008-634
 12. D. R. Williams, J. Collins, G. Tadmor and T. Colonius, *Control of a Semi-Circular Planform Wing in a "Gusting" Unsteady Freestream Flow I: Experimental Issues*, 38th AIAA Fluid Dynamics / 4th Flow Control Conference and Exhibit, June 23-26, 2008
 13. D. R. Williams, J. Collins, G. Tadmor and T. Colonius, *Control of a Semi-Circular Planform Wing in a "Gusting" Unsteady Freestream Flow II: Modeling and Feedback Design*, 38th AIAA Fluid Dynamics / 4th Flow Control Conference and Exhibit, June 23-26, 2008
 14. B. R. Noack, M. Schlegel, B. Ahlborn, G. Tadmor, G. Mutschke, M. Morzynski, & P. Comte, *Finite-time thermodynamics for shear flows: a unifying formalism for instabilities, non-linear dynamics and statistical physics* (invited semi-plenary lecture). Mathematical Theory of Networks and Systems (MTNS), Blacksburg, VA, USA, 2008
 15. D. R. Williams, J. Collins, G. Tadmor, T. Colonius & C. W. Rowley, *Closed Loop Control of Post Stall Lift on a Low Aspect Ratio Wing*, 2nd Int. Conf. on Jets, Wakes and Separated Flows, Berlin, Germany, September 16-19, 2008
 16. K. Aleksic, R. King, B. R. Noack, O. Lehmann, M. Morzynski & G. Tadmor, *Nonlinear model predictive control based on a low dimensional model of fluid flow*, 2nd Int. Conf. on Jets, Wakes and Separated Flows, Berlin, Germany, September 16-19, 2008
 17. D. Williams, J. Collins, V. Quach, W. Kerstens, S. Buntain, T. Colonius, G. Tadmor and C. Rowley, *Low Reynolds Number Wing Response to an Oscillating Freestream with and without Feed Forward Control*, 47th AIAA Aerospace Sciences Meeting, 2009
- Conference Presentations** (with short abstracts, cited as [P...])
1. B. R. Noack and G. Tadmor, *Model based flow control in industrial applications: a scenario of future milestones and disenchantments*, European Forum on Flow Control 2, University of Poitiers, 4 July 2006
 2. B. R. Noack, M. Morzynski, W. Stankiewicz and G. Tadmor, *Generalized mean-field model of oscillatory flow using continuous mode interpolation*, Paper OL.00006, 59th Annual Meeting of the APS Division of Fluid Dynamics, November 19-21, 2006; Tampa Bay, Florida

3. G. Tadmor, B. R. Noack, M. Morzynski and D. Centuori, *Distributed dynamic phasors in empirical Galerkin models for separated flows over an airfoil*, Paper OL.00004, 59th Annual Meeting of the APS Division of Fluid Dynamics, November 19-21, 2006; Tampa Bay, Florida
4. G. Tadmor, B.R. Noack, D. Centuori, O. Lehmann & M. Morzynski, *Coherent structures, temporal harmonics and multi-resolution in reduced order empirical fluid flow models*. (Invited, abstract), SIAM Conference on Applications of Dynamical Systems, Snowbird, Utah, May 28 – June 1, 2007
5. G. Tadmor, B. R. Noack, O. Lehmann and M. Morzynski, *Empirical and Analytic Generalized Mean Field Models*, Amer. Phys. Soc. Div. Fluid Dynamics 60th Ann. Meeting, (Bulletin Am. Phys. Soc., Vol. 52, No. 17, EE.04), Nov. 18-20, 2007
6. B. R. Noack, M. Schlegel, B. Ahlborn, G. Mutschke, M. Morzynski and G. Tadmor, *A finite-time thermodynamics of unsteady shear flows*, Amer. Phys. Soc. Div. Fluid Dynamics 60th Ann. Meeting (Bulletin Am. Phys. Soc., Vol. 52, No. 17, JN.07), Nov. 18-20, 2007
7. M. Luchtenburg, B. Gunther, B. R. Noack, R. King. and G. Tadmor, *A generalized mean-field model for the natural and high-frequency actuated flow around a high-lift configuration*, Amer. Phys. Soc. Div. Fluid Dynamics 60th Ann. Meeting, Nov. 18-20, 2007
8. W. Stankiewicz, M. Morzynski, B. R. Noack & G. Tadmor, *Model for vortex shedding for NACA-0012 airfoil having high AoA*, 2nd Workshop on Bluff-Body Wakes, Instabilities and Control, H. Kudela organizer, Politechnika Wroclawska, Wroclaw, 27.-28. November 2007.
9. B. R. Noack, M. Schlegel, M. Pastoor, D. R. Luchtenburg, R. King, G. Mutschke, M. Morzynski, P. Comte, G. Tadmor & B. Ahlborn, *Low-dimensional Galerkin models, statistical physics and attractor control – towards a unifying theory for unsteady shear flows* (invited talk). Industrial Applications of Low Order Models Based On Proper Orthogonal Decomposition (POD) Workshop, organized by Iollo, A., Institut de Mathematiques de Bordeaux, 2008.
10. B. R. Noack, L. Cordier, M. Morzynski & G. Tadmor, *Reduced order models for feedback flow control: A review of key enablers and show stoppers* (invited talk). 79th Ann. Meeting of the Inst. For Appl. Math. & Mech. (GAMM) e.V., ZARM, University of Bremen, Germany, 2008.
11. M. Schlegel, B. R. Noack, B. Ahlborn, G. Mutschke, M. Morzynski, P. Comte & G. Tadmor, *Finite-time thermodynamics of shear flows - modelling attractors of simple to complex dynamics*, Dynamics Days Europe, Delft (Holand), August 25 - 29, 2008
12. D. R. Williams, J. Collins, G. Tadmor and T. Colonius, *Lift force time delays on 2D and 3D wings in unsteady flows*, 61st Annual Meeting of the Division of Fluid Dynamics of the APS, San Antonio, Texas, USA, November 23 - 25, 2008
13. M. Pastoor, L. Henning, B. R. Noack, R. King and G. Tadmor, *Vortex-model based flow control of turbulent wakes in experiment*, 61st Annual Meeting of the Division of Fluid Dynamics of the APS, San Antonio, Texas, USA, November 23 - 25, 2008
14. G. Tadmor, B. R. Noack, M. Schlegel and M. Morzynski, *A generalized Landau model for oscillatory to complex shear flows - enablers for reduced, low and least-order Galerkin models*, 61st Annual Meeting of the Division of Fluid Dynamics of the APS, San Antonio, Texas, USA, November 23 - 25, 2008

Short Course

1. B. R. Noack, G. Tadmor & M. Morzynski (organizers), *Reduced Order Model for Flow Control*, CISM - International Centre for Mechanical Sciences, Udine, Italy, September 15-19, 2008.

Supported Personnel: Gilead Tadmor, Professor, PI

Interactions/Transitions/Presentations:

- i. 1st Int. Active Flow Control Conf., Berlin, September 2006
- ii. 45th & 46th AIAA Aerospace Sciences Meetings and Exhibit, Jan. 2007 & 2008
- iii. 4th Flow Control / 38th Fluid Dynamics Conference, June 2008
- iv. 59th, 60th, Ann. Meetings of the APS DFD, November, 2006 & 2007
- v. Workshop on Bluff-Body Wakes, Instabilities and Control¹, Warsaw, 25. & 26. January 2007 (represented by B. R. Noack).
- vi. Workshop on Reduced Order Models for Flow & Noise Control, German Armed Forces Univ., Munich, 2/2007 (represented by B. R. Noack).
- vii. SIAM Conf. on Math & Comp. Issues in Geosciences, March 2007.
- viii. SIAM Conference on Applications of Dynamical Systems, May, 2007.
- ix. Seminars at Tel Aviv University (7/2007), U. Maryland (10/2007), George Wash. U. (10/2007), Harvard U. (2/2008)), KTH (Sweden, 5/2008), Weizmann Inst. (Israel, 6/2008).

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Service Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.

1. REPORT DATE (DD-MM-YYYY) 12-03-2009		2. REPORT TYPE Final		3. DATES COVERED (From - To) From 01-03-2006 to 30-11-2008	
4. TITLE AND SUBTITLE Design Models and Model Based Design in Fluid Flow with Application to Micro Air Vehicles				5a. CONTRACT NUMBER FA9550-06-1-0373	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
				5d. PROJECT NUMBER	
6. AUTHOR(S) Gilead Tadmor				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Northeastern University, Communication & Digital Signal Processing Center. Administrative Office: DSPA, 360 Huntington Ave., 405 Lake Hall, Boston, MA 02115-5000				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) AFOSR/NM Mathematical & Space Sciences 875 North Randolph St Suite 325, Room 3112 Arlington VA 22203-1954				10. SPONSOR/MONITOR'S ACRONYM(S) AFOSR/NM	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-OSR-VA-TIR-2012-0084	
12. DISTRIBUTION/AVAILABILITY STATEMENT A-Approved for Public Release					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT Our focus has been on structural enablers for very low order design models and for model-based flow control, including the flow physics underpinnings of low order flow models. Basic theory investigations concentrated primarily on Galerkin models: We derived from the NSE the essential role and form of mean field models and developed a novel none-equilibrium statistical closure and implied sub-grid turbulence models. Mean-field models now predict lift dynamics and high frequency actuation. With harmonically-pure mode-sets, mode interpolation maintains minimum model order across changing operating conditions, and is assisted by a new, efficient POD computation. Experimental studies were done in conjunction with a related MURI project, and complemented independently supported, long-term international team collaborations. We explored new feedback paradigms, including implementing duty ratio feedback modulation of pulsating jets, validated by MAV lift enhancement, and Lagrangian models in feedback for drag reduction behind a 3D bluff body. The research is presented in 7 journal papers + 2 under review / 1 in preparation, 2 Book chapters, 17 refereed conference papers, 14 conference abstracts, a forthcoming book and an international short course.					
15. SUBJECT TERMS feedback flow control, reduced order models, Galerkin models, mean field models, finite time thermodynamics, boundary actuation, proper orthogonal decomposition, transient dynamics					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			Gilead Tadmor
U	U	U	UU		19b. TELEPHONE NUMBER (Include area code) 617 373 5277

