

REPORT DOCUMENTATION PAGE					<i>Form Approved OMB No. 0704-0188</i>							
The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to the Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.												
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.												
1. REPORT DATE (DD-MM-YYYY) 06-12-2012		2. REPORT TYPE Final		3. DATES COVERED (From - To) 09-29-10 To 09-30-12								
4. TITLE AND SUBTITLE Transient Plasma Ignition for Small Internal Combustion Engines				5a. CONTRACT NUMBER								
				5b. GRANT NUMBER FA9550-10-1-0554								
				5c. PROGRAM ELEMENT NUMBER								
6. AUTHOR(S) Dr. Martin A. Gundersen Dr. Paul Ronney				5d. PROJECT NUMBER								
				5e. TASK NUMBER								
				5f. WORK UNIT NUMBER								
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Southern California Department of Contracts & Grants 3720 S. Flower Street				8. PERFORMING ORGANIZATION REPORT NUMBER								
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Office of Scientific Research 875 North Randolph Street Suite 325, Room 3112 Arlington, VA 22203-1768 Dr. Chiping Li				10. SPONSOR/MONITOR'S ACRONYM(S)								
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-OSR-VA-TR-2013-0099								
12. DISTRIBUTION/AVAILABILITY STATEMENT Distribution A: Approved for Public Release, distribution is unlimited.												
13. SUPPLEMENTARY NOTES												
14. ABSTRACT This is a Capstone undergraduate student project that focused on introducing transient plasma ignition (TPI) into a small combustion engine (2 hp Fuji Imvac BF-34EI), seeking to demonstrate improved operating efficiency. The project was directed towards involving undergraduate students in the aerospace-oriented research activity. For this project, because the Department of Defense has identified the need for increased mission capability of future Unmanned Aerial Systems, including increased payload, range, and loiter time, it was deemed advisable to direct the undergraduate students work towards achieving these goals by modifying the engine ignition and combustion using TPI. TPI, involving short, intense, low-energy electrical pulses (typically 10-50 nanoseconds), has been shown to effectively improve engine performance for a wide range of combustion-driven engines relative to conventional thermal ignition, and earlier considerations suggested its potential for smaller engine applications.												
15. SUBJECT TERMS Transient plasma ignition combustion small engine efficiency nanosecond pulsed power												
16. SECURITY CLASSIFICATION OF: <table border="1" style="width: 100%; border-collapse: collapse; margin-top: 5px;"> <tr> <td style="width: 33%; padding: 2px;">a. REPORT</td> <td style="width: 33%; padding: 2px;">b. ABSTRACT</td> <td style="width: 33%; padding: 2px;">c. THIS PAGE</td> </tr> <tr> <td style="text-align: center; padding: 2px;">U</td> <td style="text-align: center; padding: 2px;">U</td> <td style="text-align: center; padding: 2px;">U</td> </tr> </table>			a. REPORT	b. ABSTRACT	c. THIS PAGE	U	U	U	17. LIMITATION OF ABSTRACT U		18. NUMBER OF PAGES	
a. REPORT	b. ABSTRACT	c. THIS PAGE										
U	U	U										
					19a. NAME OF RESPONSIBLE PERSON Dr. Martin A. Gundersen							
					19b. TELEPHONE NUMBER (Include area code) (213)740-4396							

Reset



AFRL-OSR-VA-TR-2013-0099

Transient Plasma Ignition for Small Internal Combustion Engines

Gundersen, M. and Romney, P.

University of Southern California

FEBRUARY 2013

Final Report

DISTRIBUTION A: Approved for public release.

**AIR FORCE RESEARCH LABORATORY
AF OFFICE OF SCIENTIFIC RESEARCH (AFOSR)/RSA
ARLINGTON, VIRGINIA 22203
AIR FORCE MATERIEL COMMAND**

Transient Plasma Ignition for Small Internal Combustion Engines

FA9550-10-1-0554

Martin Gundersen / Paul Ronney

Abstract

This is a Capstone undergraduate student project that focused on introducing transient plasma ignition (TPI) into a small combustion engine (2 hp Fuji Imvac BF-34EI), seeking to demonstrate improved operating efficiency. The project was directed towards involving undergraduate students in the aerospace-oriented research activity. For this project, because the Department of Defense has identified the need for increased mission capability of future Unmanned Aerial Systems, including increased payload, range, and loiter time, it was deemed advisable to direct the undergraduate students work towards achieving these goals by modifying the engine ignition and combustion using TPI. TPI, involving short, intense, low-energy electrical pulses (typically 10-50 nanoseconds), has been shown to effectively improve engine performance for a wide range of combustion-driven engines relative to conventional thermal ignition, and earlier considerations suggested its potential for smaller engine applications. TPI is an attractive technology for the ignition of small internal combustion engines such as those used in unmanned applications because of engine data showing significant reductions in ignition delay, ignition of leaner fuel-air mixtures, lower specific fuel consumption, and faster burn rates. Successful results were achieved, and although preliminary, nevertheless demonstrated improved operating parameters, and potential for significantly impacting Air Force goals of improved engine performance on several levels, while employing basic research results of AFOSR-oriented research. The results included 25% increase in RPM with the same fuel consumption, indications of improved efficiency, and more consistent burn. In addition, miniaturized pulsed power conditioning, based on results from an AFOSR project in nanosecond pulsed power, was introduced that would be appropriate for development for airborne vehicles.

Introduction

The Fuji engine that is used for this work is installed on a lab bench, and is currently operational. A Windows PC with Labview and a National Instruments data acquisition card has been installed in the lab for use with this project. A dynamometer has been designed, built, and installed. It uses an automotive alternator with the field winding current varied to adjust the engine load. The alternator power output is sunk into electrical heating coils.

A force transducer mounted a known distance from the centerline of the engine is used to determine the engine torque. We have a 2000 g scale that is used as a load cell. A piezoelectric cylinder pressure transducer is used to measure cylinder pressure. The transducer has been installed in the engine.


The pulse generator to produce transient plasma ignition (TPI) for this experiment has been built. This device can operate up to 100 Hz, which is enough for a 4-stroke engine with a maximum RPM of 11,000. A TPI electrode compatible with the Fuji engine was designed and manufactured, and is ready for use. A

shaft encoder will be used to determine crank angle; from this and the known geometry of the engine, the cylinder volume is easily calculated. From the pressure vs. time and volume vs. time, pressure-volume plots will be generated and work per cycle computed.



Background

The DoD has identified the need for increased mission capability of future Unmanned Aerial Systems (UAS), including increased payload, range, and loiter time. Transient plasma ignition (TPI), involving short, intense, low-energy electrical pulses (typically 10-50 ns), has been shown to effectively improve engine performance for a wide range of combustion-driven engines relative to conventional thermal ignition [1-3]. TPI is an attractive technology for the ignition of small internal combustion engines such as those used in UAS because of engine data showing significant reductions in ignition delay, ignition of leaner fuel-air mixtures, lower specific fuel consumption, and faster burn rates. Here we describe research into development and optimization of TPI implementation in a single-cylinder 2 hp Fuji Imvac BF-34EI internal combustion engine.

Transient Plasma Ignition




A single non-thermal transient plasma discharge in air favorably alters pre-combustion chemistry and physics. Shown here are streamers generated by a 54 ns, 61 kV pulse across a 15 mm gap [4]. Production of active particles in streamer channels through electron impact dissociation, excitation, and ionization of atoms and molecules significantly impact chain branching reactions, reducing ignition delay times and allowing for more complete combustion.




Photos of flame development in ethylene-air, 7 ms after discharge. Left: Spark ignition using a standard 105 mJ, 10 μ s, 15 kV spark ignition system and a spark plug; Right: Transient plasma ignition using a 365 mJ, 54 ns, 56 kV pulse with a 15 mm gap [5].


Experimental Setup



- Custom dynamometer with automobile alternator and heaters under construction
- Necessary engine parameters are logged using a LabVIEW virtual instrument
- A custom made plenum is used to prevent pulsing in the intake manifold and to stabilize the airflow measurements
- TPI system delivers a 50 ns, 25 kV, 50 mJ pulse to a non-resistive spark plug with coaxial electrode
- TPI delivered with the same timing as spark ignition (SI) based on magnetic pickup on the crankshaft



Results



Experiments performed in a 1-cyl gasoline engine, delivering one 50 ns pulse-per-cycle. Based on previous results with plasma enhanced combustion we expect, greater than 10% improvement in combustion efficiency.

- Demonstrated TPI on small internal combustion engine in the USC lab
- Compared to SI, TPI results in 25% increase in RPM with the same fuel consumption
- Indicates improved efficiency
- TPI resulted in more consistent burn than SI
- Experiments will be performed once the dynamometer is operational

Future Work

After demonstrating faster burning rates and improved fuel efficiency with TPI, attention will be turned to engine design. The faster burn rates produced by TPI may be used in conjunction with intake port and combustion chambers intentionally shaped to provide reduced turbulence levels and thus reduce

thermal losses while still obtaining rapid burn rates. Moreover, the reduced cooling system load means that smaller cooling systems can be used, thus reducing aerodynamic drag. This double benefit (increased efficiency and reduced drag) is potentially enabling technology for long-distance small engines having large combustion chamber surface area to volume ratios. Piston and cylinder head design, intake manifold flow straighteners, and ignition timing and air-fuel ratios will be explored in future work.

Summary

Using transient plasma in a single-cylinder gasoline engine, a 25% increase in RPM was demonstrated under the same operating conditions when compared to traditional spark ignition. A custom dynamometer is being constructed so that heat release and combustion efficiency can be measured.

References

1. Cathey, C., T. Tang, T. Shiraishi, T. Urushihara, A. Kuthi, and M. A. Gundersen, "Nanosecond Plasma Ignition for Improved Performance of an Internal Combustion Engine," IEEE Trans on Plasma Sci., Dec. 2007: 35, 6, Part 1, 1664-1668.
2. J.B. Liu, F. Wang, G. Li, A. Kuthi, E. J. Gutmark, P.D. Ronney, and M.A. Gundersen, "Transient Plasma Ignition," IEEE Transactions on Plasma Science, Vol. 33, No. 2, April 2005.
3. Shiraishi, T., Urushihara, T., and Gundersen, M., "A trial of ignition innovation of gasoline engine by nanosecond pulsed low temperature plasma ignition", J. Phys. D: Appl. Phys. 42 (2009) 135208.
4. D. Singleton, S J. Pendleton, and M. A. Gundersen, "The role of non-thermal transient plasma for enhanced flame ignition in C₂H₄-air," J. Phys. D: Appl. Phys. 44 (2011) 022001.
5. D. Singleton and M. A. Gundersen, "Transient Plasma Fuel-Air Ignition," IEEE Transactions on Plasma Science, vol. 39, no. 11, pp. 2214-2215, Nov. 2011.