

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 11/4/08		2. REPORT TYPE Final		3. DATES COVERED (From - To) 6/15/07 - 6/14/08	
4. TITLE AND SUBTITLE Instrumentation for Nano-porous, Nano-particulate Geopolymeric Materials Research				5a. CONTRACT NUMBER FA9550-07-1-0490	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Kriven, Waltraud M.				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The Board of Trustees of the University of Illinois 506 South Wright Street Urbana, IL 61801				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) AF Office of Scientific Research 875 N. Randolph St., Rm 3112 Arlington, VA 22203				10. SPONSOR/MONITOR'S ACRONYM(S) AFOSR	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) AFRL-OSR-VA-TR-2012-0469	
12. DISTRIBUTION / AVAILABILITY STATEMENT A					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT -- Geopolymers are a new class of ceramic materials which are best understood as rigid inorganic, aluminosilicate, hydrated gels, charge-balanced by cations such as Na ⁺ , K ⁺ , or Cs ⁺ . The ease and versatility of forming, together with the tailorability of their properties (e.g. nano-porosity) qualify geopolymers as promising candidates for a variety of applications such as filters, catalyst supports, light weight, thermal shock resistant refractory composites, thermal/environmental barrier coatings, as well as smart composites. The PIs group, supported by AFOSR (Grant # FA 9550-06-1-0221) is working on tailoring the nano- and meso-porosity, and the microstructure of geopolymers and their composites. This grant was used to procure equipment to synthesize and characterize the nano- and meso-porous geopolymers, and study their evolution upon curing and conversion to ceramic phase. The instruments purchased included (a) Micromeritics ASAP 2020 equipped with chemisorption option and mass spectrometer, (b) TestEquity 1007H Temperature/Humidity Chamber, is deemed essential, (c) Union Process Model 01HD Attritor mill, and (d) Thinky Mixer ARE 250.					
15. SUBJECT TERMS Geopolymers; nano-porosity; microstructure; nano-particles; surface area					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT SAR	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON Waltraud M. Kriven
a. REPORT UU	b. ABSTRACT UU	c. THIS PAGE UU			19b. TELEPHONE NUMBER (include area code) (217) 333-5258

FINAL REPORT

Project Title: Instrumentation for Nano-porous, Nano-particulate Geopolymeric Materials Research

Principal Investigator: Prof. Waltraud M. Kriven

Institution: Department of Materials Science and Engineering
University of Illinois at Urbana-Champaign
1304 West Green Street
Urbana, IL 61801

Contract Number: FA9550-07-1-0490

The primary objective of instrumentation purchased through this AFOSR-DURIP award (Grant # FA9550-07-1-0490) was to enable quantitative characterization of nano-porosity and mesoporosity in the microstructure of geopolymers, and their evolution upon curing and conversion to ceramic. The ability to understand and tailor the nano and meso-porosity and microstructure of geopolymers and their composites is part of an ongoing research project in the PIs research group, which has been supported by the AFOSR (Grant# FA 9550-06-1-0221). For this purpose, instrumentation for both characterization and processing of geopolymers was requested and included (a) Micromeritics ASAP 2020 Accelerated Surface Area and Porosimetry analyzer system equipped with a chemisorption option and mass spectrometer, (b) TestEquity 1007H Temperature/Humidity Chamber, is deemed essential, (c) Union Process Model 01HD Attritor mill, and (d) Thinky Mixer ARE 250.

All the above instruments were purchased through this grant, and are being used (or installed) to study nano-porous and nano-particulate geopolymeric materials.

The Micromeritics ASAP 2020 instrument was purchased and is being installed. It will enable quantitative evaluation of both the physical characteristics and physiochemical changes as a function of composition and processing conditions. The TestEquity 1007H Temperature/Humidity Chamber, is being used to study the effect of humidity and temperature, the two most crucial factors that influence curing of geopolymers, on the geopolymer microstructure under a range of controlled conditions. Further results from these studies will be reported in the technical report for the respective AFOSR sponsored project.

The use of controlled humidity to properly cure, dry, and tailor geopolymer porosity has never been previously explored. As geopolymers are being increasingly considered for a number of high tech applications such as filters, precursors to glass ceramics, catalysts, and coatings, such a study stands to benefit to a number of areas. Previous work in the PIs research group had shown that although most geopolymers set in less than four hours at room temperature, they continue to react for months. Microstructurally, this involves coarsening of the small precipitates commonly observed via SEM. The use of controlled humidity above 50-60°C is expected to accelerate curing and other reaction processes in a more reasonable timeframe suitable for conclusive studies. This will further the understanding of the relationship between intrinsic microstructure, porosity, curing conditions and resultant properties.

The attritor mill and the Thinky ARE 250 mixer were purchased to improve the synthesis and processing of geopolymers and geopolymer composites. The attritor mill enables synthesis

of nano-sized high surface area ceramic powders in geopolymers and geopolymeric composites. On the other hand, the Thinky ARE-250 mixer was purchased to assist with homogeneous dispersion of secondary phases in geopolymer composites. The THINKY ARE-250 Mixer is a non-contact "planetary" mixer which mixes, disperses, and degasses materials in seconds to minutes, in a sealed or lid-less container such as a jar, beaker, syringe tube, or cartridge. It is also effective in controlling shear, so as not to damage the materials. This product was evaluated specifically for use in geopolymer processing and our findings suggest that Thinky ARE-250 mixer provides exceptional advantages in mixing secondary phases, such as fibers and other nano-sized particulates. The mixing action (essential for reaction with metakaolin) and the ability to de-air (for removal of macropores) are also superior to an overhead mixer system which was used in the research project earlier.

The equipment purchased through this award is essential for the success of ongoing research in geopolymers by the PI (AFOSR Grant # FA 9550-06-1-0221). It is anticipated to catalyze the advancement of knowledge in this class of material system which holds strong promise in applications such as light weight, thermal shock resistant ceramic composites, coatings as well as smart composites.

Broader Impact

Geopolymers are a new class of ceramic materials which are best understood as rigid inorganic, aluminosilicate, hydrated gels, charge-balanced by cations such as Na^{+1} , K^{+1} , or Cs^{+1} . The microstructure of geopolymers is nano-porous (~ 3.4 nm radius), nano-particulate (≤ 5 nm in size), and the porosity constitutes over 40% of the body by volume. The ease and versatility of forming, together with the tailorability of their properties (e.g. nano-porosity) qualify geopolymers as promising candidates for a variety of applications such as filters, catalyst supports, light weight, thermal shock resistant refractory composites, thermal/environmental barrier coatings, hydrogen storage materials, as well as smart composite materials (e.g. sensors). In order to realize the full potential of this material, it is imperative to develop a fundamental understanding of the geopolymer microstructure, leading to its evolution into a polycrystalline ceramic upon heating. The lack of quantitative material science knowledge is an impediment to the advancement of this class of material. The current stage of geopolymer research is fraught at the elementary stage of porosity engineering and control. Success at this stage has the potential to usher in a variety of high tech applications for this very promising material.

Instrumentation purchased through this grant was aimed to overcome the equipment limitation being faced in the awarded research contract (AFOSR Grant # FA 9550-06-1-0221), and thus facilitate superior quality research deliverables also. This instrumentation complements the equipment available to the PI for research at UIUC. It will certainly transform the way research is conducted on geopolymer materials.