

Droplet Sampling of an Oil-Based and Two Water-Based Antievaporant Ultra-Low Volume Insecticide Formulations Using Teflon®- and Magnesium Oxide-Coated Slides

Author(s): Alexandra Chaskopoulou , Mark D. Latham , Roberto M. Pereira , and Philip G. Koehler

Source: Journal of the American Mosquito Control Association, 29(2):173-176. 2013.

Published By: The American Mosquito Control Association

DOI: <http://dx.doi.org/10.2987/12-6305r.1>

URL: <http://www.bioone.org/doi/full/10.2987/12-6305r.1>

BioOne (www.bioone.org) is a nonprofit, online aggregation of core research in the biological, ecological, and environmental sciences. BioOne provides a sustainable online platform for over 170 journals and books published by nonprofit societies, associations, museums, institutions, and presses.

Your use of this PDF, the BioOne Web site, and all posted and associated content indicates your acceptance of BioOne's Terms of Use, available at www.bioone.org/page/terms_of_use.

Usage of BioOne content is strictly limited to personal, educational, and non-commercial use. Commercial inquiries or rights and permissions requests should be directed to the individual publisher as copyright holder.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 2013		2. REPORT TYPE		3. DATES COVERED 00-00-2013 to 00-00-2013	
4. TITLE AND SUBTITLE Droplet Sampling of an Oil-Based and Two Water-Based Antievaporant Ultra-Low Volume Insecticide Formulations Using Teflon- and Magnesium Oxide-Coated Slides				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Florida, Department of Entomology, Building 970 Natural Area Drive, Gainesville, FL, 32611-0620				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT We estimated the diameters below which 50% and 90% of the volume of droplets exist (Dv50 and Dv90, respectively) of 1 oil-based (Permanone 30-30) and 2 water-based (AquaReslin, Aqua-KOthrine) antievaporant aerosols (with the Film Forming Aqueous Spray Technology [FFASTTM]) using TeflonH- and magnesium oxide (MgO)-coated slides and determined whether the aging of the droplets on the slides (up to 60 min) exhibited any significant effect on Dv50 and Dv90 calculations. There were no significant differences in either Dv50 or Dv90 estimates on MgO-coated slides at 0 min and 60 min for all 3 products tested. On Teflon-coated slides, the only product that showed significant difference between 0 min and 60 min in both Dv50 and Dv90 estimates was Aqua-K-Othrine, perhaps due to a difference in formulation components. Specifically, both values corresponding to Dv50 and Dv90 at 60 min decreased by approximately 50% when compared to the values at 0 min. For the other 2 products, AquaReslin and Permanone, aging of droplets on Teflon up to 60 min did not have any significant effect on Dv50 and Dv90 values. To further investigate the behavior of Aqua-K-Othrine droplets on Teflon-coated slides we observed the droplets immediately after spraying and at 10-min intervals under different conditions of temperature and humidity. The majority of the shrinkage occurred within the 1st 10 min after impaction on the slides under all conditions tested. So in most field situations where slides are read several hours or days after collection, this shrinkage would not be observed. The MgO-coated slides should be the preferred field method for sampling droplets of Aqua-K-Othrine with the FFAST antievaporant technology.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

SCIENTIFIC NOTE

DROPLET SAMPLING OF AN OIL-BASED AND TWO WATER-BASED ANTIEVAPORANT ULTRA-LOW VOLUME INSECTICIDE FORMULATIONS USING TEFLON®- AND MAGNESIUM OXIDE-COATED SLIDES

ALEXANDRA CHASKOPOULOU,^{1,3} MARK D. LATHAM,² ROBERTO M. PEREIRA¹
AND PHILIP G. KOEHLER¹

ABSTRACT. We estimated the diameters below which 50% and 90% of the volume of droplets exist (Dv_{50} and Dv_{90} , respectively) of 1 oil-based (Permanone 30-30) and 2 water-based (AquaReslin, Aqua-K-Othrine) antievaporant aerosols (with the Film Forming Aqueous Spray Technology [FFAST™]) using Teflon®- and magnesium oxide (MgO)-coated slides and determined whether the aging of the droplets on the slides (up to 60 min) exhibited any significant effect on Dv_{50} and Dv_{90} calculations. There were no significant differences in either Dv_{50} or Dv_{90} estimates on MgO-coated slides at 0 min and 60 min for all 3 products tested. On Teflon-coated slides, the only product that showed significant difference between 0 min and 60 min in both Dv_{50} and Dv_{90} estimates was Aqua-K-Othrine, perhaps due to a difference in formulation components. Specifically, both values corresponding to Dv_{50} and Dv_{90} at 60 min decreased by approximately 50% when compared to the values at 0 min. For the other 2 products, AquaReslin and Permanone, aging of droplets on Teflon up to 60 min did not have any significant effect on Dv_{50} and Dv_{90} values. To further investigate the behavior of Aqua-K-Othrine droplets on Teflon-coated slides we observed the droplets immediately after spraying and at 10-min intervals under different conditions of temperature and humidity. The majority of the shrinkage occurred within the 1st 10 min after impaction on the slides under all conditions tested. So in most field situations where slides are read several hours or days after collection, this shrinkage would not be observed. The MgO-coated slides should be the preferred field method for sampling droplets of Aqua-K-Othrine with the FFAST antievaporant technology.

KEY WORDS Ultra-low volume, droplet sampling, Teflon-coated slides, MgO-coated slides

One of the factors affecting the efficacy of an aerosolized, ultra-low volume (ULV) insecticidal spray (space spray) for targeting flying insects such as mosquitoes is the size of the droplets contained within the aerosol cloud (Mount 1970). One of the most commonly used methods to sample droplets in the field is by impaction on rotating glass microscope slides; this method is simple, affordable, and easy to use.

The coating of the slides used for droplet impaction varies based on the formulation characteristics of the insecticide. For oil-based insecticides, Teflon® coating was found to be a suitable material for droplet impaction (Anderson and Schulte 1971) because oil-based products are relatively nonvolatile and retain their original diameter for extended periods of time (Anderson and Schulte 1971). On the other hand, water-based insecticides are more prone to volatilization/

evaporation and for that reason a magnesium oxide (MgO) slide coating has been used for water-based insecticidal droplets (May 1945, 1950; Rathburn 1970; Matthews 1975) because the impressions that the droplets create upon impaction on the slide are measured, not the actual droplets. These impressions are permanent and allow for a more precise size determination, even though droplets may shrink due to evaporation (Rathburn 1970).

In recent years, a new group of insecticidal formulations were developed as water-based preformed emulsions utilizing an antievaporant technology known as Film Forming Aqueous Spray Technology (FFAST™) to slow droplet evaporation (Groome et al. 1989). In the past, both Teflon and MgO coatings have been used to sample droplets of FFAST products (Brown et al. 1998, 2003; Mickle and Brown 1999, 2000, 2001; Lothrop et al. 2007). However, experiments for direct comparison of these 2 coatings in determining the volume median diameters (Dv_{50} s) of FFAST® droplets are not known and the appropriateness of Teflon as a FFAST droplet impaction surface has not been investigated in relation to droplet size measurements and shrinkage. Our main objective was to estimate the Dv_{50} and the Dv_{90} of 1 oil-based and 2 water-based,

¹ Department of Entomology, University of Florida, Building 970 Natural Area Drive, Gainesville, FL 32611-0620.

² Manatee County Mosquito Control District, 2317 2nd Avenue W, Palmetto, FL 34221.

³ US Department of Agriculture–Agricultural Research Service European Biological Control Laboratory, Tsimiski 43, 54623, Thessaloniki, Greece.

antievaporant aerosols using Teflon- and MgO-coated slides and to determine whether aging of the droplets on the slides (up to 60 min) has any significant effect on Dv_{50} and Dv_{90} calculations.

Three commercially available ULV formulations registered for mosquito adulticiding were used in all experiments: 1 oil-based formulation, Permanone 30-30 (30% permethrin, Bayer Environmental Science, Research Triangle Park, NC), and 2 water-based FFAST formulations, Aqua-Reslin (20% permethrin, Bayer Environmental Science, Research Triangle Park, NC) and Aqua-K-Othrine (2% deltamethrin, Bayer Environmental Science, Lyon, France). The latter product is registered in the European Union but not currently available for use in the USA. All compounds were used neat (undiluted). An earlier version of the Colt 4 portable ULV-generator (London Fogger Inc., Long Lake, MN) was used to atomize all compounds. The generator operated with a flow rate of approximately 60 ml/min.

Battery-powered slide rotators (Compact Aerosol Droplet Sampler Model 312, John W. Hock Company, Gainesville, FL) were used for droplet sampling. Rotators were operated at a speed of 550 rpm and were placed side by side to create a sampling line on a stand approximately 1 m from the ground. In order to create a relatively uniform spray cloud, the handheld generator was facing the rotators and moved at the same height and alongside the sampling line at a constant distance (approximately 2 m). Microscope glass slides ($25 \times 75 \times 1$ mm) were either coated with Teflon plastic film (BioQuip Products Inc., Rancho Dominguez, CA) or purchased plain (Fisher Scientific Company, Pittsburg, PA) and coated with MgO as described by Chaskopoulou et al. (2011). Three rotators were used containing 1 Teflon- and 1 MgO-coated slide each.

After spraying was completed the rotators, with the slides still attached, were collected and transported to the laboratory. Once in the laboratory the slides were removed from the rotators and placed on the microscope stage individually so the droplets could be measured. The droplets on both coating types were measured immediately after spraying each rotator (within 3 min), and at 60 min postspraying for both coating types. During the 60-min period, the slides were kept on their holding racks in the laboratory where the temperature and humidity remained relatively constant (approximately 20°C and 55% relative humidity [RH]). The droplet sizes were determined under a VanGuard compound microscope (model 14867FLi, Vee Gee Scientific, Kirkland, WA) at $200\times$ magnification with an ocular micrometer calibrated so that each division measured $4.5\text{ }\mu\text{m}$. The diameters of at least 200 droplets were measured per slide for a total of 3 Teflon- and 3 MgO-coated slides per

product tested. For those droplets that did not have a spherical shape, 2 measurements were made corresponding to the narrowest and widest dimension of the droplet. The average of these 2 measurements was used as the droplet diameter.

When estimating the Dv_{50} and Dv_{90} values, the correction for volume diameter was done using the diameter (D) value rather than the volume diameter (D^3) associated with each droplet, as suggested by Yeomans (1949). A spread factor of 0.61 was used for the 3 compounds on Teflon; spread factors of 0.86, 0.8, and 0.75 were used for droplet sizes >20 , 15–20, and 10–15 μm on MgO coating, respectively (May 1945).

All statistical analyses were performed with the SAS software package (version 8.01; SAS Institute, Cary, NC). A paired *t*-test was performed to determine the effect of droplet aging on the calculation of droplet Dv_{50} and Dv_{90} values for droplets sprayed on MgO- and Teflon-coated slides ($P = 0.05$). The Dv_{50} and Dv_{90} values of the droplets immediately upon impaction on the slides were calculated and compared with the Dv_{50} and the Dv_{90} values of the droplets 60 min postimpact.

The mean Dv_{50} and Dv_{90} values of insecticide droplets at 0 and 60 min after impaction on Teflon- and MgO-coated slides were calculated for all 3 products tested. There were no significant differences in either Dv_{50} or Dv_{90} estimates on MgO slides at 0 min and 60 min for all 3 products tested (Table 1). On Teflon-coated slides, the only product that showed significant difference between 0 min and 60 min in both Dv_{50} and Dv_{90} estimates was Aqua-K-Othrine. Specifically, both values corresponding to Dv_{50} and Dv_{90} at 60 min decreased by approximately 50% when compared to the initial readings. For the other 2 products, AquaReslin and Permanone, time did not have any significant effect on Dv_{50} and Dv_{90} values.

To further investigate the behavior of Aqua-K-Othrine droplets on Teflon-coated slides we observed the droplets immediately after spraying and at 10-min intervals for 60 min. Spray and slide preparation was repeated as described above, except that this time the effects of 3 different environmental scenarios on droplet behavior were investigated. For the 1st scenario the slides were kept spinning at temperatures $25\text{--}27^{\circ}\text{C}$ and humidity $>80\%$ RH, resembling spinning slides in the field during a night spray. The 2nd scenario was identical to the 1st one except that the slides were not spinning. For the 3rd scenario the slides were stationary in their slide racks at conditions of temperatures $18\text{--}20^{\circ}\text{C}$ and humidity $<55\%$ RH, resembling a laboratory where slides would normally be stored for droplet measurement after a night-spray trial. In order to observe droplet behavior, the slides were moved immediately to the laboratory after spraying and

Table 1. Mean Dv_{50} and Dv_{90} values for Permanone, Aqua-K-Othrine and AquaReslin droplets on MgO- and Teflon®-coated slides immediately (0 min) and 60 min after impaction to slides.¹

Product	Mean $Dv_{50} \pm SE$				Mean $Dv_{90} \pm SE$			
	Teflon		MgO		Teflon		MgO	
	0 min	60 min	0 min	60 min	0 min	60 min	0 min	60 min
Permanone	5.7 $\pm$ 0.2	5.6 $\pm$ 0.1	6.7 $\pm$ 0.1	7.0 $\pm$ 0.1	11.1 $\pm$ 0.3	11.0 $\pm$ 0.2	13.9 $\pm$ 0.8	14.0 $\pm$ 0.2
Aqua-K-Othrine	8.5 $\pm$ 0.1	4.3 $\pm$ 0.8*	6.2 $\pm$ 0.3	5.9 $\pm$ 0.2	25.8 $\pm$ 5.0	9.4 $\pm$ 1.4*	18.7 $\pm$ 1.0	17.3 $\pm$ 0.4
AquaReslin	7.2 $\pm$ 0.5	6.2 $\pm$ 0.4	7.4 $\pm$ 0.2	7.8 $\pm$ 0.3	18.9 $\pm$ 4.2	11.9 $\pm$ 0.8	14.9 $\pm$ 0.2	15.0 $\pm$ 0.2

¹ Dv_{50} , volume median diameter; Dv_{90} , volume 90% diameter; MgO, magnesium oxide.
* Mean Dv_{50} and Dv_{90} values at 60 min are significantly smaller than corresponding values at 0 min ($P = 0.05$, t -test).

observed by microscopy (200 $\times$ magnification). Droplet behavior was recorded through time by photographing a set field of approximately 10–20 droplets every 10 min for 60 min. The same field of droplets on each slide was captured every time. This procedure was repeated over 8 different slides and a total of approximately 100 droplets were recorded for each one of the 3 scenarios. The slides were on the microscope stage only long enough to capture the images and were immediately returned to the conditions described above. A digital microscope camera (DCM500, Hangzhou Huaxin IC Technology Inc., Zhejiang, China) with the corresponding computer software (ScopePhoto 3.0 Image Processing, Hangzhou Huaxin IC Technology Inc., Zhejiang, China) was used to capture, manage, and save the image files.

The images of the droplet fields and of a calibrated stage micrometer (1 division = 4.5 μ m) were printed at the same scale on standard copy paper or transparent acetate sheets (216 $\times$ 279 mm), respectively. The stage micrometer on the acetate sheet was used to measure the droplets on the printed images of the droplet fields.

The diameter of Aqua-K-Othrine droplets decreased significantly during all 3 experimental conditions (dry environment/nonspinning slides, moist environment/nonspinning slides, moist environment/spinning slides) (Fig. 1). The majority of the shrinkage occurred during the 1st 10 min after impaction on the slides under all 3 environmental conditions tested.

In previous studies with FFAST antievaporant water-based products some inconsistencies between Dv_{50} estimated using Teflon- versus MgO-coated slides have been demonstrated. The Teflon slides produced a measured Dv_{50} that was approximately $\frac{1}{2}$ the Dv_{50} measured by using MgO slides (Mickle and Brown 2000, Brown et al. 2003). Mickle and Brown (2001) showed that characterization of their nozzle using a laser wind tunnel in the laboratory yielded a Dv_{50} nearly 5-fold greater than what was measured in the field using Teflon slides. Findings by these authors suggest that possible evaporation of the aqueous formulation may have resulted into smaller droplets being measured on the Teflon slides.

This study provided direct evidence that FFAST droplets of Aqua-K-Othrine, despite containing antievaporant ingredients, will shrink significantly on Teflon-coated slides within 10 min after impaction and, therefore, MgO slides should be preferred over Teflon. On the other hand, despite




Fig. 1. Droplet diameter (in μ m) distribution for Aqua-K-Othrine (AKO) on Teflon®-coated slides at 0, 10, 20, and 60 min. (A) Dry, nonspinning scenario. (B) Moist, nonspinning scenario. (C) Moist, spinning scenario.

losing their spherical shape, AquaReslin droplets on Teflon-coated slides did not shrink significantly within 60 min postspraying. Although both Aqua-K-Othrine and AquaReslin formulations contain the same FFAST antievaporant technology, these formulations contain a combination of ingredients (actives and/or solvents/synergists) with variable physical properties (i.e., vapor pressure) resulting in different evaporation rates.

Magnesium oxide slides also have several disadvantages. Some of the most important disadvantages are the requirement of a long preparation time (Anderson and Schulte 1971) and their high susceptibility to dust and other airborne contaminants, which may leave imprints on the slide surface. Although we currently recommend the use of MgO-coated slides, a new technology is needed for a more accurate droplet sampling of FFAST antievaporant insecticides under field conditions. In the meantime, correction factors adjusted for each FFAST formulation and droplet size will need to be determined to allow for the usage of Teflon-coated slides.

We thank Jane Bonds (Barber), Roxanne Connelly, and Carol Thomas for useful editing advice. We thank Gail Stout and Martin West for their assistance during the experimentation. We thank the Deployed War-Fighter Protection Research Program for their support. Last, but not least, we thank Bayer Environmental Sciences for providing us with samples of their products.

REFERENCES CITED

- Anderson CH, Schulte W. 1971. Teflon as a surface for deposition of aerosol droplets. *Mosq News* 4:499–504.
- Brown JR, Mickle RE, Yates M, Zhai J. 2003. Optimizing an aerial spray for mosquito control. *J Am Mosq Control Assoc* 19:243–250.
- Brown JR, Steinke WE, Zhai J, Sykes D. 1998. Aqua-Reslin droplet analysis. *J Am Mosq Control Assoc* 14:467–469.
- Chaskopoulou A, Latham MD, Pereira RM, Connelly R, Bonds JAS, Koehler P. 2011. Efficacy of aerial ultra-low volume applications of two novel water-based formulations of unsynergized pyrethroids against riceland mosquitoes in Greece. *J Am Mosq Control Assoc* 27:414–422.
- Groome JM, Martin R, Slatter R. 1989. Advances in the control of public health insects. *Int Pest Control* 31:137–140.
- Lothrop HD, Lothrop BB, Palmer M, Wheeler S, Gutierrez A, Gonsi DE, Reisen WK. 2007. Evaluation of pyrethrin and permethrin ground ultra-low volume applications for adult *Culex* control in rural and urban environments for the Coachella Valley of California. *J Am Mosq Control Assoc* 23:190–207.
- Matthews GA. 1975. Chemicals and equipment. Determination of droplet size. *Pest Art News Summ* 21:213–225.
- May KR. 1945. The cascade impactor: an instrument for sampling coarse aerosols. *J Sci Instrum* 22:187–195.
- May KR. 1950. The measurement of airborne droplets by the magnesium oxide method. *J Sci Instrum* 27:128–130.
- Mickle RE, Brown JR. 1999. *Aerial adulticide spray trials characterization and optimization results, Crowley Rice Research Station, LA*. Report to Louisiana Mosquito Control Association.
- Mickle RE, Brown JR. 2000. *Optimization strategies for the aerial application of Aqua-Reslin, Georgetown, SC trials 1999*. Report to Aventis Environmental Health.
- Mickle RE, Brown JR. 2001. *Optimization trials for the aerial application of Aqua-Reslin using rotary atomizers, Easterwood, LA, 2000*. Final report to Aventis Environmental Health.
- Mount GA. 1970. Optimum droplet size for adult mosquito control with space sprays or aerosols of insecticides. *Mosq News* 30:70–75.
- Rathburn CB. 1970. Methods of assessing droplet size of insecticidal sprays and fogs. *Mosq News* 30:501–513.
- Yeomans AH. 1949. *Directions for determining particle size of aerosols and fine sprays, ET-267*. Washington, DC: US Department of Agriculture Bureau of Entomology and Plant Quarantine.