

Detonator-Effects Investigation of AXEUMM Experiments

**by Matthew M. Biss, Richard Benjamin, Ronnie Thompson,
and William Sickels**

ARL-TN-537

June 2013

NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Citation of manufacturer's or trade names does not constitute an official endorsement or approval of the use thereof.

Destroy this report when it is no longer needed. Do not return it to the originator.

Army Research Laboratory

Aberdeen Proving Ground, MD 21005-5066

ARL-TN-537

June 2013

Detonator-Effects Investigation of AXEUMM Experiments

Matthew M. Biss and Richard Benjamin
Weapons and Materials Research Directorate, ARL

Ronnie Thompson
Dynamic Science Inc.

William Sickels
Bowhead Science and Technology LLC

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) June 2013		2. REPORT TYPE Final		3. DATES COVERED (From - To) December 2012-June 2013	
4. TITLE AND SUBTITLE Detonator-Effects Investigation of AXEUMM Experiments				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Matthew M. Biss, Richard Benjamin, Ronnie Thompson*, and William Sickels**				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army Research Laboratory ATTN: RDRL-WML-C Aberdeen Proving Ground, MD 21005-5066				8. PERFORMING ORGANIZATION REPORT NUMBER ARL-TN-537	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.					
13. SUPPLEMENTARY NOTES *Dynamic Science Inc. **Bowhead Science and Technology LLC					
14. ABSTRACT AXEUMM experiments were conducted to investigate the presence/absence of jetting at the charge surface of detonating energetic materials due to the detonator employed. Experiments are conducted using gram-range spherical charges in the blast chamber at the U.S. Army Research Laboratory's Detonation Science Facility. Early-time high-speed images of the detonation wave's breakout and air shock wave's early-time expansion are captured using a high-speed intensified camera. Explosively driven air shock waves are qualitatively analyzed throughout their early-time expansion. Captured images are shown to exhibit a nearly spherical air shock wave throughout early-time expansion without the presence of jetting due to the detonator.					
15. SUBJECT TERMS laboratory-scale, detonator, jetting effects, high-speed					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UU	18. NUMBER OF PAGES 14	19a. NAME OF RESPONSIBLE PERSON Matthew M. Biss
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code) 410-278-3708

Contents

List of Figures	iv
List of Tables	v
Acknowledgments	vi
1. Introduction	1
2. Experimental Methods	1
3. Results and Discussion	3
4. Conclusions	4
5. References	5
Distribution List	6

List of Figures

Figure 1. Monolithic spherical charge with centrally positioned detonator..... 2

Figure 2. Experimental imaging setup..... 2

Figure 3. Composite image generated from high-speed images for shot 12354-1..... 3

Figure 4. Composite image generated from high-speed images for shot 12354-2..... 4

Figure 5. Composite image generated from high-speed images for shot 12354-3..... 4

List of Tables

Table 1. Tabulated charge properties and camera imaging variables.....	3
--	---

Acknowledgments

We would like to acknowledge the U.S. Army Research Laboratory's Lethality Division Mission Program for funding of this research and Mr. Roy Maulbetsch, Mr. Terry Piatt, and Mrs. Lori Pridgeon of the Ingredient, Formulation, and Processing Team for pressing of the energetic samples.

1. Introduction

Detonation and air shock wave measurements are traditionally gathered using full-scale experiments in which charge masses may vary anywhere from 1 to 10^5 kg (1). Consequently, the advent of the explosive scaling laws (2–4) in the early 1900s permitted the scaling of these widely ranging experimental results for comparative purposes. Nearly a century later, experimental laboratory-scale-based research has been shown to extend the scaling laws' validity down through the milligram range for select materials (5–8). In this research, optical flow visualization techniques (e.g., schlieren, shadowgraph, etc.) are combined with high-speed cameras to track explosively driven air shock wave propagation rates for characterization purposes. Captured high-speed images have been shown to provide detonation and air shock wave properties at the interface between the energetic material and surrounding medium (velocity, pressure, particle velocity, and density) in addition to radially varying air shock wave properties (e.g., peak pressure, peak temperature, peak density, and positive pressure duration) (5–8). The extension down to the laboratory scale has been demonstrated to be a highly accurate, cost-effective alternative to traditional detonation and air shock wave characterization experiments.

However, some questions exist regarding the validity of these measurements (8), due to the possibility of adverse jetting effects introduced by the detonator employed. In response, the present research was conducted to address these concerns and verify the presence/absence of jetting effects in AXEUMM (ARL eXplosive Evaluation Utilizing Minimal Material) experiments as a result of detonator-initiated spherical charges. Experiments were conducted using laboratory-scale spherical charges composed from the energetic compound cyclotrimethylene trinitramine (RDX). A high-speed intensified camera was used to image the detonation wave breakout at the energetic charge surface in addition to the initial propagation of the air shock wave generated. Captured images were qualitatively analyzed for the presence/absence of jetting at the charge surface.

2. Experimental Methods

Experiments were conducted with spherical 13-mm-diameter energetic-material charges. Monolithic RDX charges were pressed to a specified density of 1.77 g/cm^3 using a specially designed pressing die and hydraulic press. Spherical charges possess a centrally positioned

right-circular-cylinder void to accommodate an RP-3 (Teledyne-RISI, Inc.) exploding bridgewire (EBW) detonator (29-mg pentaerythritol tetranitrate [PETN]) for initiation, figure 1.




Figure 1. Monolithic spherical charge with centrally positioned detonator.

Experiments were performed in the blast chamber located at the U.S. Army Research Laboratory's Detonation Science Facility. Figure 2 shows the experimental setup used for the present experiments. A xenon flash bulb is triggered to frontlight the charge and obtain a static image of the charge orientation. A Teledyne-RISI FS-43 EBW firing system, charged to 4.2 kV, subsequently initiates the RP-3 detonator, while a PCO-Tech model HSFC-Pro high-speed intensified camera records the explosively driven air shock wave propagation history. The resulting explosive fireball and subsequent ionization of the surrounding air due to the shock wave provide self-illumination for the duration of the record. The generated air shock wave is imaged for a total of three charges. Pressed charge properties and camera settings are tabulated in table 1.




Figure 2. Experimental imaging setup.

Table 1. Tabulated charge properties and camera imaging variables.

Shot #	Density (g/cm ³)	Mass (g)	Frame rate (frames/s)	Exposure (ns)
12354-1	1.77	1.823	1,000,000	100
12354-2	1.77	1.821	1,000,000	40
12354-3	1.77	1.826	1,000,000	40

3. Results and Discussion

High-speed images were qualitatively analyzed to determine the presence of jetting at the charge surface (specifically the surface opposite the detonator) and to verify the early-time expansion shock wave sphericity. A composite image was constructed for each experiment from the captured high-speed image sets, figures 3–5. As shown, all three composite images lack any semblance of jetting at the specified surface. Additionally, air shock waves were determined to tend toward sphericity by the second frame following detonation wave breakout for all image sets. The initial image following shock wave breakout was anticipated to be aspherical, as the detonator is unable to act as a perfect point source initiator and therefore results in a slight variation of the detonation wave’s breakout along the charge surface as shown. However, this does not affect previous measurements, as they were acquired from the surface normal to the detonator axis, therefore ensuring a normally propagating shock wave (8).




Figure 3. Composite image generated from high-speed images for shot 12354-1.




Figure 4. Composite image generated from high-speed images for shot 12354-2.




Figure 5. Composite image generated from high-speed images for shot 12354-3.

4. Conclusions

AXEUMM experiments were conducted and investigated for the presence/absence of jetting due to the detonator in addition to shock wave sphericity. High-speed images were gathered for multiple experiments to capture the detonation wave breakout at the energetic charge surface and initial air shock wave propagation history. The air shock wave was determined to be spherical in nature for all image sequences and lacked any semblance of jetting at the surface of interest. It was therefore concluded that prior measurements taken along this surface (8) were valid and acceptable for characterization purposes.

5. References

1. Dewey, J. The Air Velocity in Blast Waves From TNT Explosions. *Proceedings of the Royal Society of London. Series A, Mathematical and Physical Sciences* **1964**, 279 (1378), 366–385.
2. Cranz, C. *Lehrbuch der Ballistik*; Springer-Verlag: Berlin, 1926.
3. Hopkinson, B. *British Ordnance Minutes*; Report No. 13563; British Ordnance Office, 1915.
4. Sachs, R. G. *Dependence of Blast on Ambient Pressure and Temperature*; BRL Report No. 466; Ballistic Research Laboratory: Aberdeen Proving Ground, MD, 1944.
5. Kleine, H.; Dewey, J.; Ohashi, K.; Mizukaki, T.; Takayama, K. Studies of the TNT Equivalence of Silver Azide Charges. *Shock Waves* **2003**, 13 (2), 123–138.
6. Hargather, M.; Settles, G. Optical Measurement and Scaling of Blasts From Gram-Range Explosive Charges. *Shock Waves* **2007**, 17 (4), 215–223.
7. Biss, M.; Settles, G. On the Use of Composite Charges to Determine Insensitive Explosive Material Properties at the Laboratory Scale. *Propellants, Explosives, Pyrotechnics* **2010**, 35 (5), 452–460.
8. Biss, M. M. *Removing Full-Scale Testing Barriers: Energetic Material Detonation Characterization at the Laboratory Scale*; ARL-TR-5943; U.S. Army Research Laboratory: Aberdeen Proving Ground, MD, March 2012.

<u>NO. OF</u> <u>COPIES</u>	<u>ORGANIZATION</u>	
1 (PDF)	DEFENSE TECHNICAL INFORMATION CTR DTIC OCA	W DRYSDALE RDRL WML H J NEWILL RDRL WMP G R EHLERS RDRL WM P BAKER B FORCH P PLOSTINS
1 (PDF)	DIRECTOR US ARMY RESEARCH LAB RDRL CIO LL	
1 (PDF)	GOVT PRINTG OFC A MALHOTRA	
1 (PDF)	NAVAL RSRCH LAB TECH LIB	
1 (PDF)	US ARMY ARDEC A DISTASIO	
1 (PDF)	US ARMY ARDEC S NICOLICH	
1 (PDF)	US ARMY ARDEC P ANDERSON	
1 (PDF)	NAVAL SURF WARFARE CNTR H HAYDEN	
 <u>ABERDEEN PROVING GROUND</u>		
22 (PDF)	US ARMY RESEARCH LAB DIR USARL RDRL WML M ZOLTOSKI RDRL WML A W OBERLE RDRL WML B N TRIVEDI J MORRIS J GOTTFRIED RDRL WML C S AUBERT K MCNESBY B ROOS G SUTHERLAND K SPANGLER T PIEHLER V BOYLE M BISS RDRL WML D R BEYER RDRL WML E P WEINACHT RDRL WML F D LYON RDRL WML G	