

Technical Report ARWSB-TR-12024

Stress Concentration at Inclined Crossbore Holes in Pressurized, Autofrettaged Tubes

**Anthony P. Parker
Edward Troiano**

October 2012



ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER
Weapons & Software Engineering Center
Benét Laboratories



Approved for public release; distribution is unlimited.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 16 OCT 2012		2. REPORT TYPE FINAL		3. DATES COVERED 00-00-2010 to 00-00-2011	
4. TITLE AND SUBTITLE Stress Concentration at Inclined Crossbore Holes in Pressurized				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Anthony Parker; Edward Troiano				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. ARMY ARDEC, Benet Laboratories, RDAR-WSB, Watervliet, NY, 12198				8. PERFORMING ORGANIZATION REPORT NUMBER ARWSB-TR-12024	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. ARMY ARDEC, Benet Laboratories, RDAR-WSB, Watervliet, NY, 12198				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT A sequence of analytic, elastic superpositions is employed to obtain a single equation for determining the maximum stress at the bore of a pressurized thick cylinder intersected by an inclined, circular crossbore hole whose axis intersects that of the cylinder. The crossbore hole may contain a pressure that differs from that in the bore, a situation that pertains in some gun tubes during firing. The formulation permits the modeling of any plane (constant strain) end condition, including zero strain, open-ends and closed-ends. The crossbore hole may itself have an additional stress concentrator on its boundary; such concentrators may result from erosion, corrosion or manufacturing defects. Finally, preexisting residual stresses, prior to introduction of the crossbore hole, may also be incorporated. The single equation presented applies to the crossbore-bore intersection.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 15	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

The views, opinions, and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy, or decision, unless so designated by other documentation.

The citation in this report of the names of commercial firms or commercially available products or services does not constitute official endorsement by or approval of the U.S. Government.

Destroy this report when no longer needed by any method that will prevent disclosure of its contents or reconstruction of the document. Do not return to the originator.

REPORT DOCUMENTATION PAGE				<i>Form Approved</i> OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188) Washington, DC 20503.					
PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (<i>DD-MM-YYYY</i>) 16-10-2012		2. REPORT TYPE FINAL		3. DATES COVERED (<i>From - To</i>)	
4. TITLE AND SUBTITLE Stress Concentration at Inclined Crossbore Holes in Pressurized, Autofrettaged Tubes				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Anthony P. Parker, Edward Troiano				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, RDAR-WSB Watervliet, NY 12189-4000				8. PERFORMING ORGANIZATION REPORT NUMBER ARWSB-TR-12024	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, RDAR-WSB Watervliet, NY 12189-4000				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER	
12. DISTRIBUTION AVAILABILITY STATEMENT Approved for public release; distribution is unlimited or other distribution statement.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT A sequence of analytic, elastic superpositions is employed to obtain a single equation for determining the maximum stress at the bore of a pressurized thick cylinder intersected by an inclined, circular crossbore hole whose axis intersects that of the cylinder. The crossbore hole may contain a pressure that differs from that in the bore, a situation that pertains in some gun tubes during firing. The formulation permits the modeling of any plane (constant strain) end condition, including zero strain, open-ends and closed-ends. The crossbore hole may itself have an additional stress concentrator on its boundary; such concentrators may result from erosion, corrosion or manufacturing defects. Finally, preexisting residual stresses, prior to introduction of the crossbore hole, may also be incorporatedThe single equation presented applies to the crossbore-bore intersection,					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT U	18. NUMBER OF PAGES 15	19a. NAME OF RESPONSIBLE PERSON Edward Trioano
a. REPORT U/U	b. ABSTRACT U	c. THIS PAGE U			19b. TELEPHONE NUMBER (<i>Include area code</i>) 518-266-5112

INSTRUCTIONS FOR COMPLETING SF 298

1. REPORT DATE. Full publication date, including day, month, if available. Must cite at least the year and be Year 2000 compliant, e.g., 30-06-1998; xx-08-1998; xx-xx-1998.

2. REPORT TYPE. State the type of report, such as final, technical, interim, memorandum, master's thesis, progress, quarterly, research, special, group study, etc.

3. DATES COVERED. Indicate the time during which the work was performed and the report was written, e.g., Jun 1997 - Jun 1998; 1-10 Jun 1996; May - Nov 1998; Nov 1998.

4. TITLE. Enter title and subtitle with volume number and part number, if applicable. On classified documents, enter the title classification in parentheses.

5a. CONTRACT NUMBER. Enter all contract numbers as they appear in the report, e.g. F33615-86-C-5169.

5b. GRANT NUMBER. Enter all grant numbers as they appear in the report, e.g. 1F665702D1257.

5c. PROGRAM ELEMENT NUMBER. Enter all program element numbers as they appear in the report, e.g. AFOSR-82-1234.

5d. PROJECT NUMBER. Enter all project numbers as they appear in the report, e.g. 1F665702D1257; ILIR.

5e. TASK NUMBER. Enter all task numbers as they appear in the report, e.g. 05; RF0330201; T4112.

5f. WORK UNIT NUMBER. Enter all work unit numbers as they appear in the report, e.g. 001; AFAPL30480105.

6. AUTHOR(S). Enter name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. The form of entry is the last name, first name, middle initial, and additional qualifiers separated by commas, e.g. Smith, Richard, Jr.

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES). Self-explanatory.

8. PERFORMING ORGANIZATION REPORT NUMBER. Enter all unique alphanumeric report numbers assigned by the performing organization, e.g. BRL-1234; AFWL-TR-85-4017-Vol-21-PT-2.

9. SPONSORING/MONITORS AGENCY NAME(S) AND ADDRESS(ES). Enter the name and address of the organization(s) financially responsible for and monitoring the work.

10. SPONSOR/MONITOR'S ACRONYM(S). Enter, if available, e.g. BRL, ARDEC, NADC.

11. SPONSOR/MONITOR'S REPORT NUMBER(S). Enter report number as assigned by the sponsoring/ monitoring agency, if available, e.g. BRL-TR-829; -215.

12. DISTRIBUTION/AVAILABILITY STATEMENT. Use agency-mandated availability statements to indicate the public availability or distribution limitations of the report. If additional limitations/restrictions or special markings are indicated, follow agency authorization procedures, e.g. RD/FRD, PROPIN, ITAR, etc. Include copyright information.

13. SUPPLEMENTARY NOTES. Enter information not included elsewhere such as: prepared in cooperation with; translation of; report supersedes; old edition number, etc.

14. ABSTRACT. A brief (approximately 200 words) factual summary of the most significant information.

15. SUBJECT TERMS. Key words or phrases identifying major concepts in the report.

16. SECURITY CLASSIFICATION. Enter security classification in accordance with security classification regulations, e.g. U, C, S, etc. If this form contains classified information, stamp classification level on the top and bottom of this page.

17. LIMITATION OF ABSTRACT. This block must be completed to assign a distribution limitation to the abstract. Enter UU (Unclassified Unlimited) or SAR (Same as Report). An entry in this block is necessary if the abstract is to be limited.

ABSTRACT

A sequence of analytic, elastic superpositions is employed to obtain a single equation for determining the maximum stress at the bore of a pressurized thick cylinder intersected by an inclined, circular crossbore hole whose axis intersects that of the cylinder. The crossbore hole may contain a pressure that differs from that in the bore, a situation that pertains in some gun tubes during firing.

The formulation permits the modeling of any plane (constant strain) end condition, including zero strain, open-ends and closed-ends. The crossbore hole may itself have an additional stress concentrator on its boundary; such concentrators may result from erosion, corrosion or manufacturing defects. Finally, preexisting residual stresses, prior to introduction of the crossbore hole, may also be incorporated

The single equation presented applies to the crossbore-bore intersection, but the formulation may be directly extended to model any radial location within the wall.

Table of Contents

ABSTRACT.....	i
INTRODUCTION	1
ANALYSIS: SIMPLE ELLIPSE.....	2
ANALYSIS: ELLIPSE PLUS EROSION OR CORROSION	4
SUMMARY AND CONCLUSIONS	6
REFERENCES	7

Figure 1: Elliptical Hole Created at Intersection of Inclined Circular Crossbore Hole and Bore of Tube. Hole Radius, R , Angle of Inclination of Hole to Tube Axis	8
Figure 2: Superposition Sequences for Unpressurized and Pressurized Elliptical Hole at Bore of Thick Cylinder; Eccentricity of Ellipse c	9
Figure 3: Superposition Sequences for Unpressurized and Pressurized Elliptical Hole plus Additional Stress Concentrator (k) at end of Major Axis; Eccentricity of Ellipse c	9

INTRODUCTION

Crossbore holes are frequently introduced into thick cylinders, including gun tubes. When the center-line of a small circular crossbore hole coincides with the center-line of the tube, the intersection at the bore of the tube creates an ellipse, Figure 1. The eccentricity of the ellipse depends upon the angle of inclination of the hole centre-line to the axis of the tube, γ . The ratio major axis/minor axis is then given by $1/(\sin \gamma)$. This creates a significant stress concentration at the end of the major axis, a location that is prone to thermal cracking and subsequent cyclic fatigue crack growth.

Cheng [1] reviewed available work and incorporated results due to Little & Bagci [2] which provide the stress concentration factor (SCF) at the bore intersection for the case in which full bore pressure also acts upon the crossbore hole. However, there is evidence that, because of a shock wave at the intersection, only a proportion of bore pressure infiltrates the crossbore in a gun tube [3], [4].

In this paper the Little and Bagci formulation is extended to include any ratio of pressure in crossbore to pressure in bore (α), any plane (constant axial strain) end-condition and any combination of residual hoop and axial stress arising from prior autofrettage.

Evacuators are also prone to gas erosion and/or corrosion pitting. These serve to further increase the SCF. The formulation is further extended to incorporate such effects.

The procedure involves superposition of a series of analytic solutions. In all cases it is necessary to model the effect of pressure infiltrating the stress concentrators. It is also necessary to properly account for contributions arising from that part of any biaxial stress field parallel to the major axis of the stress concentrator.

ANALYSIS: SIMPLE ELLIPSE

The hoop stresses at the bore of a plain tube, subjected to internal pressure p with internal radius a and external radius b , are given by Lamé's equations [5]:

$$\sigma_{\theta} = p \frac{(b^2 + a^2)}{(b^2 - a^2)} \quad (1)$$

as noted above, the eccentricity of the elliptical hole at the bore (designated c) is given by:

$$c = 1/(\sin \gamma) \quad (2)$$

where γ is the inclination of the hole centre-line to the axis of the tube.

The maximum stress around an elliptical hole subjected to remote uniaxial stress σ_n normal to the major axis occurs at the end of the major axis and is given by [5]:

$$\sigma_{\text{ellipse}(n)} = (1 + 2c)\sigma_n \quad (3)$$

This situation is illustrated, together with other relevant solutions, in Figure 2.

So for the case where only Lamé hoop stress (defined in eqn. (1)) is acting, the stress at the end of the major axis is:

$$\sigma_{\theta} = p(1 + 2c) \frac{(b^2 + a^2)}{(b^2 - a^2)} \quad (4)$$

The stress at the end of the major axis of an elliptical hole subjected to remote uniaxial stress σ_t parallel to the major axis is given by [5]:

$$\sigma_{\text{ellipse}(t)} = -\sigma_t \quad (5)$$

Depending upon end conditions, the internal pressure may create an axial stress in the tube, this is given by:

$$\sigma_z = \frac{\beta p a^2}{(b^2 - a^2)} \quad (6)$$

where $\beta = 0$ (constant axial strain, open ends), $\beta = 1$ (constant axial strain, closed ends) and $\beta = 2\nu$ (zero axial strain).

From eqn. (5), for the case where only Lamé axial stress (defined in eqn. (6)) is acting, the hoop stress at the end of the major axis created by σ_z is :

$$\sigma_\theta = \frac{-\beta p a^2}{(b^2 - a^2)} \quad (7)$$

The total hoop stress relating to the Lamé hoop and axial stresses is obtained by summing eqns (4) and (7). This is normalized using bore hoop stress in the original tube, eqn (1), to obtain the associated stress concentration factor, K_{Lame} :

$$K_{Lame} = p \frac{[(1 + 2c)(b^2 + a^2) - \beta a^2]}{(b^2 - a^2)} \quad (8)$$

Now assume that pressure αp acts within the evacuator, where $0 \leq \alpha \leq 1$

In this case the hoop stress at the end of the major axis is given by Godfrey [6]:

$$\sigma_\theta = \alpha p (2c - 1) \quad (9)$$

Note: the necessary superpositions are again shown in Figure2.

Hence the total stress arising from Lamé hoop stress plus Lamé axial stress plus pressure infiltrating the evacuator may be obtained by summing eqns (4), (7) and (9). If this total stress is normalized using Lamé bore hoop stress from eqn (1) the stress concentration factor, $K_{Lame+pressure}$, is given by:

$$K_{Lame+pressure} = \frac{b^2[(2c + 1) + \alpha(2c - 1)] + a^2[(2c + 1 - \beta) + \alpha(2c - 1)]}{(b^2 - a^2)} \quad (10)$$

Equation (10) reduces to Cheng's eqn (10) [1], for $\alpha = 1$ (full pressure in evacuator), $\beta = 1$ (closed ends) and to Cheng's eqn (11) for $\alpha = 1$ (full pressure in evacuator), $\beta = 0$ (open ends). Obviously, it further reduces to:

$$K_{Lame+pressure} = (2c + 1) \quad (11)$$

for $\alpha = 0$ (no pressure in evacuator), $\beta = 0$

So, for the following open-end cases with $b/a = 2, c = 2$

Open end, full bore pressure in evacuator $(\alpha = 1, \beta = 0)$, $K_{Lame+pressure} = 6.8$

Open end, zero pressure in evacuator $(\alpha = 0, \beta = 0)$, $K_{Lame+pressure} = 5.0$

Open end, 20% of bore pressure in evacuator $(\alpha = 0.2, \beta = 0)$, $K_{Lame+pressure} = 5.36$

If there were pre-existing hoop and axial residual stresses $\sigma_{\theta R}$ and σ_{zR} within the tube, these may be treated in the same fashion as the Lamé stresses. This gives

$$\sigma_{\theta Rconc} = (1 + 2c)\sigma_{\theta R} - \sigma_{zR} \quad (12)$$

ANALYSIS: ELLIPSE PLUS EROSION OR CORROSION

Now consider a stress concentration, k , associated with a very small additional stress concentrator at the end of the major axis of the ellipse. Following the previous analytical sequence it is possible to produce a more general form of eqns (10) and (12).

The hoop stress arising from the initial ellipse given in eqn (4) is now concentrated by a further factor of k giving:

$$\sigma_{\theta} = pk(1 + 2c) \frac{(b^2 + a^2)}{(b^2 - a^2)} \quad (13)$$

However, somewhat paradoxically, the stress at the end of the major axis of any hole symmetric about its major axis subjected to remote uniaxial stress σ_t parallel to the major axis is still given by [6], [7]:

$$\sigma_{ellipse(t)} = -\sigma_t \quad (14)$$

This situation is illustrated, together with other relevant solutions, in Figure 3.

Hence, eqn (5) is unchanged by k and

$$\sigma_{\theta} = \frac{-\beta p a^2}{(b^2 - a^2)} \quad (15)$$

giving:

$$K_{Lame} = p \frac{[k(1+2c)(b^2 + a^2) - \beta a^2]}{(b^2 - a^2)} \quad (16)$$

Again, assume that pressure αp acts within the evacuator, where $0 \leq \alpha \leq 1$

In this case the hoop stress at the end of the major axis of ellipse plus erosion is given by:

$$\sigma_{\theta} = \alpha p [k(1+2c) - 2] \quad (17)$$

where the necessary superpositions are again shown in Figure 3..

Note that eqn (17) reduces to eqn (9) for the case where there is no additional stress concentration, i.e. $k = 1$.

Hence the total stress arising from Lamé hoop stress plus Lamé axial stress plus pressure infiltrating the evacuator and erosion may be obtained by summing eqns (13), (15) and (17). If this total stress is normalized using bore hoop stress, eqn (1), the stress concentration factor, $K_{Lame+pressure+erosion}$, is given by:

$$K_{Lame+pressure+erosion} = \frac{b^2[k(1+2c)(1+\alpha) - 2\alpha] + a^2[k(1+2c)(1-\alpha) - \beta + 2\alpha]}{(b^2 + a^2)} \quad (18)$$

If there were pre-existing hoop and axial residual stresses $\sigma_{\theta R}$ and σ_{zR} within the tube, these may be treated in the same fashion as the Lamé stresses. This gives

$$\sigma_{\theta Rconc} = k(1+2c)\sigma_{\theta R} - \sigma_{\theta R} \quad (19)$$

Note that the value of the additional stress concentration, k is a function of the angle of inclination, γ . For example, when looking along the axis of the crossbore, the crossbore hole will appear circular. If an additional small erosion appears semi-circular, hole and erosion will appear elliptical and semi-elliptical respectively at the bore intersection.

SUMMARY AND CONCLUSIONS

The work reported here employs a sequence of analytic, elastic superpositions to obtain a single equation for determining the maximum stress at the bore of a pressurized thick cylinder intersected by an inclined, circular crossbore hole whose axis intersects that of the cylinder. The crossbore hole may contain a pressure that differs from that in the bore, a situation that pertains in some gun tubes during firing.

The formulation permits the modeling of any plane (constant strain) end condition, including zero strain, open-ends and closed-ends. The crossbore hole may itself have an additional stress concentrator on its boundary; such concentrators may result from erosion, corrosion or manufacturing defects. Finally, preexisting residual stresses, prior to introduction of the crossbore hole, may also be incorporated

Since all solutions assume elastic behavior there is no limit upon the Von Mises stress arising from particular combinations of bore pressure, crossbore pressure, end condition and preexisting residual stress. In such cases it will be necessary to adopt some form of 'capping' of the Von Mises stress, taking into account the specific loading sequence.

The single equation presented applies to the crossbore/bore intersection, but the formulation may be directly extended to model any radial location within the wall.

REFERENCES

- [1] Cheng, Y. F., 1978, "Stress Concentration Around Inclined Holes in Pressurized Thick-Walled Cylinders", US Army Armament Research and Development Command, Technical Report ARLCB-TR-78019, November 1978.
- [2] Little, R. E. and Bagci, C., 1965, "Stress Analyses of Pressurized Cylinders", Engineering Research Bulletin, Publication No. 145, Oklahoma State University.
- [3] Nagamatsu, H.T., Choi, K.T., Duffey, R.E., Carafano, G.C., 1987, "An Experimental and Numerical Study of the Flow Through a Vent Hole in a Perforated Muzzle Break", ARDEC Technical Report ARCCB-TR-87016, June 1987.
- [4] Troiano, E., Parker, A. P. and Izzo, J., 2012, "Influence and Modeling of Residual Stresses on the Life of Thick Walled Pressure Vessels with Through Holes", Paper PVP2012-78179, Proceedings of ASME Pressure Vessels and Piping Division Conference, July 15–19 2012, Toronto, Canada.
- [5] Timoshenko, S. P., 1970, 'Theory of Elasticity', 3rd Edition, McGraw-Hill, New York.
- [6] Godfrey, D. E. R., 1959, 'Theoretical Elasticity and Plasticity for Engineers', Thames and Husdon, London.
- [7] Sharma, D. S., 2011, "Stress Concentration around Circular/Elliptical/Triangular Cutouts in Infinite Composite Plate", Proceedings of the World Congress on Engineering 2011 Vol III, WCE 2011, July 6 - 8, 2011, London, U.K.




Figure 1: Elliptical Hole Created at Intersection of Inclined Circular Crossbore Hole and Bore of Tube. Hole Radius, R , Angle of Inclination of Hole to Tube Axis






Figure 2: Superposition Sequences for Unpressurized and Pressurized Elliptical Hole at Bore of Thick Cylinder; Eccentricity of Ellipse c



Elliptical Cutout: Stress Concentration on Major Axis + Additional Stress Concentrator (k), General Remotely Applied Biaxial Stress Field



Internally Pressurized Elliptical Cutout + Concentrator (k): Superposition to Determine Stress Concentration Factor

Figure 3: Superposition Sequences for Unpressurized and Pressurized Elliptical Hole plus Additional Stress Concentrator (k) at end of Major Axis; Eccentricity of Ellipse c