



AFRL-OSR-VA-TR-2013-0602

**CONSTRUCTURE OF UNIMODULAR SEQUENCES FOR
WAVEFORM-AGILE SENSING**

SOMANTIKA DATTA

UNIVERSITY OF IDAHO

**11/13/2013
Final Report**

DISTRIBUTION A: Distribution approved for public release.

**AIR FORCE RESEARCH LABORATORY
AF OFFICE OF SCIENTIFIC RESEARCH (AFOSR)/RSL
ARLINGTON, VIRGINIA 22203
AIR FORCE MATERIEL COMMAND**

REPORT DOCUMENTATION PAGE				<i>Form Approved</i> <i>OMB No. 0704-0188</i>	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY)		2. REPORT TYPE		3. DATES COVERED (From - To)	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION / AVAILABILITY STATEMENT					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT	b. ABSTRACT	c. THIS PAGE			19b. TELEPHONE NUMBER (include area code)

To: technicalreports@afosr.sf.mil

Subject: Final Report to Dr. Tristan Nguyen

Grant Title: Construction of Unimodular Sequences for Waveform-Agile Sensing

Grant #: FA9550-10-1-0441

Reporting Period: 15 August 2010 to 15 August 2013

Significant accomplishments:

1. The main goal of constructing *complex-valued unimodular stochastic* waveforms (both discrete and continuous) whose autocorrelation can be made arbitrarily small outside the origin has been completed.
 - In the discrete case, this is first done using Gaussian random variables and then generalized to other random variables. The random variables that can be used for the construction of such waveforms has been characterized.
 - For the continuous case, the construction of such waveforms has been done using Brownian motion.
 - The construction of multidimensional waveforms having low autocorrelation has also been done.
2. Frames are now a standard tool in signal processing due to their effectiveness in robust signal transmission and reconstruction. The unimodular stochastic waveforms with low autocorrelation as described in 1. above has been characterized in terms of frames. Further analysis on

how close such frames are to being tight, i.e., how closely they resemble orthonormal bases has also been done.

3. Welch bounds are a family of lower bounds on the maximal cross correlation between vectors or signals. These are heavily used in signal processing in analyzing the best of the worst case behavior when the number of signals accessing a channel is more than the dimension of the channel and the desired orthogonality among the vectors cannot be maintained. Under this project, this idea has been extended to obtain lower bounds on the maximal cross correlation among *subspaces* of a given Hilbert space. These are expected to be useful in light of the emerging area of fusion frames.
4. An explicit construction of a tight frame from a given frame that avoids inverting the frame operator has been done. The tight frame obtained spans the same subspace as the original frame. In addition, the tight frame vectors are linear combinations of the original frame vectors and therefore the signal coefficients do not have to be recomputed. This is particularly useful in areas of medical imaging where samples can only be taken on a set that may not be a tight frame and reconstruction time and error are both very important.

Archival publications during reporting period:

- S. Datta, *Construction of zero autocorrelation stochastic waveforms*, Advances in Pure Mathematics, Vol. 2., No. 6, pp. 428 - 440, Nov.

2012

- E. Au-Yeung & S. Datta, *Tight frames in spiral sampling*, Proc. 10th International Conf. on Sampling Theory and Applications (SampTA), Bremen, Germany, July 2013.
- E. Au-Yeung & S. Datta, *Tight frames, partial isometries, & signal reconstruction*, submitted.
- S. Datta, *Welch Bounds for Cross Correlation of Subspaces*, submitted.

Changes in research objectives, if any: none

Change in AFOSR program manager, if any: none

Extensions granted or milestones slipped, if any: none