



Cold Spray Technology for Repair of Magnesium Rotorcraft Components

ESTCP Proposal 06-E-PP3-031

Team:

ARL

Bruce Sartwell - Naval Research Laboratory

Yogi Kestler – NADEP Cherry Point

Tim Eden – ARL-PSU

Robert Guillemette SIK

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE JAN 2007		2. REPORT TYPE		3. DATES COVERED 00-00-2007 to 00-00-2007	
4. TITLE AND SUBTITLE Cold Spray Technology for Repair of Magnesium Rotorcraft Components				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Research Laboratory, 4555 Overlook Ave., SW , Washington, DC, 20375				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES 27th Replacement of Hard Chrome and Cadmium Plating Program Review Meeting, January 23-25, 2007, New Orleans, LA. Sponsored by SERDP/ESTCP.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 43	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



\$\$



Cold Spray Technology for Repair of Magnesium Rotorcraft Components

Program Objectives:

- To reclaim ZE 41A magnesium alloy components on Army and Navy helicopters that have been removed from service due to severe corrosion and/or wear.
- ARL will provide a repair/rebuild cold spray procedure for scrapped parts and assist in the transition and implementation of this technology, initially, at NADEP, Cherry Point, NC.



Cold Spray Technology for Repair of Magnesium Rotorcraft Components



Meeting Objective: to lay the foundation for a JTP that can be executed by the ESTCP team such that at the completion of the program NADEP, Cherry Point has a fully functional cold spray system that is reclaiming magnesium rotorcraft components.

•Overview of Cold Spray Technology

- Leveraged Programs (**unprecedented head start**)
- Discuss ARL Capabilities and Advantages of Cold Spray

•Present Test Results to Date

- Coating Integrity and Microstructural Analysis
- Adhesion, Hardness and Corrosion Tests
- Coating Material Selection and Powder Development
- Cold Spray Process Development and Hardware Modifications
- Cold Spray Demonstration on ZE 41A Mg Housings



Cold Spray Center at the US Army Research Laboratory (ARL) Aberdeen Proving Ground, MD 21005-5069



ARL Cold Spray Research Team

Phillip Leyman	Process Engineer	(410) 306-0818
Dr. Dennis Helfritsch	Process Engineer	(410) 306-1928
Dr. Matthew Trexler	Materials Engineer	(410) 306-0808
Michael Lister	Materials Engineer	(410) 306-1592
Scott Grendahl	Materials Engineer	(410) 306-0819
Dr. William DeRosset	Modeling/Simulation	(410) 306-0816
Marc Pepi	Mechanical Engineer	(410) 306-0848
Victor Champagne	Team Lead/Materials	(410) 306-0822



ARL Leveraged Formal Programs

•to develop aluminum cold spray coatings for aluminum, magnesium and/or steel substrates have been established with the following:

1. Defense Science & Technology Organization (DSTO)
2. Joint Strike Fighter (JSF)
3. National Center for Manufacturing Sciences (NCMS)
4. Lockheed Martin
5. Penn State Applied Research Laboratory
6. Lawrence Livermore National Labs (LLNL)
7. South Dakota School of Mines (SDSM)



Overview of Cold Spray Technology





Cold Spray: a process by which particulates are deposited by means of ballistic impingement upon a suitable substrate at super sonic velocities to form a coating or a free-standing structure.

Gas Control Module


Electric Heater

Cold Spray System Configuration

N₂ or
He gas



Powder Feeder



Supersonic Nozzle

Particle Stream

Substrate

Deposit

- Main Gas Stagnation Pressure 100-500 psi
- Gas Temperature 0-1300°F
- Main Gas Flow Rate 30-100 CFM
- Powder Feed Rate 10 to 30 pounds/hour
- Particle Velocity 300-1500 m/sec.
- Particle Size 1-100um diameter



Cold Spray Advantages



Super Plastic Particle Agglomerate Mixing (SPAM) bond

plastic deformation may disrupt thin oxide surface films to permit bonding similar to explosive welding

Compressive residual stresses

particles “peen” surface

plasma and wire-arc thermal spray coatings tend to be in tension

High density

low porosity: $< 0.5 \%$

low oxide content $< 0.3\%$

Thick coatings

free-form fabrication


Low Temperature Application

thermally sensitive substrates

low stresses due to CTE mismatch





Cold Spray vs. Thermal Spray



Cold Spray is performed at lower temperatures at high particle velocities


Copper Particle Impact Site



Cross section of the impact site between a copper particle and a stainless steel substrate.


Advantages of Low Temperature Process

Thermal Spray



www.gordonengland.co.uk



Cold Spray



The melting of particles that occurs during most thermal spray processes can result in oxidation of both the coating and substrate materials. The resulting oxides decrease the adhesive and cohesive strengths of the coating. The cold spray process avoids such reactions.



Mechanical Mixing at Interface




copper

EDS X-ray Mapping showing mechanical mixing between coating material and substrate


aluminum



Particle Velocity Distribution Measured by DPV 2000



**20 micron copper particles
25 mm downstream
400 psi, 400 C N₂ gas**





Cold Spray Coating of Nickel On 6061-T6 Al

Nickel
Coating

100% Dense




Cold Spray Ni has a hardness of HRC 41 and a resistivity of 6.84uohm/cm



316L SS Deposited by the Stationary System Using He



316L SS
Cold
Spray
Coating



Aluminum
Substrate

15kV

X50 500 μm

09 52 BES



Stationary Cold Spray System at ARL



Robot-Controlled, High Pressure, He and N Gas




Main Gas Stagnation Pressure 100-500 psi Gas Temperature 0-1300°F Main Gas Flow Rate 30-100 CFM

Powder Feed Rate 10 to 30 pounds/hour

Particle Velocity 300-1500 m/sec.

Portable Cold Spray Systems at ARL



- Hand-Held Heater-Nozzle
- Shop Compressed Air
- Particle Velocity 300-500 m/s




EMI Shielding for HMMWV Shelter by Cold Spray

ARL Produces First Prototype Using Cold Spray Technology for the Terminal High Altitude Area Defense (THAAD) Project Office.




- HMMWV shelters require EMI shielding to prevent entrance/escape of electronic signals.
- The joints in al-composite walls must be sealed with a non-porous, conducting metal.
- The composite structure requires low-temperature application of sealer.

Conductive material needed to fill seams



Aluminum

Composite






Applying EMI Shielding on the HMMWV Shelter

**Copper and Tin Deposited
Onto The Doorframe with the
Portable Cold Spray System**

**Aluminum/Zinc Applied
to Interior Seams**



**Cross Section of Cold
Spray Coating**







Cold Spray vs. Thermal Spray




Flame Spray Sn & Steel Coating, 12.2% Porosity



Cold Spray Sn Coating, 0% Porosity



Cold Spray Al Coating, 0.83% Porosity





CTMA*-NCMS Collaborative Project**

- 1. Corrosion protection of ferrous materials**
 - Painted structures – viz. ALV – access cover (USMC)
 - Hardened steel landing structures (Boeing)
 - Iron brake components (Delphi)
- 2. Corrosion protection and restoration of magnesium**
 - Repair ZE41& AZ91-D Magnesium (U.S. Army Research Lab, NADEP–Cherry Point, Ford)
- 3. Corrosion protection and restoration of aluminum**
 - repair of Alclad (Boeing commercial, Air logistics, Cherry Point)
- 4. Aluminum brazements (Delphi)**
- 5. Cold-spray consolidation by Ultrasonics (Solidica)**

* Commercial Technologies for Maintenance Activities

** National Center for Manufacturing Sciences




Cold Spray Coating of CP-Al On ZE 41A-Mg



**Cold
Spray
CP- Al
Coating**

**~100%
Dense**

**Coating /
Substrate
Interface**





CP- Al Cold Spray Coating Applied to ZE 41AMg

**Cold
Spray Al
Coating
0.015 inch**

**8,500 psi
adhesion**

**Interface is
free of voids
and oxides**





CP- Aluminum Cold Spray Coating Adhesion to Magnesium

Program	Conditions	Adhesion (psi)
ARL-DSTO	N ₂ , 380 psi, 250°C	2743
ARL-DSTO	He, 380 psi, 20°C	>6527
ARL-NCMS	He, 380 psi, 20°C	>8505


New Data Generated FY07 for ESTCP

ARL-ESTCP	N ₂ , 380 psi, 400°C	>10,350
-----------	------------------------------------	---------




Repair of Alclad Aircraft Skin by Cold Spray using CP Aluminum

Machined slot



Template shielded before spray


Cold Spray CP Al



0.035 inch thick cold spray repair



Example of Damage Repair



Machined Pit

Machined Groove

**ZE 41A
Magnesium Plate**

CP-Aluminum Cold Spray Coating

Machined Flush




Cold Sprayed vs. Wrought Materials Hardness Comparison

- The hardness of a cold-sprayed material is significantly higher than that of a conventional wrought material.**
- The hardening is a result of the plastic deformation that occurs during particle impact and the refined microstructure of the material.**




Cold Sprayed vs. Wrought Materials: Hardness






Cold Sprayed vs. Wrought Materials: Hardness





Cold Sprayed vs. Wrought Materials: Hardness











Aluminum Powder Morphology



-325 mesh 5056
Al Flake



-325 mesh Pure
Al Spherical







Aluminum Powder Morphology




1-5 um Pure Al
Agglomerated




-325 mesh Pure
Al Atomized



-325 mesh
5056 Al Flake



-325 mesh Pure
Al Spherical




Coating quality is critically dependent on the feed powder composition, morphology, oxygen content, and mechanical properties.




Purity of Cold Sprayed Aluminum

Oxygen content measured by Inert Gas Fusion

ASTM E 1019-03



-325 Mesh Cp-Al Powder



Cold Spray CP-Al Coating


0.34 %Oxygen

0.25 %Oxygen

*The oxygen content of the cold spray coating is largely determined by the oxygen content of the original powder, not the process.



Portable ARL Cold Spray System



Powder Feeder

Helium Tank


Spray Nozzle



ARL Portable System Parameters for Applying CP-Al to ZE41A - Mg

Operating Parameter	Setting
Helium Pressure	400 – 500 psi
Helium Temperature	20 Degree C
Helium Flow	20 SCFM
Powder Flow	1 – 5 gram/minute
Particle Mean Diameter	20 micron
Particle Exit Velocity	1000 meter/second
Helium Cylinder Life	9 minutes

CP-Al Deposited by the ARL Portable Cold Spray System




15kV

X30 500 μm

10 52 BES

CP-Al Deposited by the ARL Portable Cold Spray System



15kV


X100

100µm

10

52

BES



15kV


X1,000

10 μ m

10 52 BES



5056 Al Deposited by the Stationary System Using He



5056 Al
Cold
Spray
Coating

Aluminum
Substrate

Interface

X100 100 μm





5056 Al Deposited by the Stationary System Using He



**Cold
Spray
5056
Coating**

**Coating /
Substrate
Interface**





This is before process optimization!

15kV

X400 50µm

10 52 BES



Applying CP-Al by Cold Spray over Magnesium



ARL Achievements (FY07 Results Highlighted in Red)

Corrosion Resistance:

>5,000, **>7,000 hrs** salt fog resistance-ASTM B117 (Al, 4340 steel substrates)

>619, **>1,000hrs** (ZE 41A magnesium substrate)

Hardness:

57 Brinell Hardness

Yield Strength:

22ksi comparable to ZE41A-T6 and AZ91E-T6 magnesium

Density:

>99% with oxide content of 0.25%

Adhesion:

> 8,500 psi, **>10,350 psi**

Cold Spray Process Summary:

can be applied in production or in the field at room temperature





ARL Technical Hurdle

: to achieve similar results with the use of nitrogen as the carrier gas

: this hurdle has been overcome in FY07 with the use of a plastic nozzle!

Technical Approach



- * nozzle design
- *system modifications (heater, powder feed)
- *powder morphology and condition





Future Developments



Specification Development:

Like to explore using Mantech program at ARL-PSU to create commercial specification for cold spray

Cold Spray Book:

Published through the UK