

Performance of Self-Adaptive Techniques for Multi-Static, Concurrent Detection, Classification and Localization of Targets in Shallow Water using Distributed Autonomous Sensor Networks

Karim G. Sabra,
School of Mechanical Engineering, Georgia Institute of Technology
Atlanta, GA 30332
phone: (404) 385-6193 fax: (404) 894-1658 email: karim.sabra@me.gatech.edu

Award number: N00014-08-1-0087
<https://webwise.gtri.gatech.edu/auth/>

LONG TERM GOALS

To develop multi-static synthetic aperture interferometry and iterative time-reversal technique, with little signal processing effort involved and a-priori information on the environment, to provide concurrent detection, classification and localization of proud and buried targets in shallow ocean waveguides.

OBJECTIVE

The proposed Georgia Institute of Technology (GIT) research effort will develop self-adaptive signal processing techniques to enhance the resonant acoustic signatures of man-made targets. These signal processing techniques will be applied to the concurrent detection, classification and localization problem of these targets from an autonomous sensor network. Participation in the upcoming SWMASI'09 experiment, in collaboration MIT and MPL/SIO, will provide data to understand the fundamental performance and comparison between various sensor array configurations. The proposed research here will focus on the consistency and accuracy of the aforementioned self-adaptive methods when applied to scattered field data collected either on a vertical-receive array (VRA), or on a synthetic-aperture horizontal receive array (S-HRA) created from an AUV track, which is this the ultimate system implementation.

APPROACH

The GIT research effort, in collaboration with MIT and MPL/SIO, under the SWAMSI continuation, will address the fundamental scientific issues associated with using an autonomous underwater vehicle network for 3D multistatic concurrent DCL of proud and buried targets by an autonomous underwater vehicle network. In particular the performance of the developed self-adaptive technique will be assessed for two main receive array configuration (VRA and S-HRA)

Modeling and Simulation

The benefit of multi-statics for DCL in littoral MCM is the ability to explore the bistatic enhancement inherently associated with targets designed to be stealthy in regard to monostatic sonar systems. The development and design of optimal search strategies is therefore strongly tied to the understanding of

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2008		2. REPORT TYPE		3. DATES COVERED 00-00-2008 to 00-00-2008	
4. TITLE AND SUBTITLE Performance of Self-Adaptive Techniques for Multi-Static, Concurrent Detection, Classification and Localization of Targets in Shallow Water using Distributed Autonomous Sensor Networks				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Georgia Institute of Technology,School of Mechanical Engineering,Atlanta,GA,30332				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

the 3D characteristics of the target scattering process, including the mutual interaction between the target and the seabed stratification.

Target Scattering, Propagation and Signal Processing

This research project will model the bistatic acoustic response of simple elastic objects (e.g. shell) in both free space and shallow water waveguide (usgin OASES coupled to a local finite-element modelling of the target).

Algorithm Development

The main issue is to separate out the environment from the structure of the target in a self adaptive method—that is, a method not requiring detail knowledge of the environment. Additionally, the frequency content of the various target resonances vary with the bistatic aspect. Hence a conventional beamforming approach are insufficient to enhance multi-static detection of the resonating targets. Instead we will investigate detection algorithm based on the full multi-static space-time-frequency response of elastic targets.

WORK COMPLETED AND PRELIMINARY RESULTS




Figure 1: a) Bistatic response of an elastic shell (shell is 1m diameter, 1.5 cm thick steel). b) Time-frequency analysis of the backscatter response of an elastic stell (monostatic response). Note the various (narrowband) strong resonances appearing beyond the firstg specular echo.

For underwater sonar, time-frequency analysis and, in particular Wigner-Ville analysis, has been shown to be a relevant tool for discriminating a man made target (shell) from a natural one of the same shape (solid) and even to estimate some target characteristics (shell thickness, shear velocity..). This processing tool takes advantage of the evolutionary, time dependent aspect of the echo spectrum (see Fig. 1). The estimated time-frequency patterns can be used for detection and wideband classification of sonar echoes in order to reduce false alarms. In particular, the so-called "coincidence pattern" appearing for specific frequency range is a robust time-frequency signature of man-made shells (see Fig. 2). Using a standard spherical shell model target model, a time-frequency analysis allows to understand echo formation mechanisms and their bistatic evolution (see Fig. 3). The influence of the medium parameters as well as the source-receiver configuration was investigated in free space and will be extended to the case of a shallow water waveguide.

The influence of the medium parameters as well as the source-receiver configuration was also investigated in free space.




Figure 2: Sinogram of the same elastic shell (see Fig .1)

Most importantly the energetic coincidence pattern (resulting from the interactions of A0+ and A0- waves) appears to vary in the time-frequency plan when bi-static receiver angles changes.

This occur since the A0+ and A0- waves shift and separate as path lengths to the receiver vary for bi-static receiver angles (see Fig. 3). Hence a coherent processing of the various echoes of the spherical shell will not be possible using conventional approach limited to the frequency domain (e.g. conventional beamforming) since the frequency content of the echoes is not constant. Instead the full space-time-frequency coherence of the echoes need to be combined to enhance detection with respect to surrounding ambient noise and reverberation due to clutter.




Figure 3: Splitting of the bistatic time-frequency signature of the elastic shell in two patterns (#1 and #2) corresponding to the two coherent interference of A_{0+} and A_{0-} waves when their path lengths around the sphere vary (bistatic configuration); b) Theoretical interpretation of the observed time-frequency shift of the coincidence pattern due to variations in path length which is compensated by the difference in phase velocity of the interfering A_{0+} and A_{0-} waves away from the coincidence pattern.

IMPACT

This work is focused on developing potential MCM procedures to improve multistatic concurrent Detection, Classification and Localization of elastic target by investigating the full space-time-frequency coherence of their echoes.

PUBLICATIONS

“Time-frequency analysis of the bistatic response of elastic shells”, S. Anderson, K. G. Sabra. Paper in preparation.