



Cr-FREE METALLIC-CERAMIC COATINGS

ASETS Defense 2014

**Fort Myer, VA,
November 18-20, 2014**

**Bruce McMordie
Coatings for Industry**

**319 Township Line Road
Souderton, PA 18756**

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE NOV 2014		2. REPORT TYPE		3. DATES COVERED 00-00-2014 to 00-00-2014	
4. TITLE AND SUBTITLE Cr-Free Metallic-Ceramic Coatings				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Coatings for Industry,319 Township Line Road,Souderton,PA,18756				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES ASETSDefense 2014: Sustainable Surface Engineering for Aerospace and Defense, 18-20 Nov 2014, Fort Myer, VA.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 26	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

Aluminum-Ceramic Coatings on Gas Turbine Compressors

❑ Essential to Life of Steel Parts

- cases, blades, vanes, shafts

❑ Various Coatings and Systems

- Alseal 518 & 519
- SermeTel W & 962
- IP9183 & 9442
- Ceral 114 & 34
- SermeTel 5380DP



Aluminum-Ceramic Coatings

- ❑ **Slurries of Al in chromic & phosphoric acids**
- ❑ **Spray and Bake.**
 - **Chemically bonds to steel.**
- ❑ **Very Durable**
 - **Stable to more than 1000F (540C).**
 - **Resists salt corrosion, even when heated.**
 - **Unaffected by water, fuel, oils.**
 - **Tightly Adherent. Resists chipping.**

Aluminum-Ceramic Coatings

❑ Introduced in 1960's

❑ Technology Evolved

- Polished (blades & vanes) – 1975
- Corrosion Resistant Sealer – 1978
- Low Temp. Cure – 1980
- Polished & Sealed – 1980
- Dense & Smooth - 1987

❑ Now Widely Specified . . .

- PWA, CPW, GEAE, GE Energy, Siemens, others
 - Materials - PWA 595, GE A50TF1, CPW 88 and more
 - Processes – PWA 110, GE F50TF62, and more

❑ . . . And Used

- JT3D, JT8D, CF6-, T700, Allison 250, PT6-, etc.

Al-Chromate / Phosphate Slurries Contain Hexavalent Chromium

PEL = 5 micrograms / m³

No Cr⁺⁶ Remains After Cure

Source of Cr⁺⁶ in Depots

PEWG

Ultimate Green Engine

(circa 2006)

- ❑ Effort to Remove Cr^{+6} from Repair Depots**
- ❑ PEWG AFRL-ML-WP-TR-2007-4069**
Compared . . .
 - Aluminum-Inorganic Silicate**
Coatings For Industry (CFI)
 - Al-Chromate / Phosphate (Std.)**
Sermatech (now Praxair / PST)

Aluminum-Silicate Comparable to Aluminum-Chromate / Phosphate

- ❑ Humidity Resistance
- ❑ Galvanic Corrosion Resistance
 - >3000 hrs., scribed & unscribed, ASTM B117 salt fog.

**no rust, pitting, or
undercutting at scribe**

**(Al-silicate on 1010 carbon steel,
<10 ohms resistance as burnished)**



Source: AFRL-ML-WP-TR-2007-4069, Sept. 2006

Aluminum-Silicate Comparable to Aluminum-Chromate / Phosphate

- ❑ Humidity Resistance, Galvanic Corrosion Resistance
- ❑ Heat / Salt Resistance
 - Ten test cycles
 - One cycle = 6 hrs. @ 875F / 16 hrs. salt fog

1010 carbon
steel




<10 ohms
resistance as
burnished



Source: AFRL-ML-WP-TR-2007-4069, Sept. 2006

Aluminum-Silicate Comparable to Aluminum-Chromate / Phosphate

- ☐ Humidity, Galvanic Corrosion, Heat / Salt Resistance
- ☐ Adhesion & Compatibility
 - 90 degree bend around 8X dia. mandrel



Aluminum-Silicate Comparable to Aluminum-Chromate / Phosphate

- ☐ **Humidity Resistance**
- ☐ **Galvanic Corrosion Resistance**
- ☐ **Heat / Salt resistance**
- ☐ **Adhesion / Substrate Compatibility**

Source: AFRL-ML-WP-TR-2007-4069, Sept. 2006

Sealed Aluminum-Silicate Not Comparable to Sealed Aluminum-Chromate / Phosphate in PEWG Evaluation


- ☐ Corrosion Resistance – No Post Treat**
- ☐ Abrasion Resistance**
- ☐ Hot Oil, Water Resistance - Sealer**

Source: AFRL-ML-WP-TR-2007-4069, Sept. 2006



Abrasion Resistance of Aluminum-Silicate Without Sealer Comparable to Al-Chromate / Phosphate

- **Falling Sand Test of Al-Silicate Basecoat**
> 100 L sand per 1 mil (25 μm) per ASTM D968




Inorganic Phosphate Sealer for Aluminum-Silicate Unaffected by Hot Fluids

□ Stable in Hot Water

- After 24 hrs. at 120F (49C) in distilled water

Al-silicate
with 1st
generation
sealer in
PWEG test




Same Al-
silicate
with new
sealer in
same test

Inorganic Phosphate Sealer for Aluminum-Silicate Unaffected by Hot Fluids

□ Stable in Hot Oil

- After 8 hrs. at 400F (204C) in MIL-L-7808 Oil

Al-silicate
with 1st
generation
sealer in
PWEg test



Same Al-
silicate
with new
sealer in
same test



Sealed Aluminum-Silicate Comparable to Sealed Aluminum-Chromate / Phosphate

❑ Salt Spray Corrosion (ASTM B117)

- 2000 hrs. scribed and unscribed.

no rust, pitting,
or undercutting
at scribe

(Coating on plain
carbon steel)



2000 hrs. B117




Sealed Aluminum-Silicate Comparable to Sealed Aluminum-Chromate / Phosphate

■ Heat Cycle Salt Spray Corrosion

- 10 cycles 6hrs. @ 750F (399C) / 16hrs. 5 % salt fog

Al-Cr / PO₄
sealed
with
Cr / PO₄

(4130 alloy
steel)



Sealed Al with Cr(VI)

Sealed Cr-free Al-silicate

Al-silicate
with
improved
sealer

(4130 alloy
steel)

PEWG Update

**With Inorganic Phosphate Sealer,
Al-Silicate Comparable to
Sealed Al-Chromate / Phosphate**

- ☐ **Humidity Resistance**
- ☐ **Galvanic Corrosion Resistance**
- ☐ **Heat / Salt Resistance**
- ☐ **Adhesion / Substrate Compatibility**
- ☐ **Abrasion Resistance**
- ☐ **Hot Oil, Water Resistance - Sealer**
- ☐ **Corrosion Resistance - No Post Treat**

Beyond PEWG - Aluminum-Silicate on HSLA Steel

□ Galvanic Corrosion Resistance

- Pyrowear 53 HSLA steel, with & without sealer

**Sealed,
Cured
1 hour
at
425F**



**Sealed and
unsealed
(center),
Cured 4 hours
at 425F**

1000 hrs., 5 % neutral salt fog, B117

Aluminum-Silicate Handles Like Aluminum-Chromate / Phosphate

- ❑ **Single component (One Bottle)**
- ❑ **Easy to Apply**
 - Air-atomizing spray guns
 - No special spray booths
(humidity control a good idea)
 - Possible “drop-in”
- ❑ **Compatible with many substrates**
 - Carbon & HSLA steels
 - Stainless steels
 - Nickel-base alloys
 - Titanium
 - Aluminum
- ❑ **Water clean-up with no hazardous waste**



Aluminum-Silicate Is Processed Like Aluminum-Chromate / Phosphate

- ☐ Degrease substrate
- ☐ Blast with 120 mesh Al_2O_3 grit
- ☐ Apply Al-silicate
 - HVLP air-atomizing spray equipment
- ☐ Air dry 15 minutes
- ☐ Heat dry 15 minutes at 175°F
- ☐ Cure 30 minutes at 650°F
- ☐ Apply a second coat or post-treat as desired
 - Can defer cure of 1st coat until 2nd is applied.



Hazards of Inorganic Aluminum Metallic-Ceramics

Al-Cr₂O₇ / PO₄

- Zero VOC's.
- 13.0 wt. % inorganic phosphates
- 3.3 wt. % Cr⁺⁶ (hexavalent chromium) before curing.

Al-silicate

- Zero VOC's
- No hazardous mat'ls
- No carcinogens





Aseal[®] 5K Al-Silicate

Aseal[®] 5KT8 Sealer



**Aseal 5K^{††} + 5KT8 on PWA
GG-4 compressor disk**
Courtesy, Blastech Overhaul &
Repair, Bloomfield, CT

[†] PWA 36595

**Polished Aseal 5K[†] on
V8 exhaust header**
Courtesy, Maryland Performance
Coatings, Sykesville, MD



[†] US Pat. App. 2006/0166014 A1

Alseal[®] 5K

Aluminum-Silicate

☐ Specified by Pratt & Whitney

- **PWA 36595 Rev. B**
 - **Issued July 2007, Revised Nov. 2010**
- **Used on PW4000 shafts**

☐ In Test at Other OEMs

- **GE Power**
- **Rolls-Royce North America**
- **GEAE**
- **SNECMA**

**Al-Silicate Coating System
Now Available That Can
Eliminate Hazards of
Carcinogenic Cr^{+6}
in Al-Chromate / Phosphate
Compressor Coatings.**

Challenges

☐ Further Develop Capabilities


- Sealers?
- Low Temperature Cure?
- Smooth Finishes?
- Process Variables?
- Limits?

☐ Discover New Fundamentals

- 1 to 1 Correlation Not Guaranteed
- Ex. - Replacing Plating with Paint
 - Different thickness constraints
 - Blueprint Changes

☐ Produce Documentation

- Process Instructions
- Controls
- Prints & Drawings



Premium Coatings for the Aerospace Industry