



Smart Data Selection (SDS) Brief

October 2014

**Tom Young
SET Executing Agent
412 TENG/ENI
(661) 277-1071
Email: tommy.young.1@us.af.mil**

DISTRIBUTION STATEMENT A. Approved for public release: distribution unlimited.

**Test Resource Management Center (TRMC)
Test & Evaluation/ Science & Technology (T&E/S&T)
Spectrum Efficient Technology (SET)**

REPORT DOCUMENTATION PAGE				Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.					
1. REPORT DATE (DD-MM-YYYY) 25-02-2015		2. REPORT TYPE Technical Brief		3. DATES COVERED (From - To) 3/13 -- 12/14	
4. TITLE AND SUBTITLE Smart Data Selection (Brief)				5a. CONTRACT NUMBER: W900KK-13-C-0028	
				5b. GRANT NUMBER: N/A	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Shannon Wigent & Dr. Andrea Mazzario				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Laulima Systems LLC 1163 Lani Nuu St, Kalaheo, HI 96741-0000				8. PERFORMING ORGANIZATION REPORT NUMBER 412TW-PA-14507	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Test Resource Management Center Test and Evaluation/ Science and Technology 4800 Mark Center Drive, Suite 07J22, Alexandria, VA 22350				10. SPONSOR/MONITOR'S ACRONYM(S) N/A	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S) SET 2015-0032	
12. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release A: distribution is unlimited.					
13. SUPPLEMENTARY NOTES CA: Air Force Flight Test Center Edwards AFB CA CC: 012100					
14. ABSTRACT “The dominant inherent nature to TM in DoD testing is sampled time-history data from an ultimately analog world, (which) is not going to change drastically regardless of how data is transmitted to ground. A factor that could change that fact most is the degree to which answers instead of data are obtained on board the test vehicle” iNET Concept of Operations, v. 2007.1 SDS seeks to change this inherent nature of telemetry in DoD testing by: Developing an on-board capability to monitor and analyze test data in order to reduce the amount of data sent to the ground Employing bandwidth efficient algorithms to reduce bandwidth requirements Developing the capability to notify operators when data demonstrate abnormal behavior					
15. SUBJECT TERMS Spectrum, Aeronautical telemetry, algorithm, bandwidth, Integrated Networked Enhanced Telemetry (iNET), Smart Data Selection (SDS), Pulse Code modulation (PCM)					
16. SECURITY CLASSIFICATION OF: Unclassified			17. LIMITATION OF ABSTRACT None	18. NUMBER OF PAGES 22	19a. NAME OF RESPONSIBLE PERSON 412 TENG/EN (Tech Pubs)
					19b. TELEPHONE NUMBER (include area code) 661-277-8615
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			



Session 5 Processing 1

Session Chair: Steven Meyer

Smart Data Selection (SDS)

Shannon Wigent & Dr. Andrea Mazzario

International Telemetry Conference
21 October 2014

Approved for public release; distribution is unlimited
412 TW-PA-412 TW-PA-14507




U.S. AIR FORCE





Acknowledgements




This project is funded by the Test Resource Management Center (TRMC) Test and Evaluation/Science & Technology (T&E/S&T) Program through the U.S. Army Program Executive Office of Simulation, Training and Instrumentation (PEO STRI) under Contract No. W900KK-13-C-0028.

The Executing Agent and Program Manager work out of the AFTC.

Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the Test Resource Management Center (TRMC) and Evaluation/Science & Technology (T&E/S&T) Program and/or the U.S. Army PEO STRI.



Outline



- Project Description
- SDS ConOps
- System Description
- Bandwidth Efficient Algorithm
- PCM Compression Enhancement
- Benefits to T&E



Project Description

"The dominant inherent nature to TM in DoD testing is sampled time-history data from an ultimately analog world, (which) is not going to change drastically regardless of how data is transmitted to ground. A factor that could change that fact most is the degree to which answers instead of data are obtained on board the test vehicle"

iNET Concept of Operations, v. 2007.1

•SDS seeks to change this inherent nature of telemetry in DoD testing by:

- Developing an on-board capability to monitor and analyze test data in order to reduce the amount of data sent to the ground
- Employing bandwidth efficient algorithms to reduce bandwidth requirements
- Developing the capability to notify operators when data demonstrate abnormal behavior

Results in Significant Savings in Spectrum and Increased Operator Awareness



SDS ConOps





The SDS system:

- Analyzes pre-recorded data to identify behavioral trends
- Applies user-defined behavioral criteria
- Subscribes to all on-board parameters
- Determines what live data is of interest for real-time observation and analysis
- Applies bandwidth efficient algorithms to select measurements
- Generates specific messages to be sent to ground
- Provides alerts for data that demonstrate abnormal behavior
- Supports user feedback in response to alerts



System Description





Bandwidth Efficient Algorithms



- SDS applies extrapolation algorithms to “Normal” data
 - Allows for TA transmission of extrapolation parameters rather than individual measurement values
 - Ground calculates and publishes with required frequency
- TA monitors error between extrapolation values and actual measurements
- If error threshold exceeded, new parameters are calculated and applied




Bandwidth Savings




- Representative test results:
 - ~45,000 measurements at 98.04 Hz
- **Very small error threshold:**
 - Error $\leq 0.01\%$
 - SDS requires less than 7% of original bandwidth
- **Small error threshold:**
 - Error $\leq 0.02\%$
 - SDS requires less than 3% of original bandwidth




Bandwidth Efficient Algorithms



- Exponential Smoothing
 - Single Exponential Smoothing
 - $sv[i] = a * m[i] + (1 - a) * sv[i-1]$
 - Extrapolation: $ev[i+n] = sv[i]$
 - Double Exponential Smoothing
 - $sv[i] = a * m[i] + (1 - a) * (sv[i-1] + t[i-1])$
 - $t[i] = b * (sv[i] - sv[i-1]) + (1 - b) * t[i-1]$
 - Extrapolation: $ev[i+n] = sv[i] + n * t[i]$




Thermocouple Example



~45000 measurements @ 98.04 Hz







Bandwidth Savings



- 44091 Measurements
- Measurement Size = 2 bytes
- Error threshold of 0.01%
- 1001 EBE Resets
 - Transmission Cost = ~3 Measurements
- Extrapolated Data = $1001 \times 2 \times 3 = 6006$ bytes
- Raw Measurements = $44091 \times 2 = 88192$ bytes
- **SDS uses less than 7% of bandwidth required to send raw data**






Enlarged View






Enlarged View






Introduction of PCM Compression



- Utilize existing SDS framework to apply compression to PCM
- Provide PCM compression within TmNS messages
- Apply lossless data compression algorithms in conjunction with error correction for significant bandwidth savings




Benefits of Compression





- Potential to yield a 70% increase in bandwidth utilization
 - Provides availability to great volume of test data
 - Provides ability to support increased number of test articles concurrently
- Utilization of telemetry data characteristics improves upon compression rates resulting application of standard lossless compression



Introduction of PCM Compression




On-Board Test Article



Ground-Based




PCM Enhancement




- SDS current implementation is based on TmNS message format
 - Test Article and Ground modules to be updated to process PCM minor frames embedded in TmNS messages
- New capability added to process PCM in traditional PCM environment




PCM Demo





Benefits to T&E

- Bandwidth Savings/Increased Spectrum Efficiency
 - For measurements that demonstrate a normal behavior, transmit to the ground only a representation rather than the entire data set
- Simplified Pre-Test Configuration of Test Article Commutator
 - Analysis of pre-recorded test data allows for determination of expected behaviors
 - Allows for automatic configuration of transmission rates
- Enhanced Operator Awareness of Test Conditions
 - Automatic operator notification when data values outside of normal range
 - Allows operators to focus on situations requiring immediate attention



QUESTIONS?