

Geoacoustic Database Development for the ESME Initiative

James H. Miller and Gopu R. Potty
University of Rhode Island
Department of Ocean Engineering
Narragansett, RI 02881
Phone (401) 874-6540 fax (401) 874-6837 email miller@uri.edu

Award Number: N00014-00-1-0927

LONG-TERM GOALS

Our long-term objective is to establish a database of sediment and bottom properties including sediment compressional wave speed, shear wave speed, attenuation and density. Using this we propose to provide the best sediment model for any region with estimates of model uncertainty. These data would be appropriate for incorporation in state-of-the-art propagation models for acoustic effects prediction on the marine environment.

OBJECTIVES

1. Develop a surficial sediment model for the world's oceans based on optimal estimation techniques, geological models and data.
2. Integrate the sediment model into WHOI oceanographic models for input to ray/ normal mode/ PE based sonar effects studies.
3. Provide estimates for model uncertainty.
4. Apply this model in selected regions to test its accuracy and effectiveness.

APPROACH

As a first step we plan to collect all the available sediment property data at the region of interest. This includes all the geoacoustic (compressional wave speed, shear wave speed, attenuation etc.) and geotechnical properties (bulk density, permeability, porosity etc.). The geotechnical properties can be used to derive geoacoustic properties using a suitable model. These data can be obtained from literature or from available sediment property databases. In addition to these direct measurements of sediment properties we intend to collect other parameters which influence sediment distribution at any given region. These factors include, water depth at the location, distance to the shore, region, latitude, current speed and proximity to major river discharge

After collecting the data as described above, the next step is to express the non-linear model-data relationship in the form:

$$\mathbf{d}=\mathbf{G}(\mathbf{m})$$

where

Report Documentation Page

Form Approved
OMB No. 0704-0188

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE 30 SEP 2002		2. REPORT TYPE		3. DATES COVERED 00-00-2002 to 00-00-2002	
4. TITLE AND SUBTITLE Geoacoustic Database Development for the ESME Initiative				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Rhode Island, Department of Ocean Engineering, Narragansett, RI, 02881				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT Our long-term objective is to establish a database of sediment and bottom properties including sediment compressional wave speed, shear wave speed, attenuation and density. Using this we propose to provide the best sediment model for any region with estimates of model uncertainty. These data would be appropriate for incorporation in state-of-the-art propagation models for acoustic effects prediction on the marine environment.					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 6	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

$$\mathbf{d} = \begin{bmatrix} \text{water depth} \\ \text{distance from shore} \\ \text{latitude} \\ \dots\dots\dots \\ \dots\dots\dots \\ \dots\dots\dots \\ \dots\dots\dots \\ \dots\dots\dots \\ \dots\dots\dots \end{bmatrix}$$

and

$$\mathbf{m} = \begin{bmatrix} c(r) \\ \rho(r) \\ \alpha(r) \end{bmatrix}$$

The matrix \mathbf{G} defines the non-linear relationship between the sediment data (\mathbf{m}) and the factors which influence them (\mathbf{d}). The main task then will be to generate the kernel \mathbf{G} based on the relationship between \mathbf{d} and \mathbf{m} . Various sediment geoacoustic models (Hamilton⁴, Bowles⁵ etc.) sediment transport models and geological information can be used to develop the kernel matrix \mathbf{G} . We plan to proceed as follows:

1. Collect all the geoacoustic parameters available at various sites in the region of interest.
2. Collect also other parameters of influence like water depth, latitude, distance from shore, etc.
3. Develop a relationship (G) between these parameters using half of the available data.
4. Using G , predict the remaining half of the data and compare with the true data and thereby test the model. Tune the model until there is good agreement.
5. Using G calculate the geoacoustic parameters at any location.

WORK COMPLETED

A sediment model suitable for the Southern California Bight (SOCAL) region was first developed. The second test case corresponds to the Middle Atlantic Bight region. A program was written to generate sediment parameters for the Middle Atlantic Bight region which was chosen as the test site in the last (August 2001) ESME workshop. The location lies between latitudes 37 N and 43 N and 66 W and 74 W. The program is written in such a way that given the location and the frequency of interest, the sediment properties are estimated using all the available data. The sediment information available includes core data, sediment maps, sediment type information etc. For this location we were able to find some historical data which is listed below.

1. Core data:
 - ◆ Atlantic Margin Coring Sites 6009 to 6021^{1,2}. The sediment type information, sediment properties, layer thickness etc. were obtained from these.
 - ◆ Gravity core data³. Gravity cores were taken and analyzed from five locations as part of Primer study.
 - ◆ Vibrocore data
 - ◆ Piston Core data from USGS mapping program⁴
2. Sediment type information: from USGS sediment maps for the area⁵.
3. Compressional wave speeds and layer thickness using high resolution seismic studies (Brocher and Ewing)
4. Sediment sound velocity functions for North Atlantic (Houtz)
5. Sediment tomography using Primer data (Potty et.al.)
6. Thickness of surficial sand sheet (Knebel and Spiker)
7. Compressional wave velocities from multichannel refraction arrivals (Mc Ginnis and Otis)
8. Compressional and shear wave speeds using gravity wave inversion technique (Trevorrow and Yamamoto)
9. Sediment and geoacoustic models: Used for predicting the compressional and shear wave speeds as well as attenuation as function of frequency for different sediment types. These include Hamilton model¹¹, Bowles¹², and Biot- Stoll model¹³.
10. Sediment layer thickness maps⁸: Used for predicting the sediment thickness.




Figure 1. Two layer model to represent the sediment properties used in this study.

The program uses these data to arrive at the sediment parameters at a given location. The sediment compressional speed is estimated using the core data, sediment type information and the Hamilton's values for these sediment types. Sediment thickness is estimated based on the core data and sediment thickness map. Shear speed, and Compressional and shear attenuation are determined mainly using the sediment type information and predictions by Hamilton and Stoll. The bottom properties are specified for a simple two-layer model. Some of the properties (compressional and shear speeds in the basement) are assumed constant throughout the area. The output parameters are written in a text file.




Figure 2. Left panel shows the location of the ESME test case. Right panel shows the sediment sound speed obtained using the sediment model developed.

IMPACT/APPLICATIONS

Our effort is intended to provide the best possible estimates of sediment data needed for the propagation modeling component of the ESME initiative. This will enable the propagation modelers to use ‘best guesses’ when direct estimates of the sediment data is not readily available.

TRANSITIONS

We expect that this sediment model, when complete, will be useful to the acoustic community as a whole as an important database of sediment property information. This model can be integrated into OAML based on discussions with NAVOCEANO personnel.

REFERENCES

1. Hathaway J. C et al.,” U.S. Geological Survey Core Drilling on the Atlantic Shelf,” Science, 206(2), (1979).
2. Richards. A. F, Atlantic Margin Coring Project 1976- Preliminary report on shipboard and laboratory geotechnical data,” US. Geol. Surv. Open File Report 78-123, (1977).
3. Potty. G., Miller.J. H, Lynch. J.F and Smith. K.B,” Tomographic inversion of sediments in shallow water,” J. Acoust. Soc. Am., 108(3), (2000).
4. McGregor. B. A,” Environmental geological studies on the United States mid and north atlantic outer continental shelf area,” Final Report AA851-MUO-18, (1983).

5. Mattick et. al., "Sediments, structural framework, petroleum potential, environmental conditions, and operational conditions of the U.S. Mid- Atlantic outer continental shelf," USGS Open File Report, 75-61, (1975).
6. Brocher. T. M and Ewing. J. I, "A comparison of high resolution seismic methods for determining seabed velocities in shallow water," J. Acoust. Soc. Am., 79(2), (1986).
7. Houtz. R. E," Comparison of sediment sound velocity functions from conjugate margins," Geo. Soc. Am. Bull., 92(1), (1981).
8. Knebel. H. J, and Spiker. E.," Thickness and age of surficial sand sheet Baltimore Canyon area," Am. Assoc. Petr. Geo. Bull., 61, (1977).
9. Mc Ginnis. L. D, and Otis. R. M, "Compressional velocities from multichannel refraction arrivals on the Georges Bank- northwest Atlantic Ocean," ,Geophysics, 44, (1979).
10. Trevorrow. M. V, and Yamamoto. T," Summary of marine sedimentary shear modulus and acoustic speed profile results using gravity wave inversion technique," J. Acoust. Soc. Am., 90, (1991).
11. Hamilton E. L, "Geoacoustic modeling of the sea floor," J. Acoust. Soc. Am. 68(5), (1980).
12. Bowles F. A, "Observation on attenuation and shear-wave velocity in fine grained marine sediments," J. Acoust. Soc. Am. 101 (6), (1997)
13. Badiy.M, Cheng A, and Mu. Y," From geology to geoacoustics- Evaluation of Biot- Stoll sound speed and attenuation for shallow water acoustics," J. Acoust. Soc. Am., 95, (1994).

PUBLICATIONS

1. G. R. Potty, J. H. Miller and J. F. Lynch, "Inversion of sediment geoacoustic properties at the New England Bight," J. Acoust. Am. (under revision).
2. G. R. Potty and J. H. Miller, "Tomographic mapping of sediments in shallow water," IEEE. J. Ocean. Engg. (under revision)
3. K. B. Smith, C. W. Miller, A. F. D'Agostino, B. Sperry, J. H. Miller and G. R. Potty, "Three-dimensional propagation effects near the mid-Atlantic Bight shelf break (L)," J. Acoust. Am. 112(2), 373-376, 2002.
4. C- S. Chen, "Time- frequency analysis of underwater acoustic signals in the 2001 ASIAEX – East China Sea experiment," M. S Thesis, University of Rhode Island, 2002.

PRESENTATIONS/ CONFERENCE PROCEEDINGS

1. G. R. Potty, J. H. Miller, C- S Chen and C. Lazauski "Broad-band non-linear inversions in shallow water for geoacoustic parameters," First International Conference on Inverse Problems: Modeling and Simulation, Fethiye, Turkey, 2002 (Invited talk).
2. C. Lazauski, G. R. Potty, J. H. Miller, C-S. Chen and P. Dahl, "Sediment tomography in the East China Sea: Compressional wave speed and attenuation inversions from modal travel time dispersion and Airy phase measurements," J. Acoust. Am., 111(5), p.2388, 2001.
3. G. R. Potty, J. H. Miller, C- S Chen and C. Lazauski "Sediment tomography in the East China Sea: Preliminary results, J. Acoust. Am., 110(5), p.2724, 2001.