

MONITORING AIR-SEA EXCHANGE PROCESSES USING THE AMBIENT SOUND FIELD

Jeffrey A. Nystuen
Applied Physics Laboratory
University of Washington
1013 NE 40th Street
Seattle, WA 98105

phone: (206) 543-1343 fax: (206) 543-6785 email: nystuen@apl.washington.edu
Award #: N00014-96-1-0423

LONG-TERM GOAL

The ambient sound field in the ocean contains information about processes producing the sound. At higher frequencies, above 1 kHz, much of the sound is produced locally by air-sea exchange processes such as wave breaking, wind and precipitation. Furthermore, ambient bubble populations can modify these sound fields in predictable ways. By learning to listen to the ambient sound field, we will be able to develop a method for measuring these phenomena using inexpensive and robust sensors (passive hydrophones).

SCIENTIFIC OBJECTIVES

Measuring air-sea exchange processes is a critical component of predicting mixed layer development and establishing the flux of heat, momentum, water and gas between the atmosphere and oceans. Several of these processes, for example, wave breaking, precipitation and sub-surface bubble populations, are notoriously difficult to measure, in part because of the difficult environment at the air-sea interface. These same processes are responsible for much of the locally-generated underwater sound above 1 kHz. Thus, it is possible to identify surface conditions by listening to the ambient sound (Nystuen and Selsor, 1997). By measuring these processes acoustically, their contribution to mixed layer development, and their influence on other exchange processes can be studied. Conversely, predicting ambient sound levels given environmental weather conditions will be much improved.

APPROACH

Three data sets have been collected or acquired. The first is a comprehensive record of the sound generated underwater by rainfall in a shallow pond from Miami, FL. These data are 1-second resolution 0-50 kHz sound spectra from over 800 rain events during a 17 month period. Collaborating data includes rain measurements from several types of automatically-recording rain sensors, including optical, capacitance, tipping bucket, weighing, acoustic and a disdrometer (Nystuen et al. 1996; Nystuen 1997a). A second data set includes oceanic ambient sound measurements (provided by D. Farmer, IOS) recorded during the 90-day long ONR sponsored ASREX experiment in the North Atlantic during the winter of 1993/1994 (H. DeFerrari, lead PI). These data were

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1997		2. REPORT TYPE		3. DATES COVERED 00-00-1997 to 00-00-1997	
4. TITLE AND SUBTITLE Monitoring Air-sea Exchange Processes Using the Ambient Sound Field				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Washington, Applied Physics Laboratory, 1013 N.E. 40th Street, Seattle, WA, 98105				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

recorded from a sub-surface mooring. Ancillary data include sub-surface acoustic backscatter, sub-surface bubble measurements and various surface measurements, e.g., temperature, salinity, waves, humidity, etc. The third data set is from a series of autonomous acoustic drifters air-deployed in various regions around the world. A co-located passive microwave satellite (SSM/I) data were acquired for comparison to the drifter data.

In addition to these existing data sets, several new data sets are being acquired or are planned. These include ambient sound measurements from two deep ocean moorings in the eastern tropical Pacific Ocean (NOAA PACS program) and some US coastal water moorings (NOAA NDBC and NASA TRMM collaborators). These surface moorings include ancillary rainfall measurements.

WORK COMPLETED

The Miami, FL rainfall data set has been analyzed to document the potential and the limitations of the acoustical inversion to quantitatively measure raindrop size distribution within rain (Nystuen, 1997a; 1997b). The drifter data set has been analyzed to validate acoustic wind speed measurements and rainfall detection by comparison to passive microwave satellite data (Nystuen, 1997c). The ASREX data set has been partially analyzed to produce a climatic-type rainfall record for the duration of the experiment and to provide rainfall rate data for process studies on the influence of rain on other air-sea exchange processes. Two instruments were designed, built, tested and deployed on deep ocean surface moorings. Another instrument was deployed on a coastal surface mooring. Data from these new deployments are not yet available for analysis.

RESULTS

Because different raindrop sizes produce sound underwater by different physical mechanisms, the underwater sound can be decomposed into components associated with each drop size category. These drop size categories have been carefully documented and show that the acoustic inversion can be used to identify changing drop size distributions within rain, potentially allowing classification of rainfall type (convective, drizzle, stratiform). Rainfall rate, the most often desired end product, is determined by summing the contribution from each drop size category. When compared to five other types of automatic rain sensors, the acoustical measurement is correlated to the other gauges with a correlation coefficient of roughly 0.9. The single most important factor affecting the acoustic measurement is the presence or absence of very large raindrops (over 3.5 mm diameter) within the rain. These drops are extraordinarily loud underwater and dominate the sound field when present. If these very large raindrops are not properly detected and accurately counted, then the smaller drop size populations are poorly estimated. In particular, the medium raindrop size category (1.2-2.0 mm diameter) is relatively quiet underwater, and consequently, relatively hard to measure acoustically. In contrast, the small raindrops (0.8-1.2 mm diameter) are relative loud underwater and easily detected acoustically.

The first step in the analysis of oceanic ambient sound data is to identify the present surface weather conditions (wind, drizzle, heavy rain, ambient bubbles present) (Nystuen and Selsor, 1997). Oceanic ambient sound measurements from 15 autonomous surface drifters were compared to passive microwave satellite (SSM/I) measurements of surface wind speed, atmospheric liquid water (cloud and rain drops) and rainfall (Nystuen, 1997c). The correlation between acoustic and satellite wind speed estimates was 0.91 (254 data points). The acoustic wind speed measurement showed no regional or environmental variability, but was biased low compared to the satellite measurement by 0.8 m/s. Of 21 acoustically detected precipitation events (both drizzle and heavier rain), the satellite measurements confirmed 19 (90% detection rate). Given unproven algorithms and the mismatch of temporal and spatial sampling by the drifter and the satellite sensors, quantitative comparisons are difficult to evaluate. Light rain and drizzle was not acoustically detected when the wind speed was above 7-8 m/s.

The second oceanic data set, from ASREX, was analyzed to produce a 90 day record of the rainfall. An estimated 477 mm of rain fell, including 5 storms with more than 20 mm of rain accumulation. The temporal detection of rain (drizzle 3.0 % of the time; heavier rain 2.4% of the time) are the type of statistics needed by climatologists (Petty, 1995). Not only do these data demonstrate the potential for climatological rainfall measurements, they also allow the first opportunity to examine the influence of rainfall on other air-sea processes, for example, near surface salinity, surface waves, gas exchange, etc. In particular, 1-m salinity measurements showed very large "fresh water" fluxes during extended periods of light rain/drizzle, but had a very different character during heavier rain when the winds were higher. There is a suggestion of surface wave damping by rain. The ASREX data set also shows evidence of bubble injection into the mixed layer by rain. Whenever rain occurs during high wind speed (over 10 m/s) conditions, the spectral slope above 10 kHz steepens, an indication of bubbles being mixed downward deeply enough to change the ambient sound field. The deep injection of these bubbles into the mixed layer suggests possible enhanced gas exchange during these conditions (heavy rain during high winds).

IMPACT/APPLICATIONS

Analysis of the ambient sound field to provide important air-sea exchange measurements is a technology that should lead to important advances in our understanding of the physics of the air-sea interface. The measurement is simple and robust. It can be made from small, autonomous drifters, or larger surface moorings.

TRANSITIONS

The Tactical Oceanography Warfare Support (TOWS) program at NRL has sponsored the development of air-deployable autonomous drifters (Selsor, 1993). Navoceano is now deploying these sensors on a regular basis. Hydrophones have been incorporated onto a new generation of Lagrangian drifters (Niiler, SIO). The NOAA National Data Buoy

actively exploring the potential application of this technology from their platforms. As part of the NOAA PACS program, acoustic sensors have been mounted on two deep ocean moorings. If the measurements prove complimentary to the existing instrumentation, acoustic sensors could become a regular component of the NOAA TAO tropical ocean mooring array.

RELATED PROJECTS

Acoustical Rainfall Analysis, sponsored by the Ocean Sciences Division, Ocean Instrumentation, of the National Science Foundation, broadly overlaps this project. The goal of the NSF project is to develop the acoustical inversion technology to provide a means of making oceanographic rainfall measurements. These measurements will then be used to monitor rainfall in climatological or event-specific process studies.

A second project, Determination of surface rainfall drop size distribution, sponsored by the NOAA Pan-American Climate Studies (PACS) program, applies this technology to obtain rainfall data as part of a major field experiment in the eastern tropical Pacific Ocean during 1997. These data will be used to explore the structure and influence of rainfall on atmosphere-ocean conditions during this experiment.

REFERENCES

- Nystuen, J.A., 1997a: Evaluating Automatic Rain Gauges for Deployment on Ocean Buoys," National Data Buoy Center, Stennis Space Center, MS 39529, February 1997, 57 p.
- Nystuen, J.A., 1997b: Quantitative Rainfall Measurements using Underwater Sound. In *Natural Physical Processes Associated with Sea Surface Sound*, ed. T. Leighton, University of Southampton, 73-82.
- Nystuen, J.A., 1997c: Validation of Acoustic Measurements of Wind and Precipitation using Expendable Ambient Noise Sensor (ANS) Drifters, AN/WSQ-6 (XAN-2). Final Technical Report, Grant #N00014-94-1-G906, Naval Research Laboratory, via Defense Technical Information Center, Alexandria, VA 22304-6145, 21 p.
- Nystuen, J.A. and H.D. Selsor, 1997: Weather Classification using Passive Acoustic Drifters. *J. Atmos. and Oceanic Tech.*, **14**, 656-666.
- Petty, G.W., 1995: Frequencies and characteristics of global oceanic precipitation from shipboard present-weather reports, *Bull. Am. Meteor. Soc.* **76**, 1593-1616.
- Selsor, H.D., 1993: Data from the sea: Navy Drifting Buoy Program. *Sea Technology* **34**, 53-58.