

AN INVESTIGATION OF SURFACE CURRENTS AND INTERNAL WAVES OVER THE INNER AND MID SHELF DURING THE DUCK94 EXPERIMENT

Hans C. Graber

RSMAS - Applied Marine Physics

University of Miami

4600 Rickenbacker Causeway

Miami, FL 33149-1098

phone: (305) 361-4935, fax: (305) 361-4701, e-mail: hgraber@rsmas.miami.edu

Lynn K. Shay

RSMAS - Meteorology and Physical Oceanography

University of Miami

4600 Rickenbacker Causeway

Miami, FL 33149-1098

phone: (305) 361-4075, fax: (305) 361-4696, e-mail: lshay@rsmas.miami.edu

Brian K. Haus

RSMAS - Applied Marine Physics

University of Miami

4600 Rickenbacker Causeway

Miami, FL 33149-1098

phone: (305) 361-4935, fax: (305) 361-4701, e-mail: bhaus@rsmas.miami.edu

Award #: N00014-94-1-1016

LONG-TERM GOAL

To understand the dynamics and temporal and spatial variability of the circulation over the inner to mid-shelf region and to examine which mechanisms and interactions are responsible for observed surface flow features? In addition, we seek to understand to the capability of this remote sensing technique for high-resolution wind and wave measurements in coastal regions.

SCIENTIFIC OBJECTIVES

In this study we seek to establish a better understanding of the dynamics and variability of the circulation over the inner and mid shelf. Using a combination of spatial and temporal high-resolution remotely sensed surface vector current maps and in-situ current and hydrographic observation we like to determine the plausible mechanisms and interactions which drive the circulation over the inner and mid shelf. The high-resolution HF Doppler radar measurements will make it feasible to evaluate the alongshore variability of the cross-shelf transport, which is critical in assessing beach erosion and sediment transport. In addition, wind and waves are also crucial forcing function over the shelf. By estimating winds and waves from the radar measurements, we expect to investigate the ocean current response of the inner-shelf waters with respect to wind and wave effects, including the transfer of wave momentum to the mean flow. Finally, the unique data set obtained in this way will let us resolve the surface and subsurface internal wave response (from f to the Nyquist frequency of 1.5 cph) over the shelf region including barotropic and baroclinic tidal effects.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1997		2. REPORT TYPE		3. DATES COVERED 00-00-1997 to 00-00-1997	
4. TITLE AND SUBTITLE An Investigation of Surface Currents and Internal Waves over the Inner and Mid Shelf During the Duck94 Experiment				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) University of Miami,Rosensteil School of Marine and Atmospheric Science,4600 Rickenbacker Causeway,Miami,FL,33149				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 4	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

APPROACH

During the second phase (October 1994) of the DUCK94 experiment we deployed a dual-frequency, linear-phased array HF Doppler radar to measure surface currents, surface gravity waves and wind speed and direction at high spatial and temporal resolution and over a large domain between the US Army Field Research Facility (FRF) and Corolla, NC. The remotely-sensed surface vector currents provide a synoptic view of the different flow dynamics in the coastal ocean. Using improved algorithms, which we developed based on previous theory and data sets, we will also extract wind and wave information from the Doppler spectra.

WORK COMPLETED

Completed works include:

1. All surface vector currents have been processed and quality controlled. From this data set we computed tidal currents, mean (low-pass), band-pass and high-pass current fields;
2. All Doppler spectra for the month long measurement period have been processed and information of the energy in the first and second-order peaks have been extracted for computations of wave heights;
3. A data report describing the OSCAR measurements has been distributed to all DUCK94 investigators;
4. A detailed comparison has been completed between the OSCAR vector currents and the current meters at the 20 and 25-meter CoOP moorings from S. Lentz (WHOI);
5. The Doppler spectra were used to evaluate different wave height algorithms and make improvements on the modified Barrick (1977) algorithm (S. Heron, 1996, Honors Thesis);
6. Two periods have been analyzed when salinity measurements at the two WHOI moorings showed evidence of the presence of a coastal buoyant jet;
7. Two time periods were selected to analyze in detail the characteristics of the coastal buoyant jet;
8. Bragg peak ratio was used to extract high-resolution wind directions for several time periods; and
9. Radar-derived wave height maps were validated and compared with in-situ wave buoy (from R. Jensen, CERC) and pressure gauges along offshore transect (from T. Herbers, NPS).

RESULTS

Comparisons of the HF-derived surface currents to the subsurface currents from two Vector Measuring Current Meters at 4 and 6 m indicated biases of 2 to 6 cm/s, slopes of $O(1)$, and rms differences of 7 to 9 cm/s (Shay et al. 1997). These rms differences approach the uncertainties in the HF-radar of 5 cm/s and the VMCM of 2 to 3 cm/s. Tidal forcing consisted of diurnal (K_1) and semidiurnal (M_2) tidal constituents where the surface and subsurface (4 m) speeds were 3 and 8 cm/s, and 2 and 7 cm/s, respectively. The semidiurnal component was barotropic with M_2 amplitudes of about 8 to 10 cm/s in the far-field as it propagated in a cross-shelf direction (Cook and Shay, 1998).

The temporal and spatial measurements of the detided surface current fields can provide critical quantitative information on characterizing a buoyant coastal jet in terms of width, offshore distance, velocity and spatial variability. The results show that the detided, alongshore velocity field can clearly demarcate the near- and offshore boundaries of the coastal jet. Furthermore, a widening of the jet towards the south is visible that could be caused by bathymetric features there.

The DUCK94 HF radar data provided a unique opportunity to improve and validate the system's capability to measure significant wave height. Heron and Heron (1997) evaluated several existing algorithms based on simple power-law relations involving the ratio of the integrated weighted second-order radar cross-section to the first-order radar cross-section. They found that the half-power law, $H_{\text{rms}} = \alpha \lambda R^{1/2}$, is robust for rms wave heights as low as 20 cm. Here $\alpha = 1/3$ is an empirical constant and R is a weighted ratio of the integrals as defined in Barrick (1977). Heron (1996) has examined in detail the application of these three different power law relations for estimating wave heights with HF radar backscatter data acquired during DUCK94. He found that a modified version of Barrick's (1977) algorithm provided the most accurate wave height estimates with a rms error of only 14 cm for wave heights ranging from 50 cm to 4 m. Sequences of hourly averaged wave height maps derived from three 20-minute OSCAR Doppler spectra delineate the spatial evolution of the storm-generated waves as they approach the shore. As the storm strengthened the wave heights appear to be uniform in the alongshore direction. Whereas at the peak of the storm the influence of the bottom through shoaling and depth refraction is quite apparent displaying spatially variable wave heights over the inner shelf (water depth ≤ 25 m) (Graber and Heron, 1997).

We have also used the DUCK94 data set to estimate the wind direction from the ratio of the powers of the Bragg peaks. The results show the potential for acquiring high-resolution spatial information on the sub-mesoscale variability of the coastal wind field. In particular, the 1 km resolution of wind direction maps can easily detect the location of frontal systems and their subsequent movement onshore or offshore. The agreement with two local wind measurements at the FRF pier and the Inner Shelf wave discus buoy exhibit differences of less than 10 degrees.

IMPACT/APPLICATION

The use of HF radar measurements of high-resolution surface currents, wave height and wind direction estimates provides a new view into the small-scale dynamics affecting coastal and nearshore processes. The combination of in situ measurements with radar observations enhances our understanding of the evolution of the three-dimensional structure of coastal dynamics; in particular the data becomes critical test beds to validate models of coastal circulation and wave height prediction. Ultimately, these results will improve our ability to quantify sediment transport and shore erosion rates and the cross-shelf momentum transport.

TRANSITIONS

Our HF radar measurement capabilities have been used in numerous ONR-funded projects and are rapidly gaining acceptance among the oceanographic community to study coastal dynamics. NRL-Stennis is interested in using such data to validate coastal circulation models, while the US Army Corps of Engineers uses the wave height estimates to improve and validate shallow water wave prediction models.

RELATED PROJECTS

Related projects include:

1. The surface current measurements with OSCAR during DUCK94 has helped to support Sarah Rennie (VIMS) and John Largier (SIO) in analyzing the ADCP transect data from the CoOP program;
2. OSCAR surface current fields were made available to John Allen (OSU) to examine the impact of assimilating real data in simple coastal circulation models;
3. The study of the coastal buoyant jet has led to a new NRL/ONR funded measurement program on the Chesapeake Bay outfall plume experiment; and
4. OSCAR measurements will also be used to provide synoptic measurements of waves and currents during the field program phase of the new ONR-funded Shoaling Waves DRI.

REFERENCES

- Barrick, D.E., 1977. "Extraction of wave parameters from measured HF sea echo Doppler spectra," *Radio Sci.*, 12, 415-424.
- Cook, T. M., and L. K. Shay, 1998. "Tidal variability observed with high frequency radar," 2nd AMS Conf. on Coastal Atmospheric and Oceanic Prediction, 11-16 January 1998, Phoenix, AZ, American Meteorological Society, Boston, MA, (in press).
- Graber, H.C. and M.L. Heron, 1997. "Wave height measurements from HF radar," *Oceanography*, 10(2), 90-92.
- Heron, S.F., 1996. "Waveheight analysis using HF radar," Honors Thesis, Department of Physics, James Cook University of North Queensland, 91pp.
- Heron, S.F. and M.L. Heron, 1997. "A comparison of algorithms for extracting significant wave height from HF radar ocean backscatter spectra," Submitted to *IEEE J. Oceanic Eng.*
- Shay, L.K., S.J. Lentz, H.C. Graber, and B.K. Haus, 1997. "Current structure variations detected by high frequency radar and vector measuring current meters," *J. Atmos. Oceanic Tech.*, in press.