

A NEW SCHEME FOR ACOUSTICAL TOMOGRAPHY OF THE OCEAN

Alexander G. Voronovich

NOAA/ERL/ETL, R/E/ET1, 325 Broadway, Boulder, CO 80303
phone: (303)-497-6464 fax: (303)-497-3577 email: agv@etl.noaa.gov

E.C. Shang

NOAA/ERL/ETL, R/E/ET1 325 Broadway, Boulder, CO 80303
phone: (303)-497-6363 fax: (303)-497-3577 email: eshang@etl.noaa.gov

Award #: N00014-95-F-0046

Long-range propagation

LONG-TERM GOALS

The long-term purpose is to develop a new scheme of the acoustical tomography of the ocean of meso- to global scales which is based on measurements of horizontal-refraction angle (HRA) related to different acoustic modes rather than travel times along different rays.

SCIENTIFIC OBJECTIVES

To develop robust inversion scheme for retrieving 3-D ocean inner structure based on measurements of HRA. In spite of its small value HRA angle can be easily measured with the help of pair of mode-resolving line vertical arrays situated about 10 km apart (ocean interferometer). As a first approximation adiabaticity of mode propagation should be assumed. Then the scheme should be generalized to the case of non-adiabatic propagation with mode interaction taken into account in "N times 2-D" approximation, and appropriate computer simulations should be performed. Scattering of acoustic signals from internal waves should be also considered, and its effect on the accuracy of sound speed field retrieval should be estimated.

APPROACH

A low frequency tonal sound source ($F = 30\text{-}100$ Hz) is assumed to be towed by a vessel around the area of interest with typical horizontal scale of the order of 1000 km. Thus, the area is exposed from different directions, and HRA is known as a function of source position. Those data are then used for tomography inversion. It proceeds in two stages: 1) 2-D tomography which retrieves propagation constants of different modes at the nodes of horizontal rectangular grid covering the area. 2) 1-D tomography which retrieves sound speed profile (in terms of expansion with respect to a set of empirical orthogonal functions) at each node of horizontal grid based on already determined values of propagation constants.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 1997		2. REPORT TYPE		3. DATES COVERED 00-00-1997 to 00-00-1997	
4. TITLE AND SUBTITLE A New Scheme for Acoustical Tomography of the Ocean				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Oceanic and Atmospheric Administration (NOAA),Environmental Technology Laboratory,325 Broadway,Boulder,CO,80303				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 3	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

WORK COMPLETED

The inversion scheme described above was developed. Numerical simulations were conducted to check the scheme in the adiabatic case. Then mode interactions were taken into account, and appropriate iterative approach for inversions was developed. This approach was also realized as a software package, and appropriate numerical simulations were performed.

RESULTS

At the earlier stages of the research project it was found that in the adiabatic approximation the inversion scheme performs very well. The accuracy in measurements of source coordinates or ambient noise is not an issue for accomplishing this inversion scheme. The main source of errors in measurements of HRA lies in scattering from internal waves. The estimate shows that standard deviation of HRA error has the order of .001 rad. Averaging can reduce this value by a factor of 5. As a result the accuracy of retrieving the sound speed profiles for model eddy appeared to be less than 1 m/s for maximum value of deviation of sound speed and a few tens of cm/s for corresponding depth-averaged values. During 1997 the efforts were made to estimate the role of acoustic mode interaction. It was found, that the effects of mode interaction on HRA are usually small, and can be taken into account by appropriate rapidly converging iterative procedure with adiabatic propagation considered as a first approximation. Mention, that interaction effects themselves can be in fact not negligible, and corrections to modes' phase are significant. However, they cancel out for appropriate phase differences (HRA).

IMPACT/APPLICATIONS

The main conclusion is that the suggested acoustic tomography inversion scheme is feasible and can be practically used. Potential applications of the HRT for acoustic tomographic inversion of ocean frontal structure and solitons in coastal area are also promising. This scheme is simpler and cheaper than "traditional" time-of-flight based tomography, because: 1) it uses only simple low-power tonal signals; 2) there is no need in exact positioning of the source and exact time keeping; 3) interpretation of data and inversion technique is greatly simplified; 4) inversion is not subjected to "non-linear biases"; 5) duration of the tomography measurements is reduced significantly.

RELATED PROJECTS

An exact non-parabolic algorithm developed within the project "Non-parabolic marching algorithm for sound field calculations in the inhomogeneous ocean waveguide" was used for numerical simulations taking into account mode interactions.

REFERENCES

A.G. Voronovich and E.C. Shang (1997): Numerical simulations with horizontal-refraction-modal tomography. Part I. Adiabatic Propagation," J. Acoust. Soc. Am., v. 101, 2636-2643.

E.C. Shang (1997): Ocean acoustic thermometry and tomography," J. Ocean Univ. Qingdao,
v. 27, No. 1, 1-15.

E.C. Shang, Y.Y. Wang and A.G. Voronovich (1997): Nonlinear tomographic inversion by using WKB modal condition," J. Acoust. Soc. Am., v.102, (Dec. issue)