

Synoptic Estimates of Waves and Currents via Real-Time Assimilation of In-Situ Observations

PI: David T. Walker
Veridian Systems Division, Inc.
P.O. Box 134008 Ann Arbor MI 48113-4008
phone: (734) 994-1200 x2987 fax: (734) 994-5824 email: david.walker@veridian.com

CO-PI: Merrick C. Haller
Oregon State University, Corvallis, OR 97331-2302
phone: (541) 737-9141 fax: (541) 737-0485 email: hallerm@engr.orst.edu

Award Numbers: N00014-00-D-0114-0007, N00014-02-1-0147
<http://www.veridian.com/>

LONG-TERM GOALS

The long-term goal of this effort is to develop a methodology to monitor near-shore waves and currents over large spatial scales using data from in-situ sensors.

OBJECTIVES

The proposed program will develop the capability of monitoring nearshore waves and currents over large scales, and will allow the timely use of information from in-situ sensors. The specific objectives to be addressed are to: 1. Develop a near-real-time capability for assimilating single- or multiple-point in-situ observations into a phase-resolving wave model; 2. Test and validate the methodology against both simulated data and archival field data for both simple and complex beach types; and 3. Conduct a full-scale test of the methodology by applying it in near-real time to a comprehensive field experiment on complex topography.

APPROACH

The procedure being developed makes use of a variational data assimilation capability for the extended-Boussinesq wave model of Wei *et al.* (1996). The approach is to use time-series data from instruments in the interior of a region to estimate the time-dependent boundary conditions for the Boussinesq model at the boundaries of the region. These boundary conditions will yield a Boussinesq-model prediction, which matches the data.

WORK COMPLETED

The work completed during the past fiscal year includes development of the mathematical framework for the assimilation procedure, improvements in the numerical implementation of the extended Boussinesq model and its adjoint, and addition of improved wavemaker and run-up models in the parallel Boussinesq code.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE 30 SEP 2003		2. REPORT TYPE		3. DATES COVERED 00-00-2003 to 00-00-2003	
4. TITLE AND SUBTITLE Synoptic Estimates of Waves and Currents via Real-Time Assimilation of In-Situ Observations				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Veridian Systems Division, Inc., P.O. Box 134008, Ann Arbor, MI, 48113				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 5	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

RESULTS

The objective of this program is to develop a methodology to use in-situ, time-series observations from the interior of a near-shore region to determine the time-dependent boundary conditions to be applied to an extended Boussinesq wave model to reproduce the observed wave field.

During the past year the main issues addressed have been improvements to the numerical implementation and the physical modeling in the parallel Boussinesq code. The basic time-stepping scheme introduced by Wei *et al.* (1996) has been retained, but the accuracy of the spatial derivatives used on the right-hand side of the equations has been increased to fourth order, now used everywhere but in the mixed spatial/temporal derivatives which contribute to the dispersive terms, which remain second order approximations. In addition, a dealiasing filter has been implemented to limit the generation of high-wavenumber noise, caused by the nonlinearities in the equations. This filter removes energy at wavenumbers greater than two-thirds of the Nyquist wavenumber, and is applied every time step. This eliminates, at the source, the energy, which accumulates at the Nyquist frequency as a result of the nonlinear terms, and is more effective than periodically filtering the solution. In addition, the parallel code has been ported from FORTRAN77 to FORTRAN90 and implemented for both SUN and Intel/Linux platforms using either the MPICH or LAM MPI (Message Passing Interface) packages.

Improvements to the physical modeling in the forward Boussinesq model code includes improvements to the run-up model, wave-breaking and bottom friction. Wave breaking and runup were initially implemented in the manner of Chen et al. (2000). Robustness of the runup model was improved by making modifications similar to the implementation used in Nwogu & Demirbilek, (2001), where the beach is treated as a porous medium, rather than slots. One of the main differences is the introduction of an increased friction/drag coefficient in the porous medium, which serves to stabilize the flow in the porous region. Minor changes in the modeling of wave-breaking involve providing a smooth transition from a non-breaking to a breaking state (i.e. a smooth transition in the eddy viscosity). In addition, the bottom-friction model has been modified as indicated above for the porous regions of the domain. Also sponge layers have been added for wave absorption at the boundaries if needed.

Figure 1 shows results from the Boussinesq model for a roughly 6 x 7 km region around the NCEX site in La Jolla, CA. The surface elevation field is shown for 17 sec monochromatic waves propagating from 295 degrees; the significant wave height is 1 m. The bathymetry used is from the NCEX survey. The depth has been limited to 50 meters, yielding a flat bottom on the Western boundary and part of the Northern boundary, where the wavemaker is located. The most obvious feature is the refraction of the waves caused by the abrupt canyon bathymetry. This causes localized reduction of the wave height at the ends of the canyons and large wave heights at the beach near Scripps pier and Black's beach. Also in evidence are the waves reflected from the canon walls.

The results shown in Figure 1 are presently being used to develop the assimilation procedure. The assimilation procedure makes use of the adjoint to the Boussinesq equations, which are implemented in a numerically similar manner to the forward Boussinesq model. Time series data from the above forward model runs are used to generate simulated data, which is presently being used to develop the in-situ data assimilation procedure.




Figure 1 Surface elevation field for a 6 x 7 km region around the NCEX site in La Jolla, CA Monochromatic waves with a period of 17 sec and a significant wave height of 1 m from 295°T are generated at the offshore boundaries. Bathymetry contours show the near-shore canyons.

IMPACT/APPLICATIONS

The potential applications of the methodology range from determining in a timely manner the conditions on a denied beach, to providing an ongoing, synoptic view of a field experiment in progress, as well as providing a tool for interrogating the near-shore hydrodynamics on beaches with high spatial variability. The results of the proposed program will provide the capability of monitoring near-shore waves and currents over large scales with greater accuracy, and allow the timely use of information from in-situ sensors.

RELATED PROJECTS

This project is part of the ONR Nearshore Canyon Experiment.

REFERENCES

- Chen, Q., Kirby, J. T., Dalrymple, R. A., Kennedy, A. & Chawla, A. 2000 Boussinesq modeling of wave transformation, breaking, and runup. II. 2D. *J. Waterway, Port, Coast., and Ocean Eng.* **126**, 48–56.
- Wei, G., Kirby, J. T., Grilli, S. T. & Subramanya, R. 1996 A fully nonlinear Boussinesq model for surface waves. Part 1. Highly nonlinear unsteady waves. *J. Fluid Mech.* **294**, 71–92.
- Nwogu, O. G., and Demirbilek, Z. 2001 *BOUSS-2D: A Boussinesq wave model for coastal regions and harbor*. ERDC/CHL TR-01-25, U.S. Army Engineer Research and Development Center, Vicksburg, MS.