


THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

Reproduced by



CENTRAL AIR DOCUMENTS OFFICE

WRIGHT-PATTERSON AIR FORCE BASE - DAYTON OHIO

EL-

619

A.T.I

22224

NOTICE: When Government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the U.S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto."

UNCLASSIFIED

ATI 122 224

UNCLASSIFIED

(COPIES OBTAINABLE FROM CADO)

MC DONNELL AIRCRAFT CORP., ST. LOUIS, MO. (REPORT 2323)
RAM JET HELICOPTER DEVELOPMENT - PROGRESS REPORT 60 - MONTH
OF AUG 1951 - MODEL XH-20

WOOD, C.R. JR. 15 SEPT 51 24PP GRAPHS

USAF CONTR. NO. AF 33(038)-9845

HELICOPTERS, JET
ENGINES, RAMJET
HELICOPTER ROTORS, JET
XH-20

ROTATING WING AIRCRAFT (34)
DESIGN (10)

UNCLASSIFIED

REPORT NO. 2323

15 SEPTEMBER 1951

PROGRESS REPORT NO. 60

RAM JET HELICOPTER DEVELOPMENT

CONTRACT AF 33(038)-9345

Serial No. 3

Enclosure (1)
Ref: 2143-301-2073

EXTRA COPY

Official File Copy in P. R. 582-164

REPORT 2323

DATE 15 September 1951

REVISED

PROPELLER LABORATORY

MCDONNELL Aircraft Corporation

ST. LOUIS 3, MISSOURI

PROGRESS REPORT 60

MONTH OF AUGUST 1951

RAM JET HELICOPTER DEVELOPMENT

SUBMITTED UNDER Contract AF 33 (038)-9445

PREPARED BY *C. R. Wood, Jr.*
C. R. Wood, Jr.

APPROVED BY *R. R. Osborn*
R. R. Osborn

APPROVED BY *A. C. Ballauer*
A. C. Ballauer

APPROVED BY *C. E. Burkamp*
C. E. Burkamp

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE

REPORT 2323

REVISED _____

MODEL XH-20

REVISED _____

CONTENTS

	<u>Page</u>
1. SUMMARY	2
2. ROTOR DEVELOPMENT	3
2.1 No. 1, 27-Foot Diameter Rotor	3-6
2.2 No. 2, 27-Foot Diameter Rotor	6
3. RAM JETS	7
3.1 Modified Radial Finger-Type Ram Jet	7
3.2 Fabrication of 3.71-Inch Diameter Ram Jet	7-8
3.3	8
3.4 Modified Whirl Stand	8
4. XH-20, USAF NOS. 46-690 and 46-689	9
4.1 Modified XH-20, No. 2, USAF 46-690	9
4.1.1	9
4.1.2 Group Weight Statement	10
4.1.3 Flight Test Instrumentation	11
4.2 XH-20, No. 1, USAF 46-689	12
4.3 Preliminary Evaluation of Instrumentation 27-Foot Diameter Rotor, XH-20, No. 2	12-13
5. DAILY FLIGHT SHEETS	14-18
6. WORK PROGRAM FOR THE MONTH OF SEPTEMBER	19
7. FIGURES (1) THROUGH (5)	20-24

DATE 15 September 1951

McDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 3

REVISED _____

REPORT 2323

REVISED _____

MODEL XH-20

1. SUMMARY

The calibration data of the No. 1, 27-foot diameter rotor were recalculated and revised data are submitted herewith. Tests for accumulation of the data necessary to substantiate the design for the No. 2, 27-foot diameter rotor are next on the schedule. Larger ram jets are being developed for increased thrust. The actual weight and balance of the No. 2, XH-20 are submitted herewith. Preliminary ground evaluation of the instrumented 27-foot rotor installed on XH-20 No. 2, were completed and rotor assembly modifications are in work.

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 3

REVISED

REPORT 2323

REVISED

MODEL XB-20

2. ROTOR DEVELOPMENT

2.1 No. 1, 27-Foot Diameter Rotor

The rotor was utilized for improvement of the ram jet thrust on the whirl stand prior to installation on the XB-20, No. 2. Preliminary ground tests of the instrumented 27-foot diameter rotor were completed on 31 August. Tests for the measurement of rotor blade stresses, etc., are next on the schedule.

Preliminary plans have been made for the repair of the adhesive failures reported in Progress Report No. 58, for June 1951. It is proposed to replace panels of the blade covering, utilizing Epon VI adhesive which sets at relatively low curing temperatures.

The rotor calibration data submitted in the July Progress Report have been restudied and recalculated to consider the effective blade angles, the recalibration of the torque measuring system and standard atmospheric conditions. Figures (3), (4), (5), (6), (7) and (8) of Progress Report No. 59, are superseded by Figures (1), (2), (3), (4) and (5) of this Progress Report. A review of the rotor calibration tests follows: original tests were run on 16 July, and a portion of the rotor calibration was rerun on 20 July. When reviewing the

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURIPAGE 6
REPORT 2323
MODEL YH-20

REVISED

REVISED

2.1 continued

MAC Report No. 1136, and the values of T/F as derived from the NACA TN 2277 (with the necessary corrections) resulted in an increase in the T/F for the latter of approximately 2½%. The dotted lines in Figure (5) of this Progress Report represent the results of the rotor calibration test and are re-plotted from Figure (1) to show that excellent agreement exists between the MAC rotor calibration tests and the theory as based on the modified NACA test data.

2.2 No. 2, 27-Foot Diameter Rotor

As soon as the qualitative performance tests of the No. 1, 27-foot diameter rotor are obtained, they will be submitted with proposed design changes for the No. 2, 27-foot rotor, details of which were delivered in July. Studies have been made to investigate the suitability of twisting the .0095 aluminum blade covering in accordance with the drawing then submitted. The fabrication of a test sample of the 27-foot rotor, in accordance with the design submitted, resulted in wrinkles in the blade covering. The causes of the wrinkles are being determined so that the design may be modified prior to fabrication of the second 27-foot rotor.

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 7

REVISED _____

REPORT 2323

REVISED _____

MODEL XH-20

3. RAM JETS

3.1 Modified Radial Finger-Type Ram Jet

Ram Jets Nos. 32 and 33 will be modernized prior to reinstallation on the XH-20, No. 2, for further evaluation of the 27-foot diameter rotor. The modernization will include the installation of a new type fuel system and a modification of the flame holder.

3.2 Fabrication of 8.71-Inch Diameter Ram Jet

A larger cross sectional area ram jet has been designed to produce the increased thrust required for higher gross weights with the 27-foot diameter rotor. Four (4) test ram jets of 8.71-inch diameter are being fabricated for test and evaluation. The first unit has been completed and tested in the free air jet test stand in order to obtain smooth and non-destructive burning. The original tests of the 8.71-inch diameter ram jet were made with the exit diameter reduced from 5.7" to 5.4". This reduction in exit diameter resulted in the same inlet area to exit area ratio as that of an 18" long, 7.25" maximum diameter ram jet which had consistently developed high thrust and satisfactory tsfc at 800 fps in the free air jet. With the reduced exit diameter, the new 8.71" ram jet developed 59.5 lb. of thrust at tsfc of 10.

DATE 15 September 1951

McDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 9

REVISED

REPORT 2323

REVISED

MODEL XH-20

3.2 continued

The exit diameter is to be increased to the designed diameter of 5.7", and the inlet diameter is to be increased proportionately to retain the same inlet-exit area ratios, but to investigate the possibility of increased thrust. The 8.7" diameter ram jet will have the flame holder installation modified to reduce ram jet shell cracking.

3.3 A thorough investigation is being made of available ignition wire insulation materials, in an effort to increase the durability of ram jet insulators.

3.4 Modified Whirl Stand

The MAC sponsored installation of a R-985, 450 hp engine, in the whirl stand is 85% complete. The whirl stand is scheduled to be ready for initial operation with the supplementary horse power on or about 1 October 1951. This additional power will permit the calibration of the 27-foot diameter rotor throughout the normal operating range of collective pitch and rotor RPM. A single blade club rotor has been designed, and construction is scheduled to start about 1 October. This club rotor will permit the calibration of individual ram jets on the whirl test stand.

DATE 15 September 1951

McDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 9

REVISED

REPORT 2323

REVISED

MODEL XH-20

4. XH-20, USAF NOS. 46-690 and 46-699

4.1 Modified XH-20, No. 2, USAF 46-690

4.1.1 The actual weight and balance of the XH-20,
No. 2, as weighed on 17 August 1951 is as follows:

	Weight lbs.	C.G. Fwd or Aft of Rotor Q ₁
Helicopter As Weighed	643.2	0.1 aft
Deduct Flight Test Instrumentation	<u>-121.2</u>	
Weight Empty	522.0	5.0 aft
Useful Load	341.0	
Pilot 185.		
Fuel (26 gals) 156.		
Gross Weight (Normal)	863.0	1.9 aft
Gross Weight (Including Flight Test Instrumentation)	984.2	0.9 fwd

The helicopter has been placarded requiring the battery to
be installed for all flights with skid gear and extended
tail boom.

DATE 15 September 1951

McDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 10

REVISED _____

REPORT 2323

REVISED _____

MODEL XH-20

4.1.2 Group Weight Statement

ROTOR GROUP 224.8 lbs.

Blades 96.1 lbs.
Blade Retention 63.7 "
Hubs 65.0 "

TAIL GROUP (VERTICAL FIN) 12.8 lbs.

BODY GROUP 51.9 lbs.

Forward Section 44.6 lbs.
Tail Section 7.3 "

ALIGHTING GEAR (SKIDS) 109.4 lbs.

POWER PLANT GROUP 69.7 lbs.

Engines 31.7 lbs.
Starting System 5.0 "
Fuel System 33.0 "

FIXED EQUIPMENT 44.0 lbs.

Instruments 8.0 lbs.
Flight Controls 15.0 "
Electrical 6.0 "
Furnishings 15.0 "

ACTUAL WEIGHT ADJUSTMENT 9.4 lbs.

WEIGHT EMPTY 522.0 lbs.

USEFUL LOAD 341.0 lbs.

NORMAL GROSS WEIGHT 863.0 lbs.

DATE 15 September 1951

McDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 11

REVISED

REPORT 2323

REVISED

MODEL KH-20

4.1.3 Flight Test Instrumentation

The following flight test instrumentation has been installed:

Fuel Flow Meter Installation	10.6 lbs.
Cerro Bend in Control Stick	8.7 "
Battery Shelf	4.7 "
24-Volt Battery	56.0 "
6-Volt Batteries (3 Required)	8.1 "
Oscillograph	11.0 "
Oscillograph Shelf	2.0 "
Bridge Balance Box	.5 "
Control Stick Holder	5.3 "
Rotor Balance Plates	11.3 "
Misc. Test Wiring, Plugs and Gages	3.0 "
Total Instrumentation Weight	121.2 lbs.

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 12

REVISED _____

REPORT 2323

REVISED _____

MODEL XH-20

4.2 XH-20, NO. 1, USAF 46-689

The re-building of the XH-20, No. 1, was started in August upon receipt of authority from WADC. The ram jet helicopter is scheduled for completion by 19 September, to be ready for pick-up by WADC aircraft on 20 September. After display by the Propeller Laboratory to Ordnance personnel visitors, it will be returned to MAC.

4.3 Preliminary Evaluation of Instrumentation 27-Foot Diameter Rotor, XH-20, No. 2

Flight tests conducted in July confirmed higher control forces and reduced control response of the 27-foot rotor from those obtained with the 20-foot diameter rotor. As reported in Progress Report No. 59 for July 1951, the XH-20, No. 2, has been instrumented for the measurement of stick forces and stick position and blade see-saw motions. After tracking the rotor blades and adjusting the ram jets for increased thrust, instrument ground tests were conducted on 31 August. An evaluation of the qualitative and quantitative data obtained is under-way to determine the additional tests necessary.

DATE 25 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 15

REVISED _____

REPORT 2323

REVISED _____

MODEL XH-20

Test Nos: 134 and 135 Pilot: C. R. Wood, Jr.
Dates: 19 and 20 August 1951 Helicopter: No. 2.
Rotor: 27-Foot Diameter 12-Inch Chord Blade Powered By Modified
Ram Jets Nos. 32 and 33
Purpose: To Track Blades and Adjust Ram Jets for Increased Thrust
Remarks: The helicopter was tied down to track the blades and to
adjust the thrust of the ram jets to produce the increased
thrust indicated during Test No. 133.

Flight Time: 00:00

Running Time: 00:14

Total Flight Time to Date: 32:06*

Total Running Time to Date: 126.50*

*Total for XH-20, Nos. 1 and 2

DATE 15 September 1951**MCDONNELL** *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

REVISED _____

REVISED _____

PAGE 16REPORT 2323MODEL XH-20

Test No.: 136 Pilot: C. R. Wood, Jr.
Date: 24 August 1951 Helicopter: No. 2.

Rotor: 27-Foot Diameter 12-Inch Chord Blade Powered By Modified
Ram Jets Nos. 32 and 33

Purpose: To Evaluate Controllability of Rotor Assembly

Remarks: Oscillograph traces data were obtained at 500 to 580 RPM
at 2°, 3° and 4° indicated pitch[#] while displacing the
cyclic stick longitudinally approximately full travel at
higher than normal rate of control displacement. The
rotor was rough, required tracking, and the data were
unusable.

Flight Time: 00:00

Running Time: 00:18

Total Flight Time to Date: 32:06*

Total Running Time to Date: 127:08*

*Total for XH-20, Nos. 1 and 2

The indicated pitch is to be checked.

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 17

REVISED _____

REPORT 2323

REVISED _____

MODEL XH-20

Test No.: 137 Pilot: C. R. Wood, Jr.
Date: 25 August 1951 Helicopter: No. 2.

Rotor: 27-Foot Diameter 12-Inch Chord Blade Powered By Modified
Ram Jets Nos. 32 and 33

Purpose: To Evaluate Controllability of Rotor Assembly

Remarks: The ram jets lighted satisfactorily at low speed but did not develop normal thrust for rotor acceleration. The instrumentation was inoperative because of moisture in the thermocouples. The test was terminated for the strain gauges to dry.

Flight Time: 00:00

Running Time: 00:08

Total Flight Time to Date: 32:06*

Total Running Time to Date: 127:16*

* Total for XH-20, Nos. 1 and 2

DATE 15 September 1951

MCDONNELL Aircraft Corporation

PAGE 18

REVISED

ST. LOUIS 3, MISSOURI

REPORT 2523

REVISED

MODEL XH-20

Test No.: 138 Pilot: C. R. Wood, Jr.
Date: 31 August 1951 Helicopter: No. 2.
Rotor: 27-Foot Diameter 12-Inch Chord Blade Powered By Modified
Ram Jets Nos. 32 and 33
Purpose: To Measure Control Force and Position and Rotor Blade Data
Remarks: The XH-20 was tied down for these tests. Ram jet operation
was satisfactory for the recording of oscillograph data
under the following conditions:

RPM	FUEL FLOW (LBS/HR)	ACTUAL PITCH
560	760	2 3/4°
600	760	3°
560	780	3°
540	720	2°
560	740	2°
560	680	1 1/2°
560	700	1 1/2°

Preliminary qualitative control force and position and
blade flapping data were obtained at 3 rates of longitudinal
control displacement; slow, medium and fast control forces.

Flight Time: 00:00

Running Time: 00:42

Total Flight Time to Date: 32:06*

Total Running Time to Date: 127:58*

* Total for XH-20, Nos. 1 and 2

DATE 15 September 1951

MCDONNELL *Aircraft Corporation*
ST. LOUIS 3, MISSOURI

PAGE 19

REVISED _____

REPORT 2323

REVISED _____


MODEL XH-20

6. WORK PROGRAM FOR THE MONTH OF SEPTEMBER

6.1 Modified XH-20, No. 2

Further evaluation of the 27-foot diameter rotor will be conducted upon repair and modification of Ram Jets Nos. 32 and 33.

FIGURE



CRC 9/18/51





FIGURE 3

Page 22
Report 2323
Model 25-20

THrust RES. vs EFFECTIVE ANGLE
27 FT. REAR COLD DRAG TEST
RAM JETS 32 & 33 OPEN
STANDARD AIR
TARGE CALIBRATION 7/17/51
TEST DATE 7/18/51
R. A. 1731

EXTRAPOLATED



200-11 RET. FEEL & KUBER CO
10 X 10 to the 1/2 inch, both lines centered.
MADE IN U.S.A.


CRC 8/30/51
TEN

FIGURE 4

C_D Vs. θ_e
COLD DRAG TEST
27 ROTOR
RAM JETS 32 & 33
OPEN & FLOW CONES

NOTE:

TORQUE CALIBRATION
OF 7/17/51 & FAIRED TIP
RUN OF 7/20/51 USED



CRC 9/26/51

FIGURE 57

