

UNCLASSIFIED

AD NUMBER	
ATI070337	
CLASSIFICATION CHANGES	
TO:	unclassified
FROM:	confidential
LIMITATION CHANGES	
TO: Approved for public release; distribution is unlimited. Document is partially illegible.	
FROM: Distribution authorized to DoD only; Administrative/Operational Use; Aug 1949. Other requests shall be referred to Naval Proving Ground, Dahlgren, VA.	
AUTHORITY	
Naval Surface Weapons Center notice dtd 4 Jun 1975	

THIS PAGE IS UNCLASSIFIED

UNCLASSIFIED

AD NUMBER
ATI070337
CLASSIFICATION CHANGES
TO
confidential
FROM
restricted
AUTHORITY
Naval Proving Ground ltr dtd 30 Dec 1953

THIS PAGE IS UNCLASSIFIED

Reproduction Quality Notice

This document is part of the Air Technical Index [ATI] collection. The ATI collection is over 50 years old and was imaged from roll film. The collection has deteriorated over time and is in poor condition. DTIC has reproduced the best available paper copy utilizing the most current imaging technology. ATI documents that are partially legible have been included in the DTIC collection due to their historical value.

If you are dissatisfied with this document, please feel free to contact our Directorate of User Services at [703] 767-9066/9068 or DSN 427-9066/9068.

**Do Not Return This Document
To DTIC**

U. S. NAVAL PROVING GROUND
DANLREN, VIRGINIA

REPORT NO. 355

MINE AND MINE COMPONENT TESTING
UNDER
TASK ASSIGNMENT NPG-33-Re6b-311-1

7th Partial Report

AIRCRAFT DROPS OF REEFED PARACHUTES,
4K. 2 MOD. 3, ASSEMBLED ON MINES, MK. 36.
TO DETERMINE TERMINAL VELOCITY AND
FLIGHT CHARACTERISTICS

FINAL Report

Copy no. _____

Task

Assignment NPG-33-Re6b-311-1

Classification

RESTRICTED

NPG REPORT NO. 355

RESTRICTED

U. S. NAVAL PROVING GROUND
DAHLGREN, VIRGINIA

Seventh Partial Report
on
Mine and Mine Component Testing
under
Task Assignment NPG-33-Re6b-311-1

Final Report
on
Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

Project No.: NPG-33-Re6b-311-1
No. of Pages: 7

Date: 23 AUG 1949

RESTRICTED

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

PART ASYNOPSIS

1. This is a report on aircraft drops of Mines, Mk. 36, assembled with Reefed Parachutes, Mk. 2 Mod. 3, conducted under Task Assignment No. NPG-33-Rc6b-311-1.

2. This test was conducted to determine the flight characteristics and terminal velocities of Mines, Mk. 36, assembled with Parachutes, Mk. 2 Mod. 3, which contained reef lines to control the diameter of the mouth of each parachute.

3. It is concluded that:

a. The flight characteristics of each mine were satisfactory.

b. The terminal velocity for each mine drop was as follows:

<u>Drop No.</u>	<u>Diameter of Mouth of Chute (Feet)</u>	<u>Terminal Velocity (Feet Per Second)</u>
1	6 (Not Reefed)	164
2	5	173
3	4	202
4	3-1/2	211
5	3	218
6	2-1/2	241
7	2	256
8	1-1/2	298

The estimated probable errors of the terminal velocities are plus or minus five feet per second.

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

TABLE OF CONTENTS

	<u>PAGE</u>
SYNOPSIS	1
TABLE OF CONTENTS	2
AUTHORITY	3
REFERENCES	3
BACKGROUND	3
OBJECT OF TEST	3
PERIOD OF TEST	3
REPRESENTATIVES PRESENT.	3
DESCRIPTION OF ITEM UNDER TEST	4
DESCRIPTION OF TEST EQUIPMENT.	4
PROCEDURE	5
RESULTS AND DISCUSSION	5
CONCLUSIONS	6
DISPOSITION OF MATERIAL	6
APPENDIX A - NPG PHOTOGRAPHS	FIGURES 1 & 2
APPENDIX B - NPG MOVIE NO. 808 (ORIGINAL ONLY, DELIVERED BY HAND TO NOL FIELD EVALUATION DIVISION)	
APPENDIX C - TABULATED TEST DATA	TABLE I
APPENDIX D - DISTRIBUTION	1-2 (Incl.)

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

PART B

INTRODUCTION

1. AUTHORITY:

This test was directed by reference (a) under Task Assignment No. NPG-34-Re6b-311-1 authorized by reference (c). Reference (a) requested that the test be conducted in accordance with the outline in reference (b).

2. REFERENCES:

- a. NOL restr. speedltr NP51/F43-1(1-259) dated 11 April 1949.
- b. NOL TSS No. 5528.
- c. BuOrd Conf. ltr. NP9(Re6b) dated 3 September 1948.
- d. NPG restr. report No. 337 dated 1 August 1949.

3. BACKGROUND:

This test is part of a program to design a parachute capable of withstanding opening shock at high launching speeds.

4. OBJECT OF TEST:

This test was conducted to determine the terminal velocity and flight characteristics of Reefed Parachutes, Mk. 2 Mod. 3, assembled on Mines, Mk. 36.

5. PERIOD OF TEST:

- | | |
|-------------------------------------|---------------|
| a. Date of Project Letter | 11 April 1949 |
| b. Date Necessary Material Received | 27 April 1949 |
| c. Date Commenced Test | 28 April 1949 |
| d. Test Completed | 29 April 1949 |

6. REPRESENTATIVES PRESENT:

G. L. Fogal	Naval Ordnance Laboratory
L. C. Ripley	" " "
J. I. Kistle	" " "

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

PART C

DETAILS OF TEST

7. DESCRIPTION OF ITEM UNDER TEST:

a. Seven standard Parachutes, Mk. 2 Mod. 3, which have a diameter of 6 feet, were modified by choking the diameters at the hemline to 5 feet, 4 feet, 3-1/2 feet, 3 feet, 2-1/2 feet, 2 feet and 1-1/2 feet, respectively. One standard Parachute, Mk. 2 Mod. 3, was not modified by reefing. Figure 1 shows the method of reefing. In this particular case the diameter is three feet.

b. The parachutes were housed in Parachute Pack, Mk. 9 Mod. 0, modified as described in reference (d). This is shown in Figure 2.

c. Parachute packs were assembled on plaster loaded Mine Cases, Mk. 36, by means of attaching bands constructed according to NOL Sketch 95315.

8. DESCRIPTION OF TEST EQUIPMENT:

a. The following types of aircraft were used in this test:

(1) Mines were launched from a TBM-3E.

(2) Aerial photographs were taken with a hand-held Cine-Flex camera from an SNJ-4.

b. Ground instrumentation consisted of three Mitchell high speed cameras. Two Mitchell cameras with 4 inch lenses were focused on the target to record data necessary to compute terminal velocities. One Mitchell camera with 17 inch lens was used to photograph release, trajectory, and impact of each mine. This film and the film from the Cine-Flex camera is included as Appendix (B).

RESTRICTED

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

9. PROCEDURE:

a. Eight Mines, Mk. 36, with the test parachutes attached were launched separately from a TBM-3E type aircraft using horizontal bombing technique from true altitudes of 5000 feet and at airspeeds of 120 knots, indicated.

b. Aerial photographs were taken from an SNJ-4 type aircraft which flew approximately 200 feet below and 400 feet to one side of the launching aircraft. Upon release of the mine, the photographic plane descended in a sharp bank to photograph the entire flight of the mine. Film from the stationary Mitchell cameras was evaluated for terminal velocity data. The film from the Mitchell with 17 inch lens and the Cine-Flex camera was used to determine flight characteristics of each drop.

10. RESULTS AND DISCUSSION:

a. The operation of the parachutes and packs was satisfactory for all drops. The reef lines held the parachutes in a balloon shape which filled properly and remained inflated throughout flight. The flight of each mine was relatively smooth with no excessive yawing or oscillation.

b. The terminal velocities of the reefed parachutes assembled on Mines, Mk. 36, were determined to be as follows:

<u>Drop No.</u>	<u>Diameter of Mouth of Chute (Feet)</u>	<u>Terminal Velocity (Feet Per Second)</u>
1	6 (Not reefed)	164
2	5	173
3	4	202
4	3-1/2	211
5	3	218
6	2-1/2	241
7	2	256
8	1-1/2	298

c. Detailed data are tabulated in Appendix (C).

RESTRICTED

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

PART DCONCLUSIONS

11. It was concluded that:

a. The flight characteristics of each mine were satisfactory.

b. The terminal velocity for each mine drop is as follows:

<u>Drop No.</u>	<u>Diameter of Mouth of Chute (Feet)</u>	<u>Terminal Velocity (Feet Per Second)</u>
1	6 (Not Reefed)	164
2	5	173
3	4	202
4	3-1/2	211
5	3	218
6	2-1/2	241
7	2	256
8	1-1/2	298

The estimated probable errors of the terminal velocities are plus or minus five feet per second.

PART EDISPOSITION OF MATERIAL

.. 12. The eight mines dropped were recovered and the parachutes were returned to the Naval Ordnance Laboratory representatives.

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

PREPARED BY: E. B. Hall
E. B. HALL
Project Engineer

SUBMITTED: R. L. Klassy
R. L. KLASSY
Lieutenant, USN
Assistant Special
Project Officer

CONCUR: M. P. Bagdanovich
M. P. BAGDANOVICH
Captain, USN
Aviation Ordnance Officer

CONCUR: W. C. Bryson
W. C. BRYSON
Captain, USN
Experimental Officer

APPROVED:

C. H. Anderson
C. H. ANDERSON
Captain, USN
Commander, Naval Proving Ground,
Acting.

NP9 38657 - Parachute, Mk. 2 Mod. 3, reefed to a diameter of 3 feet.

3 May 1949

RESTRICTED



Figure 1

A

NP9 38269 - Reefed parachute, housed in Parachute Pack, Mk. 9 Mod. 0
(Modified), assembled on Mine, Mk. 36.
28 April 1949

RESTRICTED



Figure 2

NPG REPORT NO. 355

RESTRICTED

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics
- - - - -

NPG MOVIE NO. 808

(ORIGINAL ONLY, DELIVERED
BY HAND TO THE NAVAL ORDNANCE
LABORATORY, FIELD EVALUATION
DIVISION)

RESTRICTED
APPENDIX B

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Vines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

RESTRICTEDTABLE ITABULATED TEST DATA

Tests of Reefed Parachutes, Mk. 2 Mod. 3 assembled on Vines, Mk. 36.

Date	Plane Type	Weight of Unit	Airspeed at Release (Knots, Ind.)	Altitude at Release (feet true)	Diameter of Chute (Feet)	Vertical Component of Striking Vel. (f/s)	Ballistic* Coefficient	Terminal* Velocity	Remarks
4/28/49	TBM-3E	1056	120	5000	6	163	.0415	164	Chute not reefed. Slight oscillation. Good flight.
"	"	1080	"	"	5	173	.0460	173	Oscillated during descent. Satisfactory flight.
"	"	1063	"	"	4	202	.0620	202	Oscillated slightly. Satisfactory flight.
"	"	1076	"	"	3.5	210	.0665	211	Satisfactory flight.
"	"	1067	"	"	3	219	.0715	218	Satisfactory flight.
4/29/49	"	1079	"	"	2.5	239	.0860	241	Satisfactory flight.
"	"	1051	"	"	2	254	.0965	256	Slight oscillation. Good flight.
"	"	1066	"	"	1.5	292	.128	298	Satisfactory flight.

* Values adjusted to standard air density.

RESTRICTED
APPENDIX C

RESTRICTED

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

DISTRIBUTION

Bureau of Ordnance:

Ad3	2 (w/o Appendix (B))
Re6	1 (w/o Appendix (B))
Re6b	1 (w/o Appendix (B))
Chief of Ordnance, Department of the Army	2 (w/o Appendix (B))
Commanding General Aberdeen Proving Ground Aberdeen, Maryland Attn: Technical Information Section Development & Proof Services	1 (w/o Appendix (B))
Naval Gun Factory Attn: Aircraft Armament Section	1 (w/o Appendix (B))
Naval Ordnance Laboratory Attn: Technical Evaluation Dept. Field Evaluation Division	1 (w/o Appendix (B)) 1 (with Appendix (B))
Bureau of Aeronautics Attn: Armament Section	2 (w/o Appendix (B))
NATC, Patuxent River, Md.	3 (w/o Appendix (B))
NAOTS, Chincoteague, Va.	1 (w/o Appendix (B))
Air Material Command Liaison Officer Wing 3 Headquarters, Aberdeen Proving Ground, Aberdeen, Maryland	2 (w/o Appendix (B))
Naval Air Development Station, Johnsville, Pa.	1 (w/o Appendix (B))
Naval Liaison Officer USAFPGC, Eglin Field, Fla.	1 (w/o Appendix (B))

RESTRICTED
APPENDIX D

Aircraft Drops of Reefed Parachutes,
Mk. 2 Mod. 3, Assembled on Mines, Mk. 36,
To Determine Terminal Velocity and Flight Characteristics

DISTRIBUTION (Cont'd)

U. S. Air Force
AIC Engineering Field Office
Room 1833, Main Navy Building,
Navy Department,
Washington 25, D. C.

2 (w/o Appendix (D))

Local:

RX
RO
KB
File

1 (w/o Appendix (D))
1 (w/o Appendix (B))
1 (w/o Appendix (B))
1 (w/o Appendix (B))

Reproduced by



CENTRAL AIR DOCUMENTS OFFICE

WRIGHT-PATTERSON AIR FORCE BASE - DAYTON, OHIO

REEL-C

3305

B

A.T.I

70337

The
U.S. GOVERNMENT

IS ABSOLVED

FROM ANY LITIGATION WHICH MAY ENSUE FROM ANY
INFRINGEMENT ON DOMESTIC OR FOREIGN PATENT RIGHTS
WHICH MAY BE INVOLVED.

CLASSIFIED

UNCLASSIFIED

UNCLASSIFIED

✓
ATL- 70 337 *

U.S. Naval Proving Ground, Dahlgren, Va. (355)
SEVENTH PARTIAL REPORT ON MINE AND MINE
COMPONENTS TESTING UNDER TASK ASSIGN-
MENT NPG-33-RE6B-311-1 - FINAL REPORT ON
AIRCRAFT DROPS OF REEFED PARACHUTES,
MK.2 MOD. 3, ASSEMBLED ON MINES, MK.36, TO
DETERMINE TERMINAL VELOCITY AND FLIGHT
CHARACTERISTICS - AND APPENDIXES A-D
(NPG REPORT), by E.B. Hall, Aug '49, 7 pp.
incl. photos, tables.

(Not abstracted)

DIVISION: Ordnance and Armament (22)
SECTION: Torpedoes and Mines (9)
DIVISION: Flight Safety (15)
SECTION: Bail-Out (4)

DISTRIBUTION: Copies obtainable from ATTRA-DSC.

I. Mines, Parachute
I. Hall, E.B.

(OVER)

SECURITY INFORMATION

When this card has served its purpose, it may
be destroyed in accordance with AFR 205-1, Army
Reg. 380-5 or OPNAV Inst. 351-1.

ARMY - ~~SECURITY~~ TECHNICAL INFORMATION AGENCY

~~ARMY - ~~SECURITY~~ TECHNICAL INFORMATION AGENCY~~
~~DOCUMENT SERVICE CENTER~~

NTIS, Auths, *as NSWC notation, 4 Jan 75*

U *Auth: NSNSWC notice, 4 Jan 75*

Classification cancelled

or changed to

AUTH

By

Signature and Grade

Date

*Presidential
for the U.S. National Training Co.
J. Edgar Hoover
3752
J. Edgar Hoover
Jan 21, 1975*