

UNCLASSIFIED

AD NUMBER
ADA800691
CLASSIFICATION CHANGES
TO: unclassified
FROM: secret
LIMITATION CHANGES
TO: Approved for public release; distribution is unlimited.
FROM: Distribution authorized to DoD only; Foreign Government Information; 27 MAR 1945. Other requests shall be referred to British Embassy, 3100 Massachusetts Avenue, NW, Washington, DC 20008.
AUTHORITY
DSTL, AVIA 21/39, 15 Oct 2009; DSTL, AVIA 21/39, 15 Oct 2009

THIS PAGE IS UNCLASSIFIED


Reproduction Quality Notice

This document is part of the Air Technical Index [ATI] collection. The ATI collection is over 50 years old and was imaged from roll film. The collection has deteriorated over time and is in poor condition. DTIC has reproduced the best available copy utilizing the most current imaging technology. ATI documents that are partially legible have been included in the DTIC collection due to their historical value.

If you are dissatisfied with this document, please feel free to contact our Directorate of User Services at [703] 767-9066/9068 or DSN 427-9066/9068.

**Do Not Return This Document
To DTIC**

Reproduced by
AIR DOCUMENTS DIVISION



HEADQUARTERS AIR MATERIEL COMMAND

WRIGHT FIELD, DAYTON, OHIO

Produced by

The
U.S. GOVERNMENT

IS ABSOLVED

FROM ANY LITIGATION WHICH MAY
ENSUE FROM THE CONTRACTORS IN -
FRINGING ON THE FOREIGN PATENT
RIGHTS WHICH MAY BE INVOLVED.

REEL - C

214

ATTN

Secret

REEL - C

2 1 4

A.T.I.

7 1 4 8

SECRET

CONFIDENTIAL

Copy No. 134 *dup*

Report No. A.F.E.E./G.41

Date of issue. 27 MAR 1945

ATI No. **7148**

MINISTRY OF AIRCRAFT PRODUCTION

AIRBORNE FORCES EXPERIMENTAL ESTABLISHMENT
BEAULIEU, NEAR BROCKENHURST, HANTS.

M.A.P. Ref: SB.46196/RD.Airb.
A.F.E.E. Ref: S.2503/1/Tech
Date of tests: September - November 1944
Item No: A.1/3

AIR DOCUMENTS DIVISION, T-2
AMC, WRIGHT FIELD
MICROFILM No.

RC-214 F 7148

Horsa II glider
Brief performance and handling tests

by
W. E. Bartram, M.Sc.

SUMMARY

E/A.F.E.E./G.41

Tests have been made on the Horsa II at a weight of 15,750 lb. These included measurements of position error by means of a trailing static and partial descents measured over a range of speeds with and without flap.

1. Introduction

It was required to measure the performance and position error of the Horsa II glider and to compare its handling qualities with those of the Horsa I.

2. Description of glider

The Horsa II differs from the Horsa I mainly in the following particulars:-

To facilitate loading the nose now opens in a similar manner to that of the Hamilcar, the whole nose portion hinging on the starboard side so that large items of equipment - vehicles etc. - can be loaded straight in up the loading ramps.

The bridle tow of the Horsa I has been changed to chin tow on the Horsa II, the towing point being at the top of the nose wheel shock strut.

The rubber shock struts of the main and nose wheels of the Horsa I have been replaced by oil and spring struts, and tyre pressures have been reduced.

Twin nose wheels have been introduced to reduce shimmy.

The main skid has also been fitted with a spring and oil strut in place of the rubber shock absorber.

3. Loading details

The glider was loaded to an all-up weight of 15,750 lb. for these tests with C.G. at 6.03 ins. aft of datum. The light weight of this aircraft was 8,930 lb. This weight included three double seats, two single seats, loading ramps, air bottle, ladder, control locks, first aid kit and line intercommunication.

SECRET

SECRET

W-32247

4. Measurements of Position Error

Position error was measured by means of a trailing static suspended from the partly open front door, in which position it hung clear of the under-carriage and main skid. The A.S.I. connected to this static was positioned on the instrument panel in the cockpit, side by side with the pilot's A.S.I.

The static head is in the centre of the fuselage above and to the rear of the cockpit. It is a Mk. 7A anti-ice head and dimensions are shown in Fig. 1.

The following measurements of position error were made:-

On tow in high position with zero flap between 140 and 160 m.p.h. A.S.I.
In free flight with half flap (40°) between maximum permissible speed, 110 m.p.h. A.S.I., and stalling speed, 63 m.p.h. A.S.I.
In free flight with zero flap between 80 m.p.h. A.S.I. and 160 m.p.h. A.S.I.
In free flight with full flap (80°) between maximum permissible speed, 110 m.p.h. A.S.I., and stalling speed, 60 m.p.h. A.S.I.

Results of all the above tests are given in Fig. 2.

5. Measurement of stalling speed

With zero flap the glider did not stall even with the trim fully back and stick pulled back slowly as far as possible. The speed dropped to 73 m.p.h. A.S.I. and there was some vibration at about 70 m.p.h. A.S.I.

With 40° flap the glider stalled at 63 m.p.h. A.S.I. There was a tendency for the starboard wing to drop, but this could easily be corrected by the use of opposite rudder. Warning of the onset of the stall was provided by moderate vibration at a speed some 5 m.p.h. above stalling speed.

With 80° flap the glider stalled at 60 m.p.h. A.S.I. in a similar manner to the half flap stall. With full flap there is considerable vibration at all speeds so that there is no actual warning of the onset of the stall.

6. Partial descents

Partial descents were made over a range of speeds from 160 m.p.h. A.S.I. to 80 m.p.h. A.S.I. with zero flap, 110 m.p.h. A.S.I. to 70 m.p.h. A.S.I. with 40° flap and from 100 m.p.h. A.S.I. to 70 m.p.h. A.S.I. with full flap.

The results are given in Figs. 3 and 4 and show that the minimum angles of glide are 4.3° with no flap at an A.S.I. of 95 m.p.h., 7.1° with half flap at an A.S.I. of 78 m.p.h. and 10.7° with full flap at an A.S.I. of 72 m.p.h. On the Horsa I (reference 1) the minimum angle of glide with no flap was 5.0°.

7. Handling in towed flight

The Horsa II is slightly less stable in yaw than the Horsa I and is less unstable laterally. It can be held out of position either by use of rudder alone or aileron alone.

8. Handling in free flight

Half flap and full flap - There was a tendency in the Horsa II undergoing test to drop into a stall at the stall, but control could easily be regained in the normal manner.

RECEIVED

9. Controls

9.1 General

There is slight play in the controls due to the push rod mechanism, this does not adversely affect the handling. The flaps come down considerably quicker than on the Horsa I. There are no dive brakes.

9.2 Brake control

The brake control has been changed. On the Horsa I it was situated on the side of the first pilot's seat; on the Horsa II there are thumb controls on both the first and second pilots' wheels. This is considered an improvement. The lay-out of the central control box is also improved and simplified.

On this aircraft no Mk. III C.A.L. was fitted nor was there T.R.C. Line intercommunication was used between tug and glider.

Except where a difference has been specified, the handling notes for the Horsa I glider (reference 2) are applicable to the Horsa II. It is considered, however, that the Horsa II is slightly more pleasant to fly than the Horsa I.

References

- 1 Performance of Horsa in free flight. Report No. A.F.E./G.36 Part 3.
- 2 Handling tests on Horsa. Report No. A.F.E./G.36 Part 5.

Circulation

C.E.D.	D.O.K.	R.T.P. (T.I.B.)
D.T.D.	D.R.A.E.	(15 copies)
D.D.T.D.	R.A.E. (Aero F)	R.T.P.2(a)
D.D.R.D.T.	D.D.S.R.1	(85 copies)
D.D.R.D.A.	Chief Overseer	
D.D.A.P.	D.D.R.D. Inst.	
A.D.R.D. Airborne	A. & A.E.E. (2 copies)	
(Action copy + 3)		

~~SECRET~~

W-32247






FIG. 2



HORSA II RN 309 WEIGHT 15,750 LB.
POSITION ERROR.


W-32247

FIG. 3



HORSA II RN 309 WEIGHT 15,750 LB.

W-32248



REEL - C

214

A.T.I.

7148

SECRET

TITLE: Horsa II Glider-Brief Performance and Handling Tests.

ATI- 7148

REVISION

(None)

AUTHOR(S) : Bartram, W.E.

ORIG. AGENCY : Airborne Forces Experimental Establishment, Beaulieu, Hants

PUBLISHED BY : (Same)

ORIG. AGENCY NO.

AFEE G.41

PUBLISHING AGENCY NO.

(Same)

DATE	DOC. CLASS.	COUNTRY	LANGUAGE	PAGES	ILLUSTRATIONS
Nov '44	Secret	Gt. Britain	English	7	graphs

ABSTRACT:

Experiments are made to test performance and position error of Horsa II glider and compare handling qualities with Horsa I. Differences between the types are noted. Measurements of position error and stalling speed with various degrees of flaps are given. Handling in towed and free flight is discussed. Brake control has been changed from side of first pilots seat; thumb manual controls are now on both first and co-pilots wheels.

DISTRIBUTION: LIMITED. Copies obtainable from CADO by U.S. Military Organizations only.

DIVISION: Gliders (35)

SECTION: Aerodynamics and Performance (1)

SUBJECT HEADINGS: Gliders - Performance (45795)

ATI SHEET NO.:

Central Air Documents Office
Wright-Patterson Air Force Base, Dayton, Ohio

AIR TECHNICAL INDEX

SECRET

TITLE: Horsa II Glider-Brief Performance and Handling Tests

ATI- 7148

REVISION

(None)

AUTHOR(S) : Bartram, W.E.

ORIG. AGENCY : Airborne Forces Experimental Establishment, Beaulieu, Hants

PUBLISHED BY : (Same)

OEO AGENCY NO

AFEE G.41

PUBLISHING AGENCY NO.

(Same)

DATE	DOC. CLASS.	COUNTRY	LANGUAGE	PAGES	ILLUSTRATIONS
Nov '44	Secret	U.K. Britain	English	7	graphs

ABSTRACT:

Experiments are made to test performance and position error of Horsa II glider and compare handling qualities with Horsa I. Differences between the types are noted. Measurements of position error and stalling speed with various degrees of flaps are given. Handling in towed and free flight is discussed. Brake control has been changed from side of first pilots seat; thumb manual controls are now on both first and co-pilots wheels.

DISTRIBUTION: LIMITED. Copies obtainable from CADO by U.S. Military Organizations only.

DIVISION: Gliders (35) /

SECTION: Aerodynamics and Performance (1) /

SUBJECT HEADINGS: Gliders - Performance (45785)

ATI SHEET NO.:

Central Air Documents Office
Wright-Patterson Air Force Base, Dayton, Ohio

AIR TECHNICAL INDEX



Defence Signal Training Library
(dstl) Defence Signal Training Library
Defence Signal Training Library
Defence Signal Training Library
Defence Signal Training Library
Defence Signal Training Library
Defence Signal Training Library
Defence Signal Training Library

Defense Technical Information Center (DTIC)
8725 John J. Kingman Road, Suit 0944
Fort Belvoir, VA 22060-6218
U.S.A.

AD#: ADA800691

Date of Search: 15 Oct 2009

Record Summary: AVIA 21/39

Title: Horsa II glider: brief performance and handling tests
Availability Open Document, Open Description, Normal Closure before FOI Act: 30 years
Former reference (Department): A.F.E.E/G41
Held by The National Archives, Kew

This document is now available at the National Archives, Kew, Surrey, United Kingdom.

DTIC has checked the National Archives Catalogue website (<http://www.nationalarchives.gov.uk>) and found the document is available and releasable to the public.

Access to UK public records is governed by statute, namely the Public Records Act, 1958, and the Public Records Act, 1967.
The document has been released under the 30 year rule.
(The vast majority of records selected for permanent preservation are made available to the public when they are 30 years old. This is commonly referred to as the 30 year rule and was established by the Public Records Act of 1967).

This document may be treated as UNLIMITED.