


PHOTOGRAPH THIS SHEET

A950391

DTIC ACCESSION NUMBER



LEVEL

Watertown Arsenal Labs., MA



INVENTORY

Rept. No. WAL-TR-130.5/1

DOCUMENT IDENTIFICATION

Oct. '60

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

DISTRIBUTION STATEMENT

ACCESSION FOR

NTIS GRA&I ☒

DTIC TAB ☐

UNANNOUNCED ☐

JUSTIFICATION

(Oct. 1960)

BY

DISTRIBUTION / Per Ltr. on file

AVAILABILITY CODES

DIST

AVAIL AND/OR SPECIAL

A

DISTRIBUTION STAMP

Released

DTIC
ELECTE
S MAY 21 1981 D
D

DATE ACCESSIONED

UNANNOUNCED

81 5 15 198

DATE RECEIVED IN DTIC

PHOTOGRAPH THIS SHEET AND RETURN TO DTIC-DDA-2

#1

WATERTOWN ARSENAL
WATERTOWN, MASS.

WAL TR 130.5/1

PB 150917
AD

AD Sup.
244885



2

A950391

WATERTOWN ARSENAL LABORATORIES

ETCH PITS IN PYROLYTIC GRAPHITE

TECHNICAL REPORT NO. WAL TR 130.5/1

BY

ARAM TARPINIAN

and

GEORGE E. GAZZA

OCTOBER 1960

O. O. PROJECT: TB4-004, MATERIALS FOR HIGH
TEMPERATURE USES

D/A PROJECT: 5893-32-004

WATERTOWN ARSENAL
WATERTOWN 72. MASS.

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

ASTIA AVAILABILITY NOTICE

Qualified requesters may obtain copies of this report from the Armed Services Technical Information Agency, Arlington Hall Station, Arlington 12, Virginia.

This report has been released to the Office of Technical Services, U. S. Department of Commerce, Washington 25, D. C. for sale to the general public. PB 150917

PB 150917
AD

Metallography
Graphite
Dislocations in metals

ETCH PITS IN PYROLYTIC GRAPHITE

TECHNICAL REPORT WAL TR 130.5/1

By

ARAM TARPINIAN
and
GEORGE E. GAZZA

October 1960

O.O. Project: TB4-004, Materials for
High Temperature Uses
D/A Project: 5B93-32-004

WATERTOWN ARSENAL
WATERTOWN 72, MASS.

DISTRIBUTION STATEMENT A

Approved for public release;
Distribution Unlimited

WATERTOWN ARSENAL LABORATORIES

TITLE


ETCH PITS IN PYROLYTIC GRAPHITE

ABSTRACT

The observation of pits in pyrolytic graphite after ion bombardment etching is described and their similarity to dislocation etch pits is speculated. Evidence of etch pit multiplication in the form of slip line segments and low angle tilt boundaries is presented.




ARAM TARPINIAN
Physical Metallurgist



GEORGE E. GAZZA
Physical Metallurgist

APPROVED:



J. F. SULLIVAN
Director
Watertown Arsenal Laboratories

REPORT APPROVED
Date- 26 Oct 60
WAL Board of Review
Chairman- WSW

INTRODUCTION

In contrast to metals, the effect of microstructure on the properties of graphitic materials has not been investigated sufficiently to demonstrate which features are most significant. It has been shown in the case of metals and other crystalline materials that the nature of the substructures plays an extremely important role in determining the physical properties of the material. Various techniques such as "decorating" and etch pitting have been used to reveal these substructures in materials. Transmission electron microscopy of thin sections has also been utilized by observing the interference patterns produced by the transmission of the electron beam through the lattice imperfections.

In the case of graphites, the only attempts to identify the substructures have been by transmission electron microscopy. A number of electron microscope observations have been made^{1,2,3,4} which are reported to be direct evidence of dislocations in graphite. Although there is no reason to believe that graphite is so perfect that it is free of dislocations, the concept of dislocations in graphite is received by many with some skepticism. However, Grenall's work (Reference 3) with the transmission electron microscopy of graphite thin sections showing the movement of dislocation lines induced by the thermal energy provided by the electron beam is quite convincing. The electron microscope work by Dawson and Follett, (Reference 4) showing edge dislocations in the basal plane consisting of two half planes, is also convincing, since one would expect that the atomic arrangement in the hexagonal layer plane would require that two rows of atoms be removed to form the edge dislocation and still maintain the compatibility of the lattice (see Figure 1).

The authors have no knowledge of any published work reporting the use of etch pit techniques and light microscopy for revealing the substructures of graphites. Perhaps the reason for this lack is the fact that until recently there has been little interest in revealing graphite microstructures for metallurgical-type studies. The experience and know-how derived from the study of metal microstructures can be usefully applied to graphite as has already been done in many other nonmetallic and ceramic-type materials. A desire to apply metallographic principles and techniques to graphite prompted our earlier investigations in this area. During the course of these studies, cathodic etching techniques⁵ were found to be quite superior to chemical etching⁶ for both pyrolytic graphites and graphitized cokes.

Pyrolytic graphite is the term used to describe the graphite deposit derived from the high temperature ($> 2000^{\circ}\text{C}$) pyrolysis of organic vapors on hot surfaces. The most common raw material used today is methane gas, although there are numerous other organic compounds that will undergo similar pyrolysis reactions. Graphite layers are built up on a hot substrate by the continuous deposition of carbon resulting from the pyrolysis of the organic vapor. The orientation of the crystallites (grains) is such that the basal (00.2) plane lies more or less parallel to the surface of the substrate. Due to the peculiarities of the growth process, the basal planes are bowed with varying degrees of curvature, giving rise to a conical geometry to the

grain structure when viewed parallel to the (00.2) plane.

Graphitized cokes are those graphites that are produced by the heat treatment ($> 2000^{\circ}\text{C}$) of molded or extruded mixtures of petroleum coke particles and pitch or resin binder. The high temperature heat treatment graphitizes both the binder and the coke filler, resulting in a porous body consisting of fairly randomly oriented graphite crystallites held together by a graphitic pitch or resin bond.

The purpose of this paper is to report some recent work using cathodic etching techniques to reveal the substructures in pyrolytic graphite. Pyrolytic graphite was chosen in lieu of graphitized coke because of its closer approach to single crystal behavior due to the preferred orientation of the grain structure. Etch pit arrays have been observed which we believe may be direct evidence of dislocation sites.

EXPERIMENTAL PROCEDURE

In the case of graphites, chemical etching presents a problem because of the relative inertness of graphite with respect to chemical reaction. The choice of chemical reactions for etching is limited to three types: oxidation, formation of lamellar compounds, and carbide formation at high temperatures. Of the three classes, oxidation seems to be the most feasible for use as a means of etching, since the reaction product is gaseous and does not require removal or solution away from the underlying structure.

In previous work by the authors (Reference 6), a mixture of potassium dichromate - phosphoric acid was found to be the most promising oxidizing etchant for graphite. Subsequent work (Reference 5) showed that cathodic etching (ion bombardment) was much more satisfactory. Consequently, cathodic etching techniques were used in the work reported in this paper.

Pyrolytic graphite specimens were sectioned in a transverse manner so that the basal planes are viewed on edge. The sectioned surface was polished, using standard metallographic polishing techniques, and cathodically etched with argon ions. Details of the construction and operation of the cathodic etching apparatus are given in Reference 5. In general, satisfactory etching was accomplished within a half hour, using a voltage drop from 3000-4500 volts at 5-10 ma/cm². A constant leak of argon at 20 μ of H₂ was maintained during etching so that continuous evacuation of the etching chamber could be accomplished without depletion of the argon supply.

RESULTS AND DISCUSSION

Examination of the etched pyrolytic graphite surfaces using light microscopy revealed conical etch pits in arrays reminiscent of those that have been observed in other materials. Figures 2 through 6 show some of the etch pit arrays that have been observed. All photographs are oriented such that the basal plane runs horizontal across the page.

Figures 2 and 3 show linear arrays of etch pits in the form of slip line segments. Microcracks predominantly along the basal planes are also seen. The interruption of what appears to be slip at a grain boundary is shown in Figure 3. Figure 4 shows the initiation of slip at the tip of microcracks along the basal planes. The occurrence of single pits lining up to form what appears to be low angle tilt boundaries is seen in Figures 5 a and b.

Whether or not mechanical polishing prior to etching is responsible for the observed structures has not been resolved at present. It is more likely that due to the anisotropic behavior of the graphite crystal lattice, thermal expansion in the c and a axes differs to such an extent as to create thermal stresses in the deposited layers (during high-temperature deposition and during cooling after deposition) which are high enough to initiate plastic flow and propagate microcracks.


Nevertheless, the purpose of this paper is only to report an etching technique which has been successful in producing preferential attack in the form of etch pits in the surface of pyrolytic graphite. This technique has previously been used for etching graphitized petroleum cokes (Reference 5). A type of pitting was also observed on these materials and explained on the basis that they may be due to the sublimation of impurities during the high temperature heat treatment of the coke. These recent observations with pyrolytic graphite suggest that the pitting observed in the graphitized petroleum coke might be explained in terms of dislocation sites. A comparison of the graphitized petroleum coke structures with those of pyrolytic graphites shows numerous similarities. The similarity between the wavy and bowed lines seen in graphitized coke microstructures and in pyrolytic graphites suggests that the same growth mechanism responsible for the pyrolytic graphite structures is responsible for those seen in graphitized cokes. Figure 6 is a photomicrograph of a graphitized petroleum coke particle showing pitting along the curved basal planes.

SUGGESTIONS FOR FURTHER WORK

Since this investigation was of an exploratory nature, the significance of the results lies in the fact that it has revealed the existence of substructures in graphite which might be explained in terms of dislocation theory.

An obvious extension of this work would be the controlled application of stress to the pyrolytic graphite in order to determine whether there is motion of the etch pit sites due to the stress. This movement of etch pit sites would be expected if they represented dislocation sites.

The question should be resolved as to whether the mechanical polishing of the specimen prior to etching has created a cold worked layer. An attempt should be made to remove the polished layer by chemical means. Perhaps the oxidizing solution of potassium dichromate - phosphoric acid (Reference 6) used previously for etching graphites can be modified and used as an electropolishing chemical for this purpose.



OR



ATOMIC MODEL OF EDGE DISLOCATION IN GRAPHITE⁽³⁾

X - DENOTES MISSING ATOMS



CATHODIC ETCH

2000X

FIGURE 2: MULTIPLICATION OF ETCH PITS WHICH FORM SLIP LINE SEGMENTS (INDICATED BY ARROWS)



CATHODIC ETCH

2000X


FIGURE 3: INTERRUPTION OF SLIP AT THE GRAIN BOUNDARY INDICATED BY ARROW



CATHODIC ETCH

2000X

INITIATION OF SLIP AT THE TIP OF MICRO-CRACKS ALONG THE
BASAL PLANE (INDICATED BY ARROWS)



a



CATHODIC ETCH

b

2000X

LOW ANGLE TILT BOUNDARIES ALONG THE BASAL PLANE



CATHODIC ETCH
2000X
PITTING ALONG THE BASAL PLANES OF A GRAPHITIZED PETROLEUM COKE

REFERENCES

1. TSUZUKU, T., Dislocations in Graphite Crystals, Proceedings of the Conferences on Carbon, 1957, p. 433.
2. TSUZUKU, T., Origins of Dislocations in the Graphite Structure, Fourth Biennial Conference on Carbon, at University of Buffalo, Buffalo, New York, June 15-19, 1959.
3. GRENNALL, A., Dislocations in Graphite, Fourth Biennial Conference on Carbon, at University of Buffalo, Buffalo, New York, June 15-19, 1959.
4. DAWSON, I. M., and FOLLET, E. A. C., An Electron Microscope Study of Synthetic Graphite, Proceedings of the Royal Society, A, v. 253, 15 December 1959, p. 390.
5. TARPINIAN, A., Crystallographic and Microstructural Changes Occurring during the Graphitization of a Petroleum Coke, Watertown Arsenal Laboratories, WAL TR 825.5/1, January 1960.
6. TARPINIAN, A., and GAZZA, G. E., A Technique for the Microstructural Examination of Polycrystalline Graphites, Watertown Arsenal Laboratories, WAL TR 132.5/1, February 1959.

PB 150917 AD Accession No. _____ Watertown Arsenal Laboratories, Watertown 72, Mass. ETCH PITS IN PYROLYTIC GRAPHITE - Aram Tarpinian and George E. Gazza Report No. WAL TR 130.5/1, October 1960, 11 pp - illus OO Proj TB4-004, DA Proj 5B93-32-004, Unclassified Report The observation of pits in pyrolytic graphite after ion bombardment etching is described and their similarity to dislocation etch pits is speculated. Evidence of etch pit multiplication in the form of slip line segments and low angle tilt boundaries is presented. NO DISTRIBUTION LIMITATIONS PB 150917 AD Accession No. _____ Watertown Arsenal Laboratories, Watertown 72, Mass. ETCH PITS IN PYROLYTIC GRAPHITE - Aram Tarpinian and George E. Gazza Report No. WAL TR 130.5/1, October 1960, 11 pp - illus OO Proj TB4-004, DA Proj 5B93-32-004, Unclassified Report The observation of pits in pyrolytic graphite after ion bombardment etching is described and their similarity to dislocation etch pits is speculated. Evidence of etch pit multiplication in the form of slip line segments and low angle tilt boundaries is presented. NO DISTRIBUTION LIMITATIONS	UNCLASSIFIED 1. Metallography 2. Graphite 3. Dislocations in metals I. Tarpinian, Aram II. Gazza, George E. III. OO Proj TB4-004 IV. DA Proj 5B93-32-004	UNCLASSIFIED 1. Metallography 2. Graphite 3. Dislocations in metals I. Tarpinian, Aram II. Gazza, George E. III. OO Proj TB4-004 IV. DA Proj 5B93-32-004	UNCLASSIFIED 1. Metallography 2. Graphite 3. Dislocations in metals I. Tarpinian, Aram II. Gazza, George E. III. OO Proj TB4-004 IV. DA Proj 5B93-32-004
PB 150917 AD Accession No. _____ Watertown Arsenal Laboratories, Watertown 72, Mass. ETCH PITS IN PYROLYTIC GRAPHITE - Aram Tarpinian and George E. Gazza Report No. WAL TR 130.5/1, October 1960, 11 pp - illus OO Proj TB4-004, DA Proj 5B93-32-004, Unclassified Report The observation of pits in pyrolytic graphite after ion bombardment etching is described and their similarity to dislocation etch pits is speculated. Evidence of etch pit multiplication in the form of slip line segments and low angle tilt boundaries is presented. NO DISTRIBUTION LIMITATIONS PB 150917 AD Accession No. _____ Watertown Arsenal Laboratories, Watertown 72, Mass. ETCH PITS IN PYROLYTIC GRAPHITE - Aram Tarpinian and George E. Gazza Report No. WAL TR 130.5/1, October 1960, 11 pp - illus OO Proj TB4-004, DA Proj 5B93-32-004, Unclassified Report The observation of pits in pyrolytic graphite after ion bombardment etching is described and their similarity to dislocation etch pits is speculated. Evidence of etch pit multiplication in the form of slip line segments and low angle tilt boundaries is presented. NO DISTRIBUTION LIMITATIONS	UNCLASSIFIED 1. Metallography 2. Graphite 3. Dislocations in metals I. Tarpinian, Aram II. Gazza, George E. III. OO Proj TB4-004 IV. DA Proj 5B93-32-004	UNCLASSIFIED 1. Metallography 2. Graphite 3. Dislocations in metals I. Tarpinian, Aram II. Gazza, George E. III. OO Proj TB4-004 IV. DA Proj 5B93-32-004	UNCLASSIFIED 1. Metallography 2. Graphite 3. Dislocations in metals I. Tarpinian, Aram II. Gazza, George E. III. OO Proj TB4-004 IV. DA Proj 5B93-32-004

WATERTOWN ARSENAL
TECHNICAL REPORT DISTRIBUTION

Report No.: WAL TR 130.5/1

Title: Etch Pits in Pyrolytic Graphite

To:	No. of Copies
Commanding Officer Watertown Arsenal Watertown 72, Mass. Attn: ORDBE-LXM, Tech. Info. Section	5
OMRO, RPD	1
Authors	2
Office, Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTB-Res. & Materials	1
Director Army Research Office Department of the Army Washington 25, D. C.	1
Commanding General Ordnance Weapons Command Rock Island, Illinois Attn: ORDOW-IX	1
ORDOW-TX	2
Commanding General Aberdeen Proving Ground Aberdeen, Maryland Attn: Ballistic Research Lab.	1
ORDBG-LH, Tech. Library, Bldg. 313	1
Commanding General Army Ballistic Missile Agency Redstone Arsenal, Alabama Attn: ORDAB-DRF, Mr. W. A. Wilson	1
ORDAB-DSN, Dr. W. R. Lucas	5
Commanding General Army Rocket & Guided Missile Agency Redstone Arsenal, Alabama Attn: ORDAB-DV	1
ORDXR-OCF, Mr. R. L. Wetherington	5

Transmitted Date: OCT 26 1960

To:	No. of Copies
Commanding Officer Detroit Arsenal Center Line, Michigan Attn: ORDMX-BMW ORDMX-AL	 1 1
Commanding Officer Diamond Ordnance Fuze Laboratories Washington 25, D. C. Attn: ORDTL 06.33, Tech Ref. Sec.	 1
Commanding Officer Frankford Arsenal Bridge-Tacony Streets Philadelphia 37, Pa. Attn: ORDBA-1300	 2
Commanding Officer Ordnance Ammunition Command Joliet, Illinois Attn: ORDLY-AR	 1
Commanding General Ordnance Tank-Automotive Command 1501 Beard Street Detroit 9, Michigan Attn: ORDMC-RM.1	 1
Commanding General Ordnance Tank-Automotive Command Detroit Arsenal Center Line, Michigan Attn: ORDMC-RM.1, Mr. Charles Salter	 1
Commanding Officer Picatinny Arsenal Dover, New Jersey Attn: FREL	 1
Commanding Officer Redstone Arsenal Redstone Arsenal, Alabama Attn: Technical Library	 1
Commanding Officer Rock Island Arsenal Rock Island, Illinois Attn: Laboratory	 1

To:	No. of Copies
Commanding Officer Springfield Armory Springfield 1, Mass. Attn: ORDBD-TX	1
Commanding General U.S. Army Ordnance Special Weapons Ammunition Command Dover, New Jersey	1
Commanding Officer Watervliet Arsenal Watervliet, New York Attn: ORDBF-RT	1
The Director Jet Propulsion Laboratory California Institute of Technology Pasadena 3, California Attn: Dr. L. Jaffe	1
Commanding Officer Office of Ordnance Research Box CM, Duke Station Durham, North Carolina Attn: ORDOR-ED Dr. Peter Kosting	1 1
Army Reactor Branch Division of Research Development Atomic Energy Commission Washington 25, D. C.	1
Commander Armed Services Tech. Info. Agency Arlington Hall Station Arlington 12, Virginia Attn: TIPDR	10
Chief, Bureau of Aeronautics Department of the Navy Washington 25, D. C. Attn: TD Division	1
Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: Rep-3	1

To:	No. of Copies
Chief, Bureau of Ships Department of the Navy Washington 25, D. C. Attn: Code 592	1
Chief, Naval Eng. Exp. Station Department of the Navy Annapolis, Maryland	1
Commander, Naval Proving Ground Dahlgren, Virginia Attn: A&P Lab.	1
Director Naval Research Lab. Anacostia Station Washington 25, D. C. Attn: Tech. Info. Officer	1
Chief, Office of Naval Research Department of the Navy Washington 25, D. C. Attn: Code 423	1
Commander Wright Air Development Center Wright-Patterson Air Force Base, Ohio Attn: WCTRO WCRRL	1 1
U.S. Atomic Energy Commission Tech. Info. Service Ext. P.O. Box 62 Oak Ridge, Tennessee	15
National Aeronautics & Space Admin. 1520 H Street, N. W. Washington 25, D. C.	1
Defense Metals Information Center Battelle Memorial Institute Columbus, Ohio	1
Research Division Library Raytheon Company 28 Seyon Street Waltham 54, Massachusetts	1

TOTAL COPIES DISTRIBUTED - - 82

Total number of copies printed - 101

Extra copies to authors 10

Copies fwd to OTS 10/26/60 2

Copy for Publ. Editor 1

Extra copies fwd to Tech Dep Sec 6

Cy 4 - Aeronautical Systems Div Attch: ASNCEM-1
Mr Klinger, W-P AFB, Ohio Retention