

UNCLASSIFIED

AD NUMBER
ADB013563
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies only; Test and Evaluation; JUN 1974. Other requests shall be referred to Air Force Armament Laboratory, Attn: DLDE, Eglin AFB, FL 32542.
AUTHORITY
USADTC ltr, 5 Jun 1979


THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER EOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

AFATL-TR-74-104



**SOME SENSITIVITY AND PERFORMANCE
CHARACTERISTICS OF THE EXPLOSIVES
H-6 AND TRITONAL**

MASON AND HANGER - SILAS MASON COMPANY, INC.

TECHNICAL REPORT AFATL-TR-74-104

JUNE 1974

SEP 8 1976

Distribution limited to U. S. Government agencies only; this report documents test and evaluation; distribution limitation applied June 1974. Other requests for this document must be referred to the Air Force Armament Laboratory (DLDE), Eglin Air Force Base, Florida 32542.

AIR FORCE ARMAMENT LABORATORY

AIR FORCE SYSTEMS COMMAND • UNITED STATES AIR FORCE

EGLIN AIR FORCE BASE, FLORIDA



AD-B013563

**Some Sensitivity And Performance
Characteristics Of The Explosives
H-6 And Tritonal**

**R. J. Slape
J. A. Crutchner
G. T. West**

Distribution limited to U. S. Government agencies only;
this report documents test and evaluation; distribution
limitation applied June 1974. Other requests for
this document must be referred to the Air Force Armament
Laboratory (DLDE), Eglin Air Force Base, Florida 32542.

D D C
RECEIVED
SEP 8 1976
RECEIVED
D

FOREWORD

This project was conducted at the U. S. Atomic Energy Commission's Pantex Plant, which is located at Amarillo, Texas, and operated by Mason & Hanger - Silas Mason Co., Inc. (M&H-SM). All experimental work and analyses were performed by M&H-SM personnel of the Development Division at Pantex Plant under Project Order AT670D-2-0087 with the Air Force Armament Laboratory, Eglin Air Force Base, Florida. Dr. Larry O. Elkins (DLDE) served as project monitor for the Armament Laboratory.


Experimental work began in March 1972 and continued through June 1973.

The following personnel were responsible for the experimental work and/or the preparation of the report.

Project Scientist:	R. J. Slape
Development Scientists:	J. A. Crutchmer
	G. T. West

This technical report has been reviewed and is approved.

FOR THE COMMANDER



ALFRED D. BROWN, JR., Colonel, USAF
Chief, Guns, Rockets & Explosives Division

ABSTRACT

The purpose of this investigation was to determine the relative energies of H-6 and Tritonal as measured by the Lawrence Livermore Laboratory (LLL) Cylinder Test, a test which measures relative metal accelerating ability. The two explosives were also submitted to routine tests to determine thermal and handling characteristics. Both explosives were accepted for machining and general handling. One- and two-inch diameter cylinder tests were fired. Although a definite diameter effect was noted with H-6, no such effect was apparent with Tritonal. This report discusses the apparent discrepancy and includes recommendations for further testing. Tritonal and H-6 proved to be less energetic than Composition B, with H-6 more energetic than TNT and Tritonal less energetic than TNT.

Distribution limited to U. S. Government agencies only; this report documents test and evaluations; distribution limitation applied June 1974. Other requests for this document must be referred to the Air Force Armament Laboratory (DLDE), Eglin Air Force Base, Florida 32542.

TABLE OF CONTENTS

Section	Title	Page
I.	INTRODUCTION.....	1
II.	SUMMARY.....	2
III.	MACHINING AND GENERAL SAFETY.....	3
IV.	PERFORMANCE.....	7
	REFERENCES.....	14

LIST OF FIGURES

Section	Title	Page
1.	Tritonal Thermogram.....	4
2.	H-6 Thermogram.....	5
3.	Comparison of Wall Arrival Times for 1- and 2-Inch H-6 Cylinder Tests.....	10
4.	Comparison of Relative Wall Energies for 1- and 2-Inch H-6 Cylinder Tests.....	10
5.	Comparison of Wall Velocities for 1- and 2-Inch H-6 Cylinder Tests.....	10
6.	Comparison of Wall Arrival Times for 1- and 2-Inch Tritonal Cylinder Tests.....	11
7.	Comparison of Relative Wall Energies for 1- and 2-Inch Tritonal Cylinder Tests.....	11
8.	Comparison of Wall Velocities for 1- and 2-Inch Tritonal Cylinder Tests.....	11
9.	Relative Cylinder Wall Arrival Times Versus Expansion.....	12
10.	Cylinder Wall Velocity Versus Expansion.....	13
11.	Relative Cylinder Wall Energy Versus Expansion.....	13

SECTION I

INTRODUCTION

Tritonal and H-6 were tested to determine their relative energies as measured in the LLL Cylinder Test, a measure of metal accelerating ability. One- and two-inch-diameter test articles were fired to investigate diameter effects.

Thermal and impact sensitivity tests were conducted in order to determine the acceptability of H-6 and Tritonal for handling and machining at Pantex.

SECTION II

SUMMARY

Both H-6 and Tritonal were accepted for machining and general handling.

One- and two-inch-diameter cylinders were fired, and a definite diameter effect was observed with H-6. Tritonal did not exhibit a similar effect, and additional testing is recommended (a 2-inch and a 4-inch-diameter cylinder test) to resolve this apparent discrepancy. H-6 proved to be more energetic than Tritonal which, in turn, was less energetic than TNT. Composition B was more energetic than all three of the above.

SECTION III

MACHINING AND GENERAL SAFETY

In accordance with normal Pantex procedures, H-6 and Tritonal were submitted to impact sensitivity tests, differential thermal analysis, and chemical reactivity tests in order to obtain approval for machining.

Impact sensitivity results for Tritonal and H-6 are summarized in Table I, which also includes data for TNT for comparison.

TABLE I. IMPACT SENSITIVITY

<u>Explosive</u>	<u>50% Drop Height (cm)</u>
TNT	105
Tritonal	100
H-6	85

The tests and interpretation of results are discussed in other reports (1,2). Tritonal and H-6 are only slightly more sensitive than TNT and were accepted for handling and machining, subject to acceptable thermal sensitivities.

Differential Thermal Analysis (DAT) thermograms for Tritonal and H-6 are shown in Figures 1 and 2. The Tritonal thermogram is very similar to that of TNT and is considered to indicate comparable thermal stability. The H-6 thermogram indicates a melting endotherm characteristic of TNT and a rapid decomposition exotherm ($\sim 200^{\circ}\text{C}$) comparable to RDX.

The chemical stability of H-6 and Tritonal was determined by gas chromatography and the results are shown in Table II. Sample sizes are 250 milligrams, and tests are conducted at 120°C for 22 hours in a 15-psig helium atmosphere.




Figure 1. Tritonai Thermogram




Figure 2. H-6 Thermogram

Table II. Chemical Reactivity

<u>Explosives</u>	<u>Gas Evolved (Microliters) at STP</u>					<u>Total</u>
	<u>N₂</u>	<u>CO</u>	<u>NO</u>	<u>CO₂</u>	<u>N₂O</u>	
Tritonal	9.6	--	--	2.6	--	12.2
H-6	28.2	4.5	30.3	16.5	16.5	96.0

These data indicate much lower levels of reactivity when compared with PBXW-106 (348 microliters total) and PBXW-107 (274 microliters total), and Tritonal and H-6 were accepted for handling and machining.

SECTION IV

PERFORMANCE

Cylinder tests were used to measure the relative metal acceleration abilities and detonation velocities for Tritonal and H-6. The test, analysis, techniques, and interpretations of results are described elsewhere^(1,2). Nominal compositions, test densities, and resulting detonation velocities and Gurney constants are shown in Table III.

Table IV shows expansion wall arrival times and wall velocity data for the 1- and 2-inch diameter cylinder tests on H-6 and Tritonal, with 1-inch data for Composition B shown for comparison. Figures 3 through 7 are plots of the above data and of relative energies. Unfortunately, the 2-inch Tritonal cylinder broke up early (at about 19mm expansion), which made it virtually impossible to completely detect differences in energy due to the contribution of aluminum. The early breakup was attributed to visually detectable voids in the Tritonal samples provided for testing. Although the contribution of the aluminum is evident at fairly small expansions (about 12mm) in the H-6 test, there was no such contribution noted in the Tritonal test. There are at least three possible explanations:

1. Aluminum does not contribute to metal acceleration when it is used with an explosive that is as oxygen deficient as TNT (although it is evident in such late phenomena as cratering, air blast, underwater bubbles, etc.).
2. Aluminum has not contributed to the metal acceleration due to the small diameters tested, i.e., it might become evident in a 4-inch diameter test.
3. The aluminum did contribute in these tests, but only after 19mm, which would have been obscured by the breakup of the cylinder.

In order to reconcile the results, it is recommended that another 2-inch diameter test be conducted, with special precautions to ensure the absence of significant voids in the Tritonal. If there is no apparent contribution from the aluminum in the 2-inch test, then a 4-inch diameter cylinder test would be necessary to determine if the aluminum ever contributes to metal acceleration when used with TNT.

TABLE III. NOMINAL COMPOSITIONS, TEST DENSITIES, DETONATION VELOCITIES, AND GURNEY CONSTANTS

Explosives	TNT (%)	RDX (%)	D-2 Wax (%)	Aluminum (%)	Density (g/cc)	Detonation Velocity (m/sec)	C/M ^a	Gurney Constant ^b (m/sec)		
								5mm	19mm	26mm
H-6 (1")	30	45	5	20	1.76	7441	0.439	2000	2433	2517
H-6 (2")	30	45	5	20	1.76	7470	0.438	2035	2519	2636
Tritonal (1")	80	--	-	20	1.70	6430	0.424	1826	2249	2316
Tritonal (2")	80	--	-	20	1.69	6520	0.420	1816	2224	--
Composition B	36	64	-	--	1.717	7990	0.425	2350	2756	2821
TNT	100	--	-	--	1.630	6940	0.396	2039	2419	2505

^a $C/M = \left[\frac{1}{\left(\frac{OD}{ID} \right)^2} - 1 \right] \frac{\rho_c}{\rho_m}$, where ρ_c is explosive density, ρ_m is metal density and OD and ID are outside and inside diameters of the copper cylinder.

^b Gurney Constant, $G_i = V_i \sqrt{\frac{1 + 0.5 C/M}{C/M}}$, where V_i is the metal velocity at selected expansions.

TABLE IV. EXPANSION, TIME AND VELOCITY DATA FOR TRITONAL AND H-6

Expansion (mm)	Tritonal (1")		Tritonal (2") ^a		H-6 (1")		H-6 (2") ^a		Composition B	
	t (μsec)	v (mm/μsec)	t (μsec)	v (mm/μsec)	t (μsec)	v (mm/μsec)	t (μsec)	v (mm/μsec)	t (μsec)	v (mm/μsec)
4	4.92	1.05	5.07	1.03	4.40	1.15	4.35	1.17	3.77	1.32
5	5.86	1.08	6.03	1.07	5.25	1.20	5.18	1.22	4.51	1.39
6	6.77	1.11	6.94	1.11	6.07	1.24	5.98	1.27	5.22	1.44
7	7.66	1.14	7.83	1.14	6.86	1.28	6.76	1.30	5.91	1.47
8	8.52	1.17	8.70	1.16	7.63	1.31	7.52	1.33	6.59	1.49
9	9.37	1.19	9.55	1.19	8.39	1.33	8.26	1.36	7.26	1.50
10	10.21	1.21	10.38	1.21	9.14	1.35	8.99	1.38	7.92	1.52
11	11.03	1.23	11.20	1.23	9.87	1.37	9.71	1.40	8.57	1.53
12	11.84	1.25	12.00	1.25	10.60	1.38	10.42	1.42	9.22	1.55
13	12.63	1.26	12.79	1.27	11.32	1.40	11.12	1.44	9.86	1.57
14	13.42	1.28	13.58	1.28	12.03	1.41	11.82	1.46	10.50	1.58
15	14.20	1.29	14.36	1.29	12.74	1.42	12.49	1.47	11.13	1.59
16	14.97	1.30	15.14	1.30	13.44	1.43	13.17	1.48	11.75	1.62
17	15.74	1.31	15.91	1.30	14.14	1.44	13.84	1.49	12.37	1.62
18	16.49	1.33	16.67	1.31	14.83	1.45	14.52	1.50	13.00	1.62
19	17.24	1.33	17.43	1.31	15.52	1.46	15.17	1.51	13.60	1.63
20	17.99	1.34			16.20	1.47	15.83	1.52	14.22	1.64
22	19.47	1.36			17.56	1.48	17.14	1.54	15.43	1.65
24	20.94	1.37			18.90	1.50	18.42	1.56	16.64	1.66
26	22.40	1.37			20.23	1.51	19.70	1.58	17.84	1.67

^aSealing of a 2-inch cylinder to a 1-inch cylinder for a given expansion requires measurement of time as one-half the actual time at double that expansion, and measurement of velocity as actual velocity at double that expansion.




Figure 3. Comparison of Wall Arrival Times for 1- and 2-Inch H-6 Cylinders




Figure 4. Comparison of Relative Wall Energies for 1- and 2-Inch H-6 Cylinders




Figure 5. Comparison of Wall Velocities for 1- and 2-Inch H-6 Cylinders




Figure 6. Comparison of Wall Arrival Times for 1- and 2-Inch Tritonal Cylinders




Figure 7. Comparison of Relative Wall Energies for 1- and 2-Inch Tritonal Cylinders




Figure 8. Comparison of Wall Velocities for 1- and 2-Inch Tritonal Cylinders




Figure 9. Relative Cylinder Wall Arrival Times Versus Expansion




Figure 10. Cylinder Wall Velocity Versus Expansion




Figure 11. Relative Cylinder Wall Energy Versus Expansion

REFERENCES

1. G. T. West, C. C. Blair, G. L. Clink, J. H. Van Velkinburgh, "Some Sensitivity and Performance Characteristics of the Plastic Bonded Explosive PBXW-106," AFATL-TR-70-27.
2. G. T. West, C. C. Blair, G. L. Clink, R. J. Slape, "Some Sensitivity and Performance Characteristics of the Plastic Bonded Explosive PBXW-107," AFATL-TR-71-38.

INITIAL DISTRIBUTION

Hq USAF/RDQRM	2	Pantex Plant/Development Div	5
Hq USAF/SAMI	1	AFATL/DLOSL	2
AFSC/SDMM	1	AFATL/DLDE	5
Hq AFSC/DLCAN	1	ADTC/WE	1
AFIT/LD	1	ASD/ENYEHM	1
ASD/ENYS	1	Feltman Rsch Lab	3
AFWL/LR	1	Naval Ord Sys Comd	3
AUL/AUL-LSE-70-239	1		
Redstone Science Info Ctr/Doc Sec	2		
USA Wpns Comd/SARPI-LW-A	1		
AMXSY-DD	1		
AMXSY-A	1		
AMXPR-TB	1		
SARPA-TS	1		
USN Wpns Lab	1		
USN Nav Ord Lab/Tech Lib	2		
Nav Ord Stn/Tech Lib	1		
Nav Wpns Stn/20323	1		
Naval Sys Cntr/Tehc Lib	1		
USN Wpns Ctr/Code 533	2		
USNWC/Code 4565	1		
AFWL/Tech Lib	1		
Nav Air Sys Comd/Code AIR-5323	1		
Univ of Cal/Dept L-402	1		
Univ of Cal/Dept L-3	1		
Los Alamos Science Lab/Rpt Lib	1		
Chem Prop Info Agcy	2		
Battelle Mem Inst/Rpts Lib	1		
Inst for Def Analysis/Class Lib	1		
Sandia Labs/Div 5625	2		
DDC/TC	2		
Naval Wpns Lab	1		
Watervliet Ars/SARWV-RDT-L	1		
USNWC/Code 51102	1		
Ogden ALC/MMNOP	2		
Picatinny Ars/SARPA-FR-S-A	1		
US Atomic Energy Comm	1		
AEDC/ARO, Inc	1		
USA Material Sys Analysis Agcy			
AMXSY-DS	1		
Naval Rsch Lab/Code 2627	1		
TAWC/TRADOCLO	1		
AFATL/DL	1		
AFATL/DLY	1		
Aberdeen Pg Gd	2		

UNCLASSIFIED
Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) Mason & Hanger - Silas Mason Co., Inc. P. O. Box 647 Amarillo, Texas 79177		2a. REPORT SECURITY CLASSIFICATION Unclassified	
3. REPORT TITLE SOME SENSITIVITY AND PERFORMANCE CHARACTERISTICS OF THE EXPLOSIVES H-6 AND TRITONAL			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Final Report - March 1972 to June 1973			
5. AUTHOR(S) (First name, middle initial, last name) R. J. Slape J. A. Crutchmer G. T. West			
6. REPORT DATE June 1974	7a. TOTAL NO. OF PAGES 22	7b. NO. OF REFS 2	
8a. CONTRACT OR GRANT NO. Project Order No. AT6700-2-0087 a. PROJECT NO. 670A c. Task No. 03 d. Work Unit No. 029		8b. ORIGINATOR'S REPORT NUMBER(S) 8c. OTHER REPORT NOTE(S) (Any other numbers that may be assigned this report) AFATL-TR-74-104	
9. DISTRIBUTION STATEMENT Distribution limited to U. S. Government agencies only; this report documents test and evaluation; distribution limitation applied June 1974 . Other requests for this document must be referred to the Air Force Armament Laboratory (OLDE), Eglin Air Force Base, Florida 32542.			
11. SUPPLEMENTARY NOTES Available in DDC		12. SPONSORING MILITARY ACTIVITY Air Force Armament Laboratory Air Force Systems Command Eglin Air Force Base, Florida 32542	
13. ABSTRACT The purpose of this investigation was to determine the relative energies of H-6 and Tritonal as measured by the Lawrence Livermore Laboratory (LLL) Cylinder Test, a test which measures relative metal accelerating ability. The two explosives were also submitted to routine tests to determine thermal and handling characteristics. Both explosives were accepted for machining and general handling. One- and two-inch-diameter cylinders were fired. Although a definite diameter effect was noted with H-6, no such effect was apparent with Tritonal. This report discusses the apparent discrepancy and includes recommendations for further testing. Tritonal and H-6 proved to be less energetic than Composition B, with H-6 more energetic than TNT and Tritonal less energetic than TNT.			

UNCLASSIFIED

Security Classification

14	KEY WORDS	LINE A		LINE B		LINE C	
		ROLE	WT	ROLE	WT	ROLE	WT
	H-6 Explosive Tritonal Explosive Thermal and Handling Characteristics						