

UNCLASSIFIED

AD NUMBER
ADB286247
NEW LIMITATION CHANGE
TO Approved for public release, distribution unlimited
FROM Distribution authorized to U.S. Gov't. agencies only; Proprietary Info.; Aug 2002. Other requests shall be referred to U.S. Army Medical Research and Materiel Command, 504 Scott St., Ft. Detrick, MD 21702-5012.
AUTHORITY
USAMRMC ltr, dtd 28 July 2003

THIS PAGE IS UNCLASSIFIED

AD _____

Award Number: DAMD17-99-1-9329

TITLE: Integration of Digital Detectors into a Diffraction
Enhanced Imaging System

PRINCIPAL INVESTIGATOR: Miklos Z. Kiss
Doctor Dale E. Sayers

CONTRACTING ORGANIZATION: North Carolina State University
Raleigh, North Carolina 27695

REPORT DATE: August 2002

TYPE OF REPORT: Annual Summary

PREPARED FOR: U.S. Army Medical Research and Materiel Command
Fort Detrick, Maryland 21702-5012

DISTRIBUTION STATEMENT: Distribution authorized to U.S.
Government agencies only (proprietary information, Aug 02). Other
requests for this document shall be referred to U.S. Army Medical
Research and Materiel Command, 504 Scott Street, Fort Detrick,
Maryland 21702-5012.

The views, opinions and/or findings contained in this report are
those of the author(s) and should not be construed as an official
Department of the Army position, policy or decision unless so
designated by other documentation.

20030214 247

NOTICE

USING GOVERNMENT DRAWINGS, SPECIFICATIONS, OR OTHER DATA INCLUDED IN THIS DOCUMENT FOR ANY PURPOSE OTHER THAN GOVERNMENT PROCUREMENT DOES NOT IN ANY WAY OBLIGATE THE U.S. GOVERNMENT. THE FACT THAT THE GOVERNMENT FORMULATED OR SUPPLIED THE DRAWINGS, SPECIFICATIONS, OR OTHER DATA DOES NOT LICENSE THE HOLDER OR ANY OTHER PERSON OR CORPORATION; OR CONVEY ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE, OR SELL ANY PATENTED INVENTION THAT MAY RELATE TO THEM.

LIMITED RIGHTS LEGEND

Award Number: DAMD17-99-1-9329
Organization: North Carolina State University

Those portions of the technical data contained in this report marked as limited rights data shall not, without the written permission of the above contractor, be (a) released or disclosed outside the government, (b) used by the Government for manufacture or, in the case of computer software documentation, for preparing the same or similar computer software, or (c) used by a party other than the Government, except that the Government may release or disclose technical data to persons outside the Government, or permit the use of technical data by such persons, if (i) such release, disclosure, or use is necessary for emergency repair or overhaul or (ii) is a release or disclosure of technical data (other than detailed manufacturing or process data) to, or use of such data by, a foreign government that is in the interest of the Government and is required for evaluational or informational purposes, provided in either case that such release, disclosure or use is made subject to a prohibition that the person to whom the data is released or disclosed may not further use, release or disclose such data, and the contractor or subcontractor or subcontractor asserting the restriction is notified of such release, disclosure or use. This legend, together with the indications of the portions of this data which are subject to such limitations, shall be included on any reproduction hereof which includes any part of the portions subject to such limitations.

THIS TECHNICAL REPORT HAS BEEN REVIEWED AND IS APPROVED FOR PUBLICATION.

Carol B. Christian

12/30/02

REPORT DOCUMENTATION PAGEForm Approved
OMB No. 074-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE August 2002	3. REPORT TYPE AND DATES COVERED Annual Summary (1 Aug 99 - 31 Jul 02)	
4. TITLE AND SUBTITLE Integration of Digital Detectors into a Diffraction Enhanced Imaging System			5. FUNDING NUMBERS DAMD17-99-1-9329	
6. AUTHOR(S) Miklos Z. Kiss Doctor Dale E. Sayers				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) North Carolina State University Raleigh, North Carolina 27695 E-MAIL: mzkiss@unity.ncsu.edu			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Medical Research and Materiel Command Fort Detrick, Maryland 21702-5012			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution authorized to U.S. Government agencies only (proprietary information, Aug 02). Other requests for this document shall be referred to U.S. Army Medical Research and Materiel Command, 504 Scott Street, Fort Detrick, Maryland 21702-5012.				12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 Words) Images of calcifications embedded in breast tissue specimens have been obtained using a synchrotron based diffraction enhanced imaging (DEI) system and subsequently compared to images obtained using synchrotron-based radiography. Of the three specimens imaged, two contained calcifications associated with breast cancer and one was benign. The samples were imaged using 18 keV synchrotron radiation at the National Synchrotron Light Source (NSLS) at Brookhaven National Laboratory. The DEI images were obtained by placing a Silicon analyzer crystal tuned to the [333] plane in the beam path between the sample and the detector. Contrast of the calcifications is consistently higher in the DEI images when compared to the normal radiographs. This comparison, called the gain value, is the ratio of the peak contrast (or refraction contrast) to the conventional radiographic contrast. In all three specimens the gain values were consistently larger than one, indicating that image contrast using DEI is much higher than from conventional synchrotron-based radiography.				
14. SUBJECT TERMS diffraction enhanced imaging, radiographic contrast, refraction contrast			15. NUMBER OF PAGES 10	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unlimited	

Table of Contents

Cover	-
SF298	2
Table of Contents	3
Introduction	4
Annual Summary	4
Experimental Setup and Methods	4
Discussion of Results	5
Training Accomplishments	8
Key Research Accomplishments	8
Reportable Outcomes	8
Conclusions	8
References	8

Introduction

Images of calcifications in breast tissue specimens have been obtained a synchrotron-based DEI system [1, 2] and compared to images obtained using conventional synchrotron-based radiography. Three breast tissue specimens were imaged using 18 keV synchrotron radiation at the National Synchrotron Light Source (NSLS) at Brookhaven National Laboratory. The DEI images were obtained by placing a silicon analyzer crystal tuned to the [333] plane in the beam path between the sample and the detector. They showed improved contrast of the objects when compared to synchrotron-based radiographs. This comparison, called the DEI gain, is the ratio of the peak contrast (or refraction contrast) to the radiographic contrast. Experiments consistently resulted in gain values larger than one, indicating much higher contrast levels due to DEI. This is part of an ongoing effort to develop a clinical DEI prototype for mammography. One of the challenges in developing the prototype is choosing an optimal digital detector for integration into the system. The recent successes of in showing improved contrast of spiculations and lesions in breast tissue [3] has inspired similar studies to determine the contrast of calcifications. There is a well documented relationship between the presence of calcifications in the breast and breast cancer [4-6].

The samples imaged in this study were breast tissue specimens known to have calcifications. Of these specimens, one was a benign pathological sample. The other two were from mastectomies and contained invasive ductal carcinoma and lobular carcinoma, respectively. More than 100 calcifications in the three samples were analyzed, ranging in estimated sizes from 50 microns to 650 microns. Breast cancer has been connected to the presence of clusters of these small calcifications. It has been hypothesized that early detection can be improved by improving the image contrast of the calcifications.


Annual Summary

Experimental Setup and Methods

Experiments were carried out at the X-15A beamline, a general-purpose beamline at the National Synchrotron Light Source, Brookhaven National Laboratory, Upton, New York. A diagram of the apparatus is shown in figure 1.

The apparatus consisted of a double crystal Bragg monochromator that prepared an imaging beam of 1-mm height and 8-cm width. Images were obtained at 18 keV. The imaging beam was monitored by an ionization chamber to measure the skin entry dose to the various phantoms. Plastic absorbers were used to control the dose to the phantoms. A fast shutter system was used to control the exposure to the detector. The shutter opened when the scanning stage was at a constant velocity and was closed at the end of the scan range before the stage was slowed to a stop. The dose was controlled by a combination of incident beam Lucite absorbers and the scanning speed. For DEI images, an additional silicon [333] analyzer crystal was placed in the beam path between the sample and the detector. The analyzer was tuned by rotating it about its horizontal axis. A second ionization chamber measured the exit dose and the image was recorded using a Fuji HR5 image plate. The plates were read out using a Fuji BAS2500 Image Plate Reader.

Conventional radiographs were obtained by placing the image plate on the sample stage, perpendicular to the beam (as seen in figure 1a), and scanning the sample and plate together through the beam. DEI images were obtained by scanning the sample and the image plate in opposite directions (figure 1b). Raw images were obtained with the analyzer crystal tuned to the



Bragg angle (peak images), or on either side of the Bragg peak at angles corresponding the full-width half-maximum (FWHM) value of the rocking curve. The FWHM value for silicon [333] at 18 keV is approximately $3.6 \mu\text{radians}$.

In order to characterize the contrast of small calcifications in breast tissue imaged using DEI, three breast tissue specimens were chosen which were known to have calcifications. Table 1 summarizes the tissue samples and the number of calcifications analyzed in each.

Discussion of Results

Figure 2 shows the radiograph (a) peak image (b), refraction image (c) of sample 2. Numbered, red boxes surrounding the calcifications indicate which ones were analyzed. The refraction image is a composite of the images taken at either side of the rocking curve and combined according to the following relation:

$$\Delta\theta_z = \frac{I_H R(\theta_L) - I_L R(\theta_H)}{I_L \left. \frac{dR}{d\theta} \right|_{\theta_H} - I_H \left. \frac{dR}{d\theta} \right|_{\theta_L}}, \quad (1)$$

where I_H and I_L are the radiation intensities of the images taken on the high-angle and low-angle sides of the rocking curve, respectively. $R(\theta_H)$ and $R(\theta_L)$ are the reflectivities of the rocking curve on the respective sides and $dR/d\theta$ are the first derivatives of the rocking curve at the respective angles. The term $\Delta\theta_z$ is applied on a pixel-by-pixel basis. It is clear from the images that the contrast in the peak is much higher than for the radiograph.

Contrast was determined by measuring values for the minimum, maximum and/or background from several vertical line profiles in each image. The radiographic contrast is defined by,

$$C_{rad} = \frac{I_{avg} - I_{min,rad}}{I_{avg}}, \quad (2)$$

where I_{avg} is the average background in the image, and I_{min} is the minimum value in the object. The peak contrast is given by,




Figure 2. Peak images of the three tissue samples: a) synchrotron-based radiograph, b) peak image, c) refraction image. The numbered, red boxes indicate the calcifications, which were identified and analyzed.

$$C_{peak} = \frac{I_{avg} - I_{min,peak}}{I_{avg}}, \quad (3)$$

with similar definitions as in equation 2.

In addition to the definition of contrast, signal-to-noise ratios (SNR) have been defined for both the refraction image as well as the radiographic image. The SNR in the refraction image is given by

$$SNR_{ref} = \frac{R_{max} - R_{min}}{\sigma_{avg}}, \quad (4)$$

where R_{max} and R_{min} are the maximum and minimum values in the refraction image, and σ_{avg} is the noise level in the background. The noise has been defined as one standard deviation from the mean. Similarly, the SNR for the radiograph is given by,

$$SNR_{rad} = \frac{I_{avg} - I_{min}}{\sigma_{avg}}, \quad (5)$$

where all the terms are defined above

In comparing the DEI results to the radiographic results, a quantity, called the gain value is defined. For the peak image, the gain is obtained by taking the ratio of the peak contrast to the radiographic contrast:

$$G_{peak} = \frac{C_{peak}}{C_{rad}}, \quad (6)$$

while for the refraction image, the gain is obtained by taking the ratio of the refraction SNR to the radiographic SNR, or,

$$G_{ref} = \frac{SNR_{ref}}{SNR_{rad}}. \quad (7)$$

Figure 3 shows scatter plots of the contrast versus the calcification size for all three samples (samples 1 – 3 shown top to bottom). The comparison in each plot is of the peak contrast with the radiographic contrast. For each sample, regression lines have been fit to the data and the slopes are given. It is clear from the graphs that the peak contrast is consistently higher than the radiographic contrast, regardless of the calcification size. This higher contrast is




Figure 3. Experimental results. Sample 1 (top), sample 2 (middle), sample 3 (bottom). Slopes are for regression lines fit through the origin.

a direct consequence of the scatter rejection by the analyzer crystal. It is also apparent that the radiographic contrast points tend to lie closer to their regression line than images. This is due in part to the fact that DEI is more sensitive to the uniformity of the calcifications as well as the scatter rejection capability of DEI, which results in the exploitation of additional contrast mechanisms not possible with conventional radiographic techniques. Calcifications tend to be an agglomeration of material of varying homogeneity, which results in varying scatter rejection signatures in DEI. The ratio of the peak slope to the radiograph slope is approximately equal to the average gain value. In general, the gain value is size dependent, but for the specimens studied, this dependence was approximate. Table 1 lists a few of the pertinent results.

Table 1 – Breast Tissue Specimen Results

Sample	Type	No. Calcs	C_{peak} slope	C_{rad} slope	Slope ratio	Avg. G_{peak}
1	Benign	51	1.394	0.218	6.4	6.9 ± 0.4
2	Inv. Carc.	36	1.086	0.620	1.75	1.9 ± 0.1
3	Lob. Carc.	25	0.937	0.173	5.4	7.6 ± 1.8

• Training Accomplishments

As a result of the efforts of the past year, a great deal of training value has been gained. Expertise in conducting DEI experiments and proficiency of synchrotron beamline operations have been achieved. These skills have been useful in developing a doctoral dissertation and in training individuals joining the DEI collaboration. The project has also generated new image processing techniques and has resulted in the improvement of existing ones. This is important because DEI is still a relatively new imaging modality. These new techniques will prove invaluable to future researchers as the technique is implemented in the clinic.

Key Research Accomplishments

- Improved and refined the method for quantifying contrast in images obtained using DEI
- Compared DEI contrasts to conventional radiographic contrast and demonstrated the superiority of DEI over conventional radiography with respect to contrast enhancement
- Developed computational techniques for modeling DEI images and for predicting image contrast, especially at near-pixel-sized objects

Reportable Outcomes

- A paper was submitted and accepted for publication (to be published in October 2002): Kiss M.Z., Sayers D.E., Zhong Z., "Comparison of digital detectors for integration into a diffraction-enhanced imaging system," Nucl. Instr. and Meth. A 491 (2002) 165 – 175.
- It is intended that the results of this work will be submitted for publication

Conclusions

This findings in this study clearly demonstrate the ability of DEI to produce higher contrast images when compared with conventional radiographs. This is true even as the object size is approaches the size of a detector pixel (or its PSF). Conventional radiographic contrast suffers in this regime more than enhanced contrast. This becomes important for determining an optimal detector for a clinical DEI device. Further investigations will most likely include chemical composition studies of the calcifications and how this relates to formation and their subsequent imaging. While it is understood that radiographic imaging modalities are currently non-specific for chemical composition of a calcification, it may be possible to determine a relationship between the composition of calcifications and their imaging characteristics.

References

1. Chapman D., Thomlinson W., Johnston R.E., Washburn D., Pisano E., Gmur N., Zhong Z., Menk R., Arfelli F., and Sayers D., "Diffraction Enhanced x-ray Imaging," Phys. Med. Biol. 42 (1997) 2015-2025.

2. Zhong Z., Thomlinson W., Chapman D., Sayers D., "Implementation of Diffraction Enhanced Imaging Experiments at the NSLS and APS," Nucl. Instr. and Meth. A, **450** (2000) 556-567.
3. Pisano E.D., Johnston R.E., Chapman D., Geradts J., Iacocca M., Livasy C.A., Washburn D.B., Sayers D.E., Zhong Z., Kiss M.Z., Thomlinson W.C., "Human Breast Cancer Specimens: Diffraction Enhanced Imaging with Histologic Correlation – Improved Conspicuity of Lesion Detail Compared with Digital Radiography," Radiology **214** (2000) 895-901.
4. Olson S.L., Fam B.W. Winter P.F., Scholz F.J., Lee A.K., Gordon S.E., "Breast calcifications: analysis of imaging properties," Radiology **169** (1988) 329 – 332.
5. Radi M.J., "Calcium Oxalate Crystals in Breast Biopsies," Arch. Pathol. Lab Med. **113** (1989) 1367-1369.
6. Surratt J.T., Monsees B.S., Mazoujian G., "Calcium oxalate microcalcifications in the breast," Radiology **181** (1991) 141 – 142.



DEPARTMENT OF THE ARMY
US ARMY MEDICAL RESEARCH AND MATERIEL COMMAND
634 SCOTT STREET
FORT DETRICK, MARYLAND 21702-5012

REPLY TO
ATTENTION OF:

MCMR-RMI-S (70-1y)

28 July 03

MEMORANDUM FOR Administrator, Defense Technical Information
Center (DTIC-OCA), 8725 John J. Kingman Road, Fort Belvoir,
VA 22060-6218

SUBJECT: Request Change in Distribution Statement

1. The U.S. Army Medical Research and Materiel Command has reexamined the need for the limitation assigned to technical reports written for this Command. Request the limited distribution statement for the enclosed accession numbers be changed to "Approved for public release; distribution unlimited." These reports should be released to the National Technical Information Service.

2. Point of contact for this request is Ms. Kristin Morrow at DSN 343-7327 or by e-mail at Kristin.Morrow@det.amedd.army.mil.

FOR THE COMMANDER:

Encl


PHYLLIS M. RINEHART
Deputy Chief of Staff for
Information Management

ADB233865	ADB264750
ADB265530	ADB282776
ADB244706	ADB286264
ADB285843	ADB260563
ADB240902	ADB277918
ADB264038	ADB286365
ADB285885	ADB275327
ADB274458	ADB286736
ADB285735	ADB286137
ADB286597	ADB286146
ADB285707	ADB286100
ADB274521	ADB286266
ADB259955	ADB286308
ADB274793	ADB285832
ADB285914	
ADB260288	
ADB254419	
ADB282347	
ADB286860	
ADB262052	
ADB286348	
ADB264839	
ADB275123	
ADB286590	
ADB264002	
ADB281670	
ADB281622	
ADB263720	
ADB285876	
ADB262660	
ADB282191	
ADB283518	
ADB285797	
ADB269339	
ADB264584	
ADB282777	
ADB286185	
ADB262261	
ADB282896	
ADB286247	
ADB286127	
ADB274629	
ADB284370	
ADB264652	
ADB281790	
ADB286578	